



河南矿山
HENANMINE



Lifting Hooks and Rigging Hooks



HENAN KUANGSHAN CRANE CO.,LTD

Web: www.kscranegroup.com

Email: sales@kscranegroup.com

G100 COMPONENTS 100级 索具配件

- ◆ REGULAR MARK OF G100 components from SLR
- ◇ 来自于SLR认证的100级索具配件打号标准
- ◆ For example: G100 EYE BELL LOCK HOOK 10-10
- ◇ 以100级索具配件20-100为例



Regular mark 常规标记:

MARK 标记	10	-10	WLL 4T	SLR	CE	10-1
DESCRIPTION 说明	10 TON RING 100吨环	GRADE 101 92.5%Zn	WORKING LOAD LIMIT 工作力	MANUFACTURER 生产商	CE CERTIFICATE 认证书	MARK NUMBER 打号

G100 SWIVEL SELFLOCKING HOOK WITH BEARING 100级 带轴承旋转安全钩


- ◆ Forged super alloy steel: Quenched and Tempered
- ◆ 高强度合金特种合金钢锻造而成, 经过热处理
- ◆ Suitable for G100 chain
- ◆ 与100级链条配合使用
- ◆ 25% stronger than G80
- ◆ 比G80级产品强度提升25%
- ◆ Individually proof test at 2.5 times Working Load Limit
- ◆ 每件按工作拉力2.5倍进行验证测试
- ◆ Fatigue tested at 1.5 times Working Load Limit for 20000 cycles
- ◆ 在1.5倍工作拉力下循环进行20000次疲劳测试
- ◆ Breakage test: 对每一批次产品进行严格的破坏性测试
- ◆ 100% magnifying crack detection
- ◆ 100% 进行微裂纹检测
- ◆ Surface finish (表面处理): Powder painted (喷涂)
- ◆ Colour code (色号): Blue (蓝色) RAL5015



- ◆ Positive lock with selflocking when hook is loaded
- ◆ 在负载下, 钩子的锁紧机构会自动锁死, 更安全



SLR1072-G100 SWIVEL SELFLOCKING HOOK WITH BEARING 100级 带轴承旋转安全钩




ITEM CODE	WEIGHT (KG)	WLL (T)	BL (T)	Ax15	8x15	Cx2	Dx2	Ex15	Nx1	Hx3	Kx3	Lx5	Wx5
8-90	0.87	1.4	5.8	11.5	13	27	27	30	15	32	169	106.5	71
8-10	1.21	2.5	10	13	25	41	35.5	40	20	38	202	243	51
10-10	2.2	4	18	15.5	17.5	48	45	45	25	40	284	239	105
10-15	3.1	6.3	25.5	17	19	55	57.8	55	30.5	57	207	351	148
16-10	7.35	10	40	21.5	30	92	92	71	39	92	547	425	170
20-10	13.75	18	64	26.5	25.5	76	76	50	50	73	361	417	191
22-15	15.51	19	70	30	34	97	79	65	92	92	459	503	205

G100 CLEVIS SLING HOOK 100级 羊角吊钩

- Forged super alloy steel - Quenched and Tempered
- 高强度合金钢锻造 淬火回火处理
- Suitable for G100 chain
- 与100级链条配合使用
- 25% stronger than G55
- 比G55级产品性能提升25%
- Individually proof test at 2.5 times Working Load Limit
- 逐件按工作拉力的2.5倍进行验证测试
- Fatigue tested at 1.5 times Working Load Limit for 25,000 cycles
- 抽样进行25,000次疲劳测试
- Immersion test for every batch of products for surface crack detection
- 100% magnifying crack detection
- 100% 进行裂纹检测
- All load pins are 100% individually inspected and tested
- 所有销轴进行100%测试，确保所有的强度合规
- Surface finish (表面处理): Powder painted (涂层)
- Color code (色号): Blue (蓝色)RAL6015
- With cast latch 配有铸造可配件



SLR1004-G100 CLEVIS SLING HOOK WITH CAST LATCH 100级 羊角吊钩 (含铸造销片)



ITEM CODE	WEIGHT (KG)	WLL (T)	S.L (T)	A±0.5	B±1	E±1.5	H±1	M±2	L±2.5
10-SLR1004-06	0.88	1.4	5.9	2.5	42	13.5	21	83.5	100
10-SLR1004-08	0.7	2.5	10	5.5	57	25	27.5	98	104
10-SLR1004-10	1.3	4	10	12	43	21	33.5	105.5	161.5
10-SLR1004-13	2.3	6.7	26.5	15	50	36	43	134	210
10-SLR1004-16	2.6	10	40	15.5	70	44	50	160.5	248
10-SLR1004-20	7	15	64	25	95	50	55	166.5	297
10-SLR1004-22	12.1	15	75	27	110	55	62	214.5	325

Ultimate load is 4 times the Working Load Limit 极限拉力是工作拉力的4倍。

Regular mark (常规标记): 10-10-10: 4 T CR SLR-4 LATCH (100MM) (色号)

SP-SLR1004 - SPARE PART FOR SLR1004 (LOAD PIN) SLR1004的销轴配件



ITEM CODE	SIZE 规格	ITEM CODE 型号	SIZE 规格
SP-SLR1004-6	6-10	SP-SLR1004-20	20-10
SP-SLR1004-8	8-10	SP-SLR1004-22	22-10
SP-SLR1004-10	10-12		
SP-SLR1004-13	13-12		
SP-SLR1004-16	16-12		

1 SET = 1 BLACK PIN + 2 BLACK SPRING TYPE STRAIGHT (1 PIN) 1套=1个黑销轴+2个黑直筒弹簧销轴

NOTICE 注意: Please read the instruction carefully before use.

WARNING 警告




G100 CLEVIS C TYPE HOOK 100级 C型钩

- ◆ Forged super alloy steel—Quenched and Tempered
◇ 高级合金钢锻造并经回火处理，经过热处理
- ◆ Suitable for G100 chain
◇ 与100级链条配合使用
- ◆ 25% stronger than G80
◇ 比80级产品性能提升25%
- ◆ Fatigue tested at 1.5 times Working Load for 2000 cycles
◇ 在1.5倍工作拉力下能样进行2000次疲劳测试
- ◆ Breakage test
◇ 对每一批产品进行严格的破坏性测试
- ◆ 100% magnetic crack detection
◇ 100%进行磁粉探伤
- ◆ All holes pre-drilled 50% individually inspected and drilled
◇ 所有预钻孔进行100%的测试，确保孔的精度和质量



SLR1071-G100 CLEVIS C TYPE HOOK C 型钩



ITEM CODE	WEIGHT (kg)	WLL (T)	BP (T)	A±0.5	B±1	C±3	H±1	L±3	M±0.5	E±1
10-SLR1071-B	0.54	3.5	10	25	35.5	21.5	27.3	125.5	8.5	20.5
10-SLR1071-10	1.05	4	10	32.5	48.5	37	32.6	150	12	37

Use with Part 4 to as the Working Load Limit 按照拉力最大工作拉力的4倍

Regular mark 常规标记:

MARK 标志	10	-10	WLL 4T	SLR	CE	10-1
DESCRIPTION 说明	CHAIN SIZE 链条尺寸	GRADE 90 90级链条	WORKING LOAD LIMIT 工作拉力	MANUFACTURER 生产商	CE CERTIFIED CE 认证	WATCH WEARER 生产批号



WARNING 警告 This is a safety product. Please use it correctly and do not exceed the rated load.

G100 SELFLOCK HOOK 100级 自锁钩

- ◆ Forged super alloy steel - Quenched and tempered
- 锻造合金钢经淬火及回火处理
- ◆ 25% stronger than G80
- 比G80级产品性能提高25%
- ◆ Individually proof test at 2.5 times Working Load Limit
- 每件钩工作拉力前均进行验证测试
- ◆ Fatigue tested at 1.5 times Working Load Limit for 20000 cycles
- 有1.5倍工作拉力下运转进行20000次疲劳测试
- ◆ Breakout test
- 对每一批次产品进行严格的拉伸破断测试
- ◆ 100% magnetic crack detection
- 100% 磁粉探伤检测
- ◆ All load pins are 100% individually inspected and tested
- 所有销轴进行100%测试，确保无裂纹等瑕疵
- ◆ Surface finish (表面处理): Powder painted (喷漆)
- ◆ Colour code (色号): Blue (蓝色)RAL5015
- ◆ Positive latching is selflocking when hook is turned
- 在转动下，钩子的自锁结构会自动闭合，很安全



SLR1005-G100 EYE SELFLOCK HOOK 100级 眼型自锁钩

SLR1005

ITEM CODE	WEIGHT (KG)	WLL (T)	SL (T)	A	D	E	F	R	M	N	L	H
10-SLR1005-06	0.5	1.4	0.6	21x1	27x1	24x2	31x2	36x4	21x2	36x1	141x4	1341
10-SLR1005-07	0.21	1.0	2.0	21x1	21x1	21x2	34x2	32x4	21x2	21x1	102x4	1211
10-SLR1005-08	0.8	2.5	5.0	27x1	27x1	24x2	42x2	32x4	27x2	27x1	126x4	1211
10-SLR1005-10	1.5	4	8	33x2	33x2	24x2	48x2	32x4	33x2	27x2	126x4	1311
10-SLR1005-18	2.7	6.7	26.8	42x2	42x2	34x4	42x4	32x4	32x4	27x4	126x4	1311
10-SLR1005-16	5.7	10	40	42x4	42x4	34x4	34x4	32x4	32x4	27x4	126x4	1311
10-SLR1005-20	7.0	10	34	42x2	42x2	34x4	34x4	32x4	32x4	27x4	126x4	1311
10-SLR1005-22	11.3	19	20	36x2	36x2	34x4	34x4	32x4	32x4	27x4	126x4	1311
10-SLR1005-26	20.6	26.8	106	42x4	42x4	34x4	34x4	32x4	32x4	27x4	126x4	1311

Ultimate load is 4 times the Working Load Limit. 破断拉力是工作拉力的4倍。

Regular mark 常规标记:

MARK 标志	10	-10	WLL 4T	SLR	CE	10-T
DESCRIPTION 说明	CLASS 规格	GRADE 等级	WORKING LOAD LIMIT 工作拉力	MANUFACTURER 生产商	CE CERTIFIED CE 认证	SAFETY MARKING 安全标志



WARNING 警告 Please refer to the instruction manual for correct use and safety precautions.

G100 SELFLOCK HOOK 100级 自锁钩

- ◆ Forged super alloy steel - Quenched and Tempered
○ 高强度合金钢材料经淬火及回火处理，经过热处理
- ◆ Suitable for G100 chain
○ 与100级链条配合使用
- ◆ 25% stronger than G80
○ 比G80级产品强度提高25%
- ◆ Individually proof-tested at 2.5 times Working Load Limit
○ 每件工作拉力时2.5倍进行验证测试
- ◆ Fatigue tested at 1.6 times Working Load Limit for 20,000 cycles
○ 在1.6倍工作拉力下持续进行20,000次疲劳测试
- ◆ Breakage test
○ 对每一批次产品进行严格的破坏性测试
- ◆ 100% microcrack detection
○ 100% 进行裂纹检测
- ◆ All load pins are 100% individually inspected and tested
○ 所有销轴进行100%测试，确保达到最高品质
- ◆ Surface finish (表面处理) : Powder painted (电泳)
- ◆ Colour code (色号) : Blue (蓝色)RAL5015



- ◆ Positive lock catch is selflocking when hook is closed
○ 在关闭下，钩子自锁功能即自动启动，更安全

SLR1006-G100 CLEVIS SELFLOCK HOOK 100级 羊角型自锁钩

SLR1006

ITEM NO.	WEIGHT (kg)	WLL (T)	S.L (T)	A	B	E	F	R	M	N	L
10-SLR1006-05	0.5	1.4	5.4	23x5	37x13	23x2	23x22	26x4	71x8	35x7	111x4
10-SLR1006-08	0.9	2.0	10	13x15	28x12	20x3	42x2	17x4	50x7	30x7	92x4
10-SLR1006-10	1.4	4	15	19x24	34x16	45x2	45x2	24x5	55x7	34x7	104x5
10-SLR1006-13	2.5	8.2	24.5	15x7	34x15	55x2x1	55x4	32x5	55x7	32x5x1	151x5
10-SLR1006-16	5.5	10	40	15x7	35x2	67x4	74x4	23x5	74x7	35x7	107x5
10-SLR1006-18	9.5	12.5	50	22x7	38x3	73x4	73x4	22x5	73x7	44x7	123x5
10-SLR1006-20	2.5	10	34	30x15	55x2	73x4	80x4	23x5	73x7	30x5	107x7
10-SLR1006-22	12.1	19	70	54x7	50x7.5	74x4	104x5	27x5	104x7	52x5	154x5
10-SLR1006-26	21.15	26.5	100	35x7	115x2.5	66x4	117x5	32x5	121x7	57x7	169x5

Ultra-low hook is 4 times the working load limit. 超低位钩工作力为4倍。

Regular hook (常规钩) : 10-15 20, 4.7 6.2 10 R + 24CHY (M8R) (常规)

SP-SLR1006-SPARE PART FOR SLR1006 SLR1006的钩配件

ITEM CODE 编号	SIZE 规格	ITEM CODE 编号	SIZE 规格
SP-SLR1006-5	5-10	SP-SLR1006-10	10-20
SP-SLR1006-8	8-10	SP-SLR1006-20	20-50
SP-SLR1006-10	10-10	SP-SLR1006-22	22-50
SP-SLR1006-13	13-10		



G100 ROTATE SAFETY HOOK 100级 旋转安全钩

- ◆ Forged super alloy steel, Quenched and Tempered
◊ 高强度合金钢锻造而成，经过回火处理
- ◆ Suitable for G100 chain
◊ 与100级链条配合使用
- ◆ 25% stronger than G80
◊ 比G80级产品强度提升25%
- ◆ Individually proof test at 2.5 times Working Load Limit
◊ 每件按工作拉力2.5倍进行验证测试
- ◆ Fatigue tested at 1.5 times Working Load Limit for 20000 cycles
◊ 抽样进行2000次疲劳测试
- ◆ Breakage test: 对每一批次产品进行严格的破坏性测试
- ◆ 100% magniflux crack detection
◊ 100% 进行磁粉探伤
- ◆ Surface finish (表面处理): Powder painted (喷涂)
- ◆ Colour code (颜色): Blue (蓝色)RAL5015



- ◆ Positive indication is releasing when hook is loaded
◊ 在负载下，钩子的旋转机构会自动锁定，更安全

SLR1007-G100 ROTATE SAFETY HOOK 100级 旋转安全钩

SLR1007

ITEM CODE	WEIGHT (KG)	WLL (T)	SL (T)	B	C	D	E	F	M	N	K	L
10-SLR1007-06	0.0	1.4	6.6	27.42	26.27	11.57	32.25	23.22	29.1	22.7	19.54	19.25
10-SLR1007-08	1.1	2.5	10	31.42	28.27	12.1	36.42	25.22	33.1	25.7	22.54	22.25
10-SLR1007-10	2	4	16	37.42	33.27	13.17	42.42	29.22	38.17	31.42	25.94	25.12
10-SLR1007-13	4	6.7	25.8	44.42	41.42	17.42	50.42	35.42	45.42	37.42	30.42	30.12
10-SLR1007-16	8.2	10	40	51.42	48.42	21.42	57.42	41.42	53.42	43.42	35.42	35.12
10-SLR1007-20	12.5	16	64	59.42	56.42	26.42	65.42	48.42	61.42	51.42	41.42	41.12
10-SLR1007-22	17.1	18	72	67.42	64.42	27.42	73.42	54.42	67.42	57.42	45.42	45.12
10-SLR1007-26	31.2	23.6	100	73.42	70.42	32.42	79.42	61.42	75.42	65.42	51.42	51.12

Upward load is 4 times the Working Load Limit. 垂直向上工作拉力为4倍。
Regular mark (常规标记): 10-10 WLL 4 T CE SLR + BATCH NUMBER (批号)

Regular mark 常规标记:

MARK 标志	10	-10	WLL 4T	SLR	CE	10-1
CE MARKING 标志	CE MARKING 标志	CE MARKING 标志	WORKING LOAD LIMIT 工作拉力	MANUFACTURER 生产商	CE CERTIFIED CE 认证合格	BATCH NUMBER 生产批号



WARNING 警告 This product is not to be used for lifting personnel.



G100 SPECIAL EYE SELFLOCKING HOOK 100级 异型眼型安全钩

- ◆ Forged super alloy steel, Quenched and Tempered
 - 高级合金钢经特殊合金锻造而成，经过热处理
- ◆ 25% stronger than G80
 - 比G80级产品性能强25%
- ◆ Individually proof test at 2.5 times Working Load Limit
 - 每件在工作拉力的2.5倍进行验证测试
- ◆ Fatigue tested at 1.5 times Working Load Limit for 20000 cycles
 - 在1.5倍工作拉力下循环进行20000次疲劳测试
- ◆ Breakage test
 - 对每一件产品进行严格的破坏性测试
- ◆ 100% magnetic crack detection
 - 100% 进行磁粉探伤
- ◆ Surface finish (表面处理): Powder coated (喷塑)
 - ◆ Colour/codex (颜色): Blue (蓝色)RAL 9015
- ◆ Positive lock, latch is selflocking when hook is loaded.
 - 在其荷下，钩子的自锁结构能自动闭合，更安全



SLR1015-G100 SPECIAL EYE SELFLOCKING HOOK
100级 异型眼型安全钩

SLR1015

ITEM NO.	WEIGHT (kg)	WLL (T)	B.L (T)	S	Φ	G	K	H	ΦD	N	M	L
10-SLR1010-08	0.81	2.5	50	27x27	11x13	8x12	18x13	21x1	11x1	25x2	8x12	14x12
10-SLR1010-10	1.23	4	90	38x1	18x13	11x1	18x14	25x15	14x1	30x15	15x17	25x13
10-SLR1010-13	2.51	9.2	20.5	55x13	4x12	17x12	25x14	35x15	25x1	40x15	25x17	38x14
10-SLR1010-16	4.45	16	40	75x1	25x15	19x13	35x14	45x17	32x1	50x17	38x17	55x14

WLL means load is 4 times the Working Load Limit. 破断拉力为工作拉力的4倍

Regular mark (常规标记): 10-10 YELLOW CE SLR + BATCH NUMBER (批号)

Regular mark 常规标记:

MARK 标志	10	-10	WLL 4T	SLR	CE	10-1
CE MARKING 标志	CE MARK 标志	CE MARK 标志	WORKING LOAD LIMIT 工作拉力	MANUFACTURE 生产商	CE MARKING CE 认证标志	BATCH NUMBER 批号



WARNING 警告 This is a lifting device and must be used in accordance with the instructions.

G100 SPECIAL CLEVIS SELFLOCKING HOOK 100级 异型羊角安全钩

- Forged super alloy steel - Quenched and Tempered
- 高强度合金材料经淬火及回火处理而成，经过热处理
- Suitable for G100 chain
- 与100级链条配合使用
- 25% stronger than Q80
- 比Q80级产品性能提高25%
- Individually proof-tested at 2.5 times Working Load Limit
- 每件安全工作拉力时2.5倍进行验证测试
- Fatigue tested at 1.6 times Working Load Limit for 20,000 cycles
- 在1.6倍安全工作拉力下抽样进行20000次疲劳测试
- Breakage test
- 对每一批次产品进行严格的破坏性的测试
- 100% integrated crack detection
- 100% 进行综合检测
- Surface finish (表面处理): Powder-plated (电镀)
- Colour code (色号): Blue (蓝色) (RAL 5015)



- Positive lock latch is selflocking when hook is loaded
- 在负荷下，钩子的自锁结构会自动锁合，更安全

SLR1017-G100 SPECIAL CLEVIS SELFLOCKING HOOK 100级 异型羊角安全钩

SLR1017



ITEM NO.	WEIGHT (kg)	WLL (T)	B.L. (T)	A	B	C	H	G	N	M	K
10-SLR1017-08	0.8	0.5	0.5	84.7	124.2	254.5	141	84.2	714.1	84.2	184.2
10-SLR1017-10	1.2	0.7	0.7	104.2	164.2	314.7	174.5	104.2	884.5	104.2	204.2
10-SLR1017-13	2.0	1.2	1.3	134.4	204.2	414.5	214.8	134.2	1114.5	134.2	254.2
10-SLR1017-16	4.1	2.0	2.0	164.4	254.2	514.5	254.8	164.2	1314.5	164.2	304.2

Upgraded load is 4 times the Working Load Limit. 升级拉力是安全工作拉力的4倍

Regular mark (常规标记): 10-1616147 OF CLR - BATCH NUMBER (批号)

Regular mark 常规标记:

MARK 标记	10	-10	WLL 4T	SLR	CE	10-1
ORIGIN 产地	CHINA 中国	CHINA 中国	WARRICK, ONTARIO, CANADA 加拿大	WARRICK, ONTARIO, CANADA 加拿大	CE OFFICIAL CERTIFICATION 官方认证	LOT NO. NUMBER 批号

NOTICE: ALWAYS USE THE CORRECT RATCHET

WARNING 警告



G100 SPECIAL SWIVEL SELFLOCKING HOOK 100级 异型旋转安全钩

- ◆ Forged super alloy steel - Quenched and tempered
- 锻造合金钢材质经淬火及回火处理
- ◆ Suitable for G100 chain
- 与100级链条配合使用
- ◆ 25% elongation G100
- 比100级产品伸长率有25%
- ◆ Substantially proof test at 2.5 times Working Load Limit
- 组件按工作负荷的2.5倍进行验证测试
- ◆ Fatigue tested at 1.5 times Working Load Limit for 20000 cycles
- 在1.5倍工作负荷力下运转进行20000次疲劳测试
- ◆ Breakage test
- 对每一批产品进行严格的破坏性测试
- ◆ 100% magnetic crack detection
- 100% 磁粉探伤检测
- ◆ Surface finish (表面处理): Powder painted (覆膜)
- ◆ Colour code (色号): Blue (蓝色)RAL5015



- ◆ Positive lock: lock is selflocking when hook is turned
- 在转动下，钩子的自锁结构会自动闭合，很安全

SLR1018-G100 SPECIAL SWIVEL SELFLOCKING HOOK 100级 异型旋转安全钩

SLR1018

ITEM NO.	WEIGHT (kg)	WL (T)	B1 (mm)	A	B	C	D	E	F	G	H	N	M	K
10-SLR1018-08	1.25	2.5	16	220	212	2012	213	215	20	20	20	20	20	20
10-SLR1018-10	1.45	3	16	220	212	2012	213	215	20	20	20	20	20	20
10-SLR1018-13	2.34	4.2	25.8	244	240	2412	243	245	24	24	24	24	24	24
10-SLR1018-16	5.1	10	40	404	400	4012	403	405	40	40	40	40	40	40

Life span test is 4 times the Working Load Limit 寿命测试力是工作负荷4倍。
Package mark (包装标记): 10-15 (10, 15) CT SLR + BATHEN (BATHEN 编号)

G100 COMPONENTS 100级索具配件系列

- ◆ Specify only on agreed request form for customisation
- 只在经需求表下指定, 不能直接
- ◆ For further information, please contact us
- 如需了解详情, 请联系我们



SLR1019



SLR1025



SLR1026



SLR1028



WARNING 警告: This is a safety-critical component. It must be used in accordance with the instructions.


G100 EYE SLIP HOOK 100级 眼型滑钩

- ◆ Forged superior alloy steel- Quenched and Tempered
- ◇ 高强度高品质合金钢锻造而成，经过热处理
- ◆ 25% stronger than G50
- ◇ 比50级产品强度提升25%
- ◆ Individually proof test at 2.5 times Working Load Limit
- ◇ 每件在工作压力为2.5倍进行验证测试
- ◆ Fatigue tested at 1.5 times Working Load Limit for 20000 cycles
- ◇ 抽样进行20000次疲劳测试
- ◆ Breakage test 对每一批次产品进行严格的抽样破坏测试
- ◆ 100% magnetic crack detection
- ◇ 100% 进行磁粉探伤
- ◆ Surface finish (表面处理): Powder coated (喷塑)
- ◆ Colour code (色号): Blue (蓝色)RAL5015
- ◆ With cast latch 配铸连舌片配件



SLR1003-G100 EYE SLIP HOOK WITH CAST LATCH
100级 眼型滑钩 (带铸连舌片)

SLR1003



ITEM NO.	WEIGHT (kg)	WLL (T)	BL (T)	B±1	D±1	E±2	H±1	Ø±1	M±2	L±2.5
10-SLR1003-06	0.32	1.4	5.5	16.5	11	16.5	21	20.5	62	111
10-SLR1003-07	0.4	1.9	7.6	18	11	20.5	25	25	67.5	127
10-SLR1003-08	0.6	2.5	10	19	11	25	27.5	25	37.5	127
10-SLR1003-10	1.2	4	16	25	16	26.5	32	32	105.4	171.5
10-SLR1003-13	2.2	6.7	25.5	33	18	38	43.5	43	134	218
10-SLR1003-15	3.5	10	40	40	24.5	45	50	51	157	269
10-SLR1003-20	5.2	15	64	48	27	52	58	59	160	294
10-SLR1003-22	11.5	19	78	50	29	58	62	60	214	330
10-SLR1003-26	12.2	26.5	100	60	35	73	75	76	245	370
10-SLR1003-32	17.5	30.1	137.2	71	50	87	88	81.5	270	408

Ultimate breaking strength is 2.5 times the Working Load Limit. 6868 拉力是工作压力的4倍。

Regular only (常规规格): 10-15 WLL 4.7 US LBS + SIZE NUMBER (吨级)

SP-SLR1003&SLR1004-SPARE LATCH KIT FOR SLR1003 & SLR1004
SLR1003和SLR1004的铸连舌片配件



ITEM CODE 货号	SIZE 规格	ITEM CODE 货号	SIZE 规格
SP-SLR1003/4-6	6-10	SP-SLR1003/4-16	16-10
SP-SLR1003/4-7	7-10	SP-SLR1003/4-20	20-10
SP-SLR1003/4-8	8-10	SP-SLR1003/4-22	22-10
SP-SLR1003/4-10	10-12	SP-SLR1003/4-26	26-10
SP-SLR1003/4-13	13-12	SP-SLR1003/4-32	32-10

1 SET = GALVANIZED CAST LATCH + GALVANIZED SPRING + GALVANIZED BUSH + GALVANIZED NUT
1套=镀锌铸连舌片+镀锌弹簧+镀锌衬套+镀锌螺母



SLR1008

G100 CLEVIS SLING HOOK

G100 羊角挂钩


- ◆ Forged super alloy steel- Quenched and Tempered
- ◇ 高强度合金钢铸造成型并经回火处理，经过热处理
- ◆ Suitable for G100 chain
- ◇ 与100级链条配合使用。
- ◆ 25% stronger than G50
- ◇ 比G50级产品性能提升25%。
- ◆ Individually proof test at 2.5 times Working Load Limit
- ◇ 每件按工作压力的2.5倍进行验证测试
- ◆ Fatigue tested at 1.5 times Working Load Limit for 20000 cycles
- ◇ 抽样进行20000次疲劳测试
- ◆ Breakage test
- ◇ 对每一批产品进行严格的破坏性测试
- ◆ 100% magnetic crack detection
- ◇ 100% 磁粉探伤检测
- ◆ All load pins are 100% individually inspected and tested
- ◇ 所有销轴进行100%测试，确保相同等级发运
- ◆ Surface finish (表面处理): Powderly As-finish (喷漆)
- ◆ Color code (色号): Blue (蓝色)RAL5015



SLR1009-G100 CLEVIS SLING HOOK

G100 羊角挂钩

SLR1009



ITEM NO.	WEIGHT (kg)	WLL (T)	B/L (T)	A	B	E	M	W	L'	L	Φ
10-SLR1009-06	8.35	1.4	5.2	74x16	72x10	18x1	24x1	40x1	154x16	141x16	20x12
10-SLR1009-08	13.4	2.0	7.0	95x16	94x10	24x10	19x1	54x1	154x16	141x16	20x12
10-SLR1009-10	22.1	3.0	10	115x16	114x10	25x10	19x10	72x1	162x16	149x16	22x12
10-SLR1009-13	37.8	4.0	12.5	141x16	140x10	25x10	19x10	98x1	162x16	149x16	22x12
10-SLR1009-16	60.0	5.0	16	168x16	167x10	25x10	19x10	127x1	162x16	149x16	22x12
10-SLR1009-20	94.0	6.0	20	200x16	199x10	25x10	19x10	162x1	162x16	149x16	22x12
10-SLR1009-22	110	7.0	25	227x16	226x10	25x10	19x10	181x1	162x16	149x16	22x12
10-SLR1009-25	140	8.0	30	254x16	253x10	25x10	19x10	200x1	162x16	149x16	22x12

Ultimate load is 4 times the Working Load Limit 破断力为工作压力4倍

Regional mark (标记): 10-10 VLL 4 T 02 SLR + 6x10x16x10x10 (蓝色)

SP-SLR1009 - SPARE PART FOR SLR1009 (LOAD PIN) SLR1009销轴配件



ITEM CODE 型号	SIZE 规格	ITEM CODE 型号	SIZE 规格
SP-SLR1009-6	6-10	SP-SLR1009-16	16-20
SP-SLR1009-8	8-10	SP-SLR1009-20	20-22
SP-SLR1009-10	10-10	SP-SLR1009-22	22-25
SP-SLR1009-12	12-10		

1 SET = ELASTIC PIN + 2 BLACK SPRAG TYPE STRAIGHT PINS 1套=弹性销轴+2个直插型弹性销

NOTICE: ALWAYS USE THE PROPER RATED EQUIPMENT

WARNING 警告



G100 SPECIAL EYE GRAB HOOK WITH SAFETY PIN 100级带安全销钩型眼型抓钩

- ◆ Forged super alloy steel- Quenched and Tempered.
○ 高级合金和特殊合金锻造而成，经过热处理。
- ◆ Suitable for G100 chain.
○ 与100级链条配合使用。
- ◆ 25% stronger than G80.
○ 比G80级产品性能强有25%。
- ◆ Individually proof test at 2.5 times Working Load Limit.
○ 每件按工作拉力2.5倍进行验证测试。
- ◆ Fatigue tested at 1.5 times Working Load Limit for 20000 cycles.
○ 抽样进行20000次疲劳测试。
- ◆ Breakage test
○ 对每一批次产品进行严格抽样破坏测试。
- ◆ 100% magnetic crack detection
○ 100% 磁片扫描探伤。
- ◆ Surface finish (表面处理) : Powder plastified (镀膜)
- ◆ Color code (色号) : Blue (蓝色) RAL5015

- ◆ Adjust G100 chain length 调节链条长度
- ◆ With safety pin 带安全销 更安全



SLR1023 - G100 SPECIAL EYE GRAB HOOK WITH SAFETY PIN

SLR1023

100级 带安全销钩型眼型抓钩

	ITEM NO.	WEIGHT kg	WLL (T)	BL (m)	A	B	C	Φ1	E	L
	10-SLR1023-8	0.6	2.5	10	25.4x1	25.4x1	12.1	16.5x1	12.5x1	110x2
	10-SLR1023-10	1.0	4	10	44.5x1	25.4x1	13.1	21x1	16.5x1	110x2
	10-SLR1023-13	2.2	6.7	20	50.8x2	25.4x2	20.5x2	24.1x1	16.5x1x1	110x2

Ultimate pull is 4 times the Working Load Limit. 极限拉力是工作负荷的4倍。

Regular mark 常规标记: 10-10 WLL 4T OF SLR - BATCH 14280FR (B46)

SPARE PART FOR SLR1023(SAFETY PIN)
SLR1023的安全销配件



ITEM CODE 型号	SIZE 规格
SP-SLR1023-8	8-9"
SP-SLR1023-10	10-11"
SP-SLR1023-13	13-15"

1 SET = GALVANIZED SPRING + GALVANIZED PIN + GALVANIZED NUT

1套=电镀弹簧+电镀销钉+电镀螺母

Regular mark 常规标记:

MARK 标志	10	-10	WLL 4T	SLR	CE	10-1
CE MARKING 标志	CLASS 100 级100级	CLASS 100 级100级	WORKING LOAD LIMIT 工作负荷	PRODUCTS 产品	CE MARKING CE 标志	WATCH REAR SIDE 后侧检查



WARNING 警告: Do not use this product if the load exceeds the rated capacity.

G100 SPECIAL CLEVIS GRAB HOOK WITH SAFETY PIN 100级 带安全挡销羊角抓钩


- ◆ Forged super alloy steel- Quenched and Tempered.
- ◇ 高强度合金钢锻造- 淬火回火处理。
- ◆ Suitable for G100 chain
- ◇ 与100级链条配合使用。
- ◆ 25% stronger than G55
- ◇ 比G55产品性能提升25%。
- ◆ Individually proof test at 2.5 times Working Load Limit.
- ◇ 逐件按工作拉力的2.5倍进行验证测试。
- ◆ Fatigue tested at 1.5 times Working Load Limit for 20000 cycles
- ◇ 抽样进行20000次疲劳测试。
- ◆ Dimension test
- ◇ 附赠一批次产品进行严格的尺寸检测测试
- ◆ 100% magnetic crack detection
- ◇ 100% 磁力磁粉探伤
- ◆ Surface finish (表面处理): Powder painted (喷涂)
- ◆ Colour code (色号): Blue (蓝色) 4A1.5015



- ◆ Adjust G100 chain length 调节链条长度
- ◆ With safety pin 带安全销, 更安全

SLR1024 - G100 SPECIAL CLEVIS GRAB HOOK WITH SAFETY PIN 100级 带安全挡销羊角抓钩

SLR1024



ITEM NO.	WEIGHT (kg)	WLL (T)	SL (T)	A±1	B±0.5	C±1	A±1.5	B±0.5	E±0.5	L±2
10-SLR1024-S	6.70	2.5	10	35.5	25	34	45	10	10.5	130
10-SLR1024-10	1.16	4	15	44	32	40	32	12	13	154
10-SLR1024-13	3.0	6.7	25.4	57	40	50.5	107	15	15.5	175.5

Ultimate breaking force (Working Load Limit): 破断拉力(安全工作拉力)45t.
Regular mark (规格标记): 10-10 WLL 4 T OF BLUE + SAFETY PIN (蓝色)

SPARE PART FOR SLR1023(SAFETY PIN) SLR1024的安全销配件



ITEM CODE 型号	SIZE 规格
SP-SLR1024-S	3-10
SP-SLR1024-10	10-10
SP-SLR1024-13	13-10

1 SET = GALVANIZED SPRING + GALVANIZED PIN + GALVANIZED NUT
1套=带镀锌弹簧+带镀锌销钉+带镀锌螺母

Regular mark 常规标记:

MARK 标记	10	-10	WLL 4T	SLR	CE	10-1
DESCRIPTION 描述	CHAIN RING 圆环	GRADE 101 安全销钉	WORKING LOAD LIMIT 工作力	MARKING CODE 标记	CE OFFICIAL 认证	MARK NUMBER 标记


G100 CLEVIS FOREST HOOK
100級羊角森林鉤

- Forged super alloy steel - Quenched and Tempered
- 美國海軍航空兵聯合司令部認證製造，被指定處理
- 25% stronger than D30
- 比D30產品性能提升25%
- Drawings fast
- 對每一個產品進行嚴格的材料檢驗測試
- 100% magnetic crack detection
- 100% 進行磁粉探傷
- Surface finish (表面處理) : Powder-plasted (噴塗)
- Color finish (顏色) : Black (黑色) /RAL 5015


SLR1021-G100 CLEVIS FOREST HOOK
100噸羊角森林鉤

SLR1021

但是, 这种 *quasi* 类型的 *quasi* 不能出于甚型, 仅出于位本与标位逻辑值



ITEM CODE	WEIGHT (KG)	WLL (T)	SL (T)	A±1	B±1	E±1	F±1	M±1	N±2	K±2	L±1	L±1
10-SLR1021-8	0.41	2.5	10	4.5	30	9.8	31	28	12	72.6	26.4	25



ITEM CODE	WEIGHT (KG)	WLL (T)	BL (T)	A#1	B#1	E#1	F#1	M#1	N#2	K#2	L#1	L#1
90-8LR1021-13	1.87	0.3	25.9	16	37.0	17	49.6	59	27	110.5	97.5	150

Life-size bust in a glass case. Working Level 1. 玻璃柜中是工作层的模型

Regular mark 2101612:

MARK 标记	8	-10	WLL 2.5T	BLR	CE	18-1
CONSTRUCTION 设置	CHAM 500 500x500	CHAM 500 500x500	HYDROFLEX 1000x1000	MANUFACTURE 制造	CE CERTIFIED CE 认证	WALL 1800 1800x1800



WARNING 警告: Do not use the power tool with a damaged power cord. A damaged power cord can cause electric shock or fire.


G100 WEBBING SLING HOOK 100级 WK 吊带钩

- ◆ Forged super alloy steel- Quenched and Tempered
- ◇ 高强度合金钢经淬火及回火处理
- ◆ 25% stronger than G80
- ◇ 比G80强度性能提升25%
- ◆ Individually proofed at 2.5 times Working Load Limit
- ◇ 每件按工作压力的2.5倍进行验证测试
- ◆ Fatigue tested at 1.5 times Working Load Limit for 20000 cycles
- ◇ 在1.5倍工作压力下循环进行20000次疲劳测试
- ◆ Breakage test
- ◇ 对每一批产品进行严格的破坏性测试
- ◆ 100% magnetic crack detection
- ◇ 100% 磁粉探伤检测
- ◆ All load pins are 100% individually inspected and tested
- ◇ 所有销轴均经100%检测，确保绝对的质量品质
- ◆ Surface finish (表面处理): Powdercoated (喷涂)
- ◆ Colour code (颜色): Blue (蓝色) PA6,5015



SLR1055-G100 WEBBING SLING HOOK WK 吊带钩

SLR1055



ITEM CODE	WEIGHT (kg)	WLL (T)	B.L. (T)	A1	B1	C1	D1	M1	W15	E15	F15	G1	H1
10-SLR1055-1T	0.75	1	4	115	46	38	25	35.3	15	35	30	124	27
10-SLR1055-2T	1.27	2	8	155	44.5	37	25	30	21	40	38	148	29
10-SLR1055-3T	2.4	3	12	215	54	51.5	45	191	26	41	43	175	32
10-SLR1055-4T	4.75	4	16	400	70	135	64	190	52	50.5	55	255.6	40.5
10-SLR1055-5T	4.75	6	20	405	70	185	50	139	52	60.5	60	233.5	40.5
10-SLR1055-6T	4.75	8	24	405	70	152	56	128	72	50.5	50	227.5	40.5

1. The hook bears 4 times the Working Load Limit 1吨钩可承受4吨的工作拉力

Regular mark 常规标记:

MARK 标记	108	-10	WLL 5T	SLR	CE	10-1
DESCRIPTION 描述	108mm WLL 108mm	GRADE 101 101mm WLL	WORKING LOAD LIMIT 工作力	MANUFACTURE 生产	CE OFFICIAL CERTIFICATE 认证	101mm WLL 101mm

WARNING 警告

WARNING 警告



G100 EYE SLING HOOK G100 带扁大开口眼型钩

- ◆ Forged super alloy steel: Quenched and Tempered
- ◇ 锻造超合金钢经淬火和回火处理，经过热处理
- ◆ 25% stronger than Q235
- ◇ 比Q235产品性能提升25%
- ◆ Breakage test
- ◇ 对每一件次产品进行严格的拉伸破坏测试
- ◆ 100% magnifying crack detection
- ◇ 100% 进行裂纹检测
- ◆ Surface finish (表面处理): Powder painted (喷漆)
- ◆ Colour code (颜色): Blue (蓝色) RAL5015



SLR1074-G100 EYE SLING HOOK
G100 带扁大开口眼型钩


SLR1074

ITEM CODE	WEIGHT (KG)	WLL (T)	SL (T)	Φ±1	L±3	B±2	R±2	E±1	±1±1	H±2	M
SLR-1074-6	0.32	1.4	5.5	26.5	135	119	112.7	40	19	12	19
SLR-1074-8	0.72	2.8	11	24	158.5	135	120.5	37	12	18	27.5
SLR-1074-10	1.25	4	15	21.5	190	112.5	153.2	23	15	25	31
SLR-1074-13	2.30	5.7	20.8	44	241.5	140	154	03	19	33	38.5
SLR-1074-16	3.45	9	40	49	270	218	218	106	22	32	42

Load should be 4 times the Working Load Limit. 载荷应为工作重力的4倍
Regular mark (常规标记): 10-10 WLL 47 CE SLR + BATCH NUMBER (批号)

G100 CLEVIS LINK 100级 羊角环

- ◆ Forged super alloy steel: Quenched and Tempered
- ◇ 锻造超合金钢经淬火和回火处理，经过热处理
- ◆ 25% stronger than Q235
- ◇ 比Q235产品性能提升25%
- ◆ Breakage test
- ◇ 对每一件次产品进行严格的拉伸破坏测试
- ◆ 100% magnifying crack detection
- ◇ 100% 进行裂纹检测
- ◆ Surface finish (表面处理): Powder painted (喷漆)
- ◆ Colour code (颜色): Blue (蓝色) RAL5015



SLR1033-G100 CLEVIS LINK
100级羊角环

SLR1033

For container 13.5 t 用于集装箱吊钩

ITEM CODE	WEIGHT (KG)	WLL (T)	SL (T)	A±1	B±0.5	C±1	D±1	M±1.5	R±2	H±1	R±0.5	L±1.5	Q±0.2	E±1
10-SLR1033-13	1.56	6.7	25.8	59	26	15	50	93	80	21	21.5	17.8	10	35

Regular mark (常规标记): 13-13 WLL 57 CE SLR + BATCH NUMBER (批号)



G100 CLEVIS GRAB HOOK WITH CRADLE 100级 带羊角链环翅钩


- ◆ Forged super alloy steel- Quenched and Tempered
- 高级合金钢经特殊金属热处理而成，经过防腐蚀
- ◆ 25% stronger than Q235
- 比3级钢强度提高25%
- ◆ Individually proof test at 2.5 times Working Load Limit
- 零件在工作拉力的2.5倍进行验证测试
- ◆ Fatigue tested at 1.5 times Working Load Limit for 20000 cycles
- 在1.5倍工作拉力下循环进行20000次疲劳测试
- ◆ Breakage test
- 对每一件产品进行严格的破坏性测试
- ◆ 100% magnetic crack detection
- 100% 进行磁粉探伤
- ◆ Surface finish (表面处理): Powder coated (喷塑)
- ◆ Colour/codex color: Blue (蓝色RAL 9015)



SLR1080-G100 CLEVIS GRAB HOOK WITH CRADLE

SLR1080

100级 带羊角链环翅钩



ITEM NO.	WEIGHT (kg)	WLL (T)	BF (T)	A	B	C	E	H	L	K	J	U
10-SLR1080-06	0.203	1.4	8.0	54.5	31.1	31.7	31.3	30.1	33.1	40.0	36.12	21.3
10-SLR1080-08	0.30	2.0	10	55.4	31.1	31.1	31.4	30.1	34.1	40.0	36.1	21.3
10-SLR1080-10	1.522	4	15	55.4	31.1	31.1	31.1	30.1	34.1	40.0	36.1	21.3
10-SLR1080-13	3.372	6.7	20.0	55.4	31.1	31.1	31.1	30.1	34.1	40.0	36.1	21.3
10-SLR1080-15	5.57	10	25	55.4	31.1	31.1	31.1	30.1	34.1	40.0	36.1	21.3
10-SLR1080-20	9.79	15	35	55.4	31.1	31.1	31.1	30.1	34.1	40.0	36.1	21.3
10-SLR1080-22	14.02	20	45	55.4	31.1	31.1	31.1	30.1	34.1	40.0	36.1	21.3

Ull is a safe limit is 4 times the Working Load Limit. 额定拉力是工作拉力的4倍

Regular mark (常规标记): 10-31 55.4 31.1 31.1 31.1 30.1 34.1 40.0 36.1 21.3




WARNING 警告 This is a lifting device. It is not to be used for any other purpose.

G100 LARGE OPENING CLEVIS HOOK 100级 羊角大开口钩

- ◆ Forged super alloy steel-Quenched and Tempered
- ◆ 高强度合金钢锻造并经回火处理，经过热处理
- ◆ 25% stronger than Q355
- ◆ 比Q355产品强度提升25%
- ◆ Breakage test
- ◆ 对每一批产品进行严格的破坏性测试
- ◆ 100% magnetic crack detection
- ◆ 100% 进行磁粉探伤
- ◆ Surface finish (表面处理): Powder painted (喷漆)
- ◆ Colour code (颜色): Blue (蓝色)RAL5015

SLR1082-G100 LARGE OPENING CLEVIS HOOK 100级 羊角大开口钩

SLR1082



ITEM NO.	WEIGHT (kg)	WLL (T)	BP (T)	A	B	C	E	M	N	H	L
10-SLR1082-6	0.41	1.4	0.7	18x1	22x1	18x1	5x12	16x2	21x1	102x1	101x1
10-SLR1082-8	0.6	2.0	1.0	20x1.5	24x1	20x1	6x12	17x2	22x1	111x1	110x1
10-SLR1082-10	1.4	4	2.0	25x1	30x1	25x1.5	8x12	22x2	25x1	111x1	108x1
10-SLR1082-13	2.38	5.7	28.8	30x1	35x1.5	30x1	10x14	25x2	30x1	124x1	121x1
10-SLR1082-16	5.1	12	40	38x2.5	45x2	40x2	13x16	33x3	40x2	150x1	146x1

Ultimate load is 4 times the Working Load Limit. 极限拉力是工作能力的4倍
Regular mark (常规标记): 10-SLR1082-G100-BATCH10820820 (批号)

G100 CLEVIS HOOK 100级 羊角链环

- ◆ Forged super alloy steel-Quenched and Tempered
- ◆ 高强度合金钢锻造并经回火处理，经过热处理
- ◆ 25% stronger than Q355
- ◆ 比Q355产品强度提升25%
- ◆ Breakage test
- ◆ 对每一批产品进行严格的破坏性测试
- ◆ 100% magnetic crack detection
- ◆ 100% 进行磁粉探伤
- ◆ Surface finish (表面处理): Powder painted (喷漆)
- ◆ Colour code (颜色): Blue (蓝色)RAL5015



SLR1081-G100 CLEVIS HOOK 100级 羊角链环

SLR1081

ITEM NO.	WEIGHT (kg)	WLL (T)	BP (T)	A	B	E	H	L	P
10-SLR1081-10	0.54	4	15	12.5x1.5	17x1	17x1	35x1.5	105x2	20.5x1

Ultimate load is 4 times the Working Load Limit. 极限拉力是工作能力的4倍
Regular mark (常规标记): 10-SLR1081-G100-BATCH10810810 (批号)



G100 SLIDING COUPLING TACKLE HOOK 100级 滑车钩

- ◆ Forged super alloy steel- Quenched and Tempered
 - 高级合金钢经特殊合金钢锻造而成，经过热处理
- ◆ 29% stronger than G80
 - 比G80级产品性能提高29%
- ◆ Individually proof test at 2.5 times Working Load Limit
 - 零件按工作拉力的2.5倍进行验证测试
- ◆ Fatigue tested at 1.5 times Working Load Limit for 20000 cycles
 - 在1.5倍工作拉力下循环进行20000次疲劳测试
- ◆ Breakage test
 - 对每一批次产品进行严格的破坏性测试
- ◆ 100% magnetic crack detection
 - 100% 进行磁粉探伤
- ◆ Surface finish (表面处理): Powder coated (喷塑)
 - ◆ Colour/codex (颜色): Blue (蓝色)RAL 9015

SLR1085-G100 SLIDING COUPLING TACKLE HOOK

100级 滑车钩

SLR1085



ITEM NO.	WEIGHT (kg)	WLL (T)	BL (T)	A	B	E	F	M	N	O	L
10.8	5.67	4	10	34±1	48±1	21±2	185±2	12±1	26±1	32±1	118±2

WLL is safe load is 4 times the Working Load Limit, 钩额定工作拉力为WLL的4倍

Regular mark (常规标记): 10-30 V6.1.4T (21.12.14) +DATE/NAME/REV (日期)



WARNING 警告 Please read the instructions carefully before use.

G100 EYE SHORTENING GRAB HOOK 100级 眼型翅钩

- ◆ Forged super alloy steel- Quenched and Tempered
- 高强度合金钢锻造而成，经过热处理
- ◆ 25% stronger than G80
- 比G80级屈服强度提高25%
- ◆ Individually proof test at 2.5 times Working Load Limit
- 零件在工作拉力的2.5倍进行验证测试
- ◆ Fatigue tested at 1.5 times Working Load Limit for 20000 cycles
- 在1.5倍工作拉力下循环进行20000次疲劳测试
- ◆ Breakage test
- 对每一批次产品进行严格的破坏性测试
- ◆ 100% magnetic crack detection
- 100% 进行磁粉探伤
- ◆ Surface finish (表面处理): Powder coated (喷塑)
- ◆ Colour code (颜色): Blue (蓝色RAL 9015)



SLR1090-G100 EYE SHORTENING GRAB HOOK
100级 眼型翅钩

SLR1090



ITEM NO.	WEIGHT (kg)	WLL (T)	B.L (T)	A	B	C	E	M	n	L
6-10	1.23	1.4	8.8	8±1	87±5	26.5±1	5.0±1	52±2	13.5±1	81.8±2
8-10	0.5	2.5	10	6.5±1	11±0.5	34±1.5	30.5±1	42.5±2	17.5±1	134±3
13-10	2.15	11.7	28.5	10.5±2	17±1	50±2	75.5±2	101±3	28±2	121±3

Ullrich is a brand of 4 tonnes for Vötsch-Lifting-Lifts Ltd. 翅钩拉力最大为4吨

Regular mark (常规标记): 10-30 Vötsch Lift GmbH +GATEWAYLIFTS (总代理)



WARNING 警告

Read and follow the instructions for use carefully.

G100 CLEVIS GRAB HOOK 100级 羊角钩

- ◆ Forged super alloy steel- Quenched and Tempered
- ◇ 高强度合金钢锻造- 淬火回火处理
- ◆ 25% stronger than G50
- ◇ 比G50强度性能提高25%
- ◆ Individually proof test at 2.5 times Working Load Limit
- ◇ 每件在工作压力的2.5倍进行验证测试
- ◆ Fatigue tested at 1.5 times Working Load Limit for 20000 cycles
- ◇ 在1.5倍工作压力下每样进行20000次疲劳测试
- ◆ Breakage test
- ◇ 对每一批产品进行严格的破坏性测试
- ◆ 100% magnetic crack detection
- ◇ 100% 磁粉探伤检测
- ◆ Surface finish (表面处理): Powder painted (粉型)
- ◆ Colour code(色号): Blue(蓝色)RAL9010



SLR1091-G100 CLEVIS GRAB HOOK

100级 羊角钩

SLR1091



ITEM NO.	WEIGHT kg	WLL (T)	BL (T)	A	B	C	E	M	H	L
6-10	0.265	1.4	3.8	8±0.5	22±1	18±1	3.2±1	39±2	5±0.5	21±2
8-10	0.65	2.1	10	15±0.5	33±1	21±1.5	10.0±1	52.5±2	11±1	35±2
15-10	2.4	8.2	28.5	18±1	60±2	37±2	15.5±1	77±2	15±1	125±2
20-10	7	15	54	25±1	85±2	51±2	20±2	144±2	25±1	167±2

Ultra safe load is 4 times the Working Load Limit. 特别耐力是工作压力的4倍

Regular mark (常规标记): 10-15VOLT 42-55.8W BATTERY (电瓶)



G100 SWIVEL HOOK WITH LATCH 100级带轴承旋转货钩

- ◆ Forged super alloy steel- Quenched and Tempered
- 高级合金钢经特殊合金钢锻造而成，经过热处理
- ◆ 25% stronger than G80
- 比G80级韧性强度高25%
- ◆ Individually proof test at 2.5 times Working Load Limit
- 零件在工作压力的2.5倍进行验证测试
- ◆ Fatigue tested at 1.5 times Working Load Limit for 20000 cycles
- 在1.5倍工作压力下循环进行20000次疲劳测试
- ◆ Breakage test
- 对每一批次产品进行严格的破坏性测试
- ◆ 100% magnetic crack detection
- 100% 进行磁粉探伤
- ◆ Surface finish (表面处理): Powder coated (喷塑)
- ◆ Colour code (颜色): Blue (蓝色)RAL 9015

SLR1095-G100 SWIVEL HOOK WITH LATCH 100级带轴承旋转货钩

SLR1095



ITEM NO.	WEIGHT (kg)	WLL (T)	SL (T)	A	B	E	M	L1	L	N	C	H
6-10	1.05	1.8	0.6	11218	11715	26115	112	1115	1247	611	1111	1111
8-10	1.16	2.0	0.6	11112	11715	11111	112	1112	1112	1111	1111	1111
10-10	1.21	2.4	0.6	11111	11715	11111	112	1112	1112	1111	1111	1111
13-10	2.12	3.7	0.6	11111	11715	11111	112	1112	1112	1111	1111	1111
15-10	1.44	3.0	0.6	11111	11715	11111	112	1112	1112	1111	1111	1111

1/6/10/13/15 Load is 4 times the Working Load Limit. 钩的拉力是工作压力的4倍

Regular work (常规使用): 10-11 16.1-17.1 18.1 19.1 20.1 21.1 22.1 23.1 24.1 25.1 26.1 27.1 28.1 29.1 30.1 31.1 32.1 33.1 34.1 35.1 36.1 37.1 38.1 39.1 40.1 41.1 42.1 43.1 44.1 45.1 46.1 47.1 48.1 49.1 50.1 51.1 52.1 53.1 54.1 55.1 56.1 57.1 58.1 59.1 60.1 61.1 62.1 63.1 64.1 65.1 66.1 67.1 68.1 69.1 70.1 71.1 72.1 73.1 74.1 75.1 76.1 77.1 78.1 79.1 80.1 81.1 82.1 83.1 84.1 85.1 86.1 87.1 88.1 89.1 90.1 91.1 92.1 93.1 94.1 95.1 96.1 97.1 98.1 99.1 100.1 101.1 102.1 103.1 104.1 105.1 106.1 107.1 108.1 109.1 110.1 111.1 112.1 113.1 114.1 115.1 116.1 117.1 118.1 119.1 120.1 121.1 122.1 123.1 124.1 125.1 126.1 127.1 128.1 129.1 130.1 131.1 132.1 133.1 134.1 135.1 136.1 137.1 138.1 139.1 140.1 141.1 142.1 143.1 144.1 145.1 146.1 147.1 148.1 149.1 150.1 151.1 152.1 153.1 154.1 155.1 156.1 157.1 158.1 159.1 160.1 161.1 162.1 163.1 164.1 165.1 166.1 167.1 168.1 169.1 170.1 171.1 172.1 173.1 174.1 175.1 176.1 177.1 178.1 179.1 180.1 181.1 182.1 183.1 184.1 185.1 186.1 187.1 188.1 189.1 190.1 191.1 192.1 193.1 194.1 195.1 196.1 197.1 198.1 199.1 200.1 201.1 202.1 203.1 204.1 205.1 206.1 207.1 208.1 209.1 210.1 211.1 212.1 213.1 214.1 215.1 216.1 217.1 218.1 219.1 220.1 221.1 222.1 223.1 224.1 225.1 226.1 227.1 228.1 229.1 230.1 231.1 232.1 233.1 234.1 235.1 236.1 237.1 238.1 239.1 240.1 241.1 242.1 243.1 244.1 245.1 246.1 247.1 248.1 249.1 250.1 251.1 252.1 253.1 254.1 255.1 256.1 257.1 258.1 259.1 260.1 261.1 262.1 263.1 264.1 265.1 266.1 267.1 268.1 269.1 270.1 271.1 272.1 273.1 274.1 275.1 276.1 277.1 278.1 279.1 280.1 281.1 282.1 283.1 284.1 285.1 286.1 287.1 288.1 289.1 290.1 291.1 292.1 293.1 294.1 295.1 296.1 297.1 298.1 299.1 300.1 301.1 302.1 303.1 304.1 305.1 306.1 307.1 308.1 309.1 310.1 311.1 312.1 313.1 314.1 315.1 316.1 317.1 318.1 319.1 320.1 321.1 322.1 323.1 324.1 325.1 326.1 327.1 328.1 329.1 330.1 331.1 332.1 333.1 334.1 335.1 336.1 337.1 338.1 339.1 340.1 341.1 342.1 343.1 344.1 345.1 346.1 347.1 348.1 349.1 350.1 351.1 352.1 353.1 354.1 355.1 356.1 357.1 358.1 359.1 360.1 361.1 362.1 363.1 364.1 365.1 366.1 367.1 368.1 369.1 370.1 371.1 372.1 373.1 374.1 375.1 376.1 377.1 378.1 379.1 380.1 381.1 382.1 383.1 384.1 385.1 386.1 387.1 388.1 389.1 390.1 391.1 392.1 393.1 394.1 395.1 396.1 397.1 398.1 399.1 400.1 401.1 402.1 403.1 404.1 405.1 406.1 407.1 408.1 409.1 410.1 411.1 412.1 413.1 414.1 415.1 416.1 417.1 418.1 419.1 420.1 421.1 422.1 423.1 424.1 425.1 426.1 427.1 428.1 429.1 430.1 431.1 432.1 433.1 434.1 435.1 436.1 437.1 438.1 439.1 440.1 441.1 442.1 443.1 444.1 445.1 446.1 447.1 448.1 449.1 450.1 451.1 452.1 453.1 454.1 455.1 456.1 457.1 458.1 459.1 460.1 461.1 462.1 463.1 464.1 465.1 466.1 467.1 468.1 469.1 470.1 471.1 472.1 473.1 474.1 475.1 476.1 477.1 478.1 479.1 480.1 481.1 482.1 483.1 484.1 485.1 486.1 487.1 488.1 489.1 490.1 491.1 492.1 493.1 494.1 495.1 496.1 497.1 498.1 499.1 500.1 501.1 502.1 503.1 504.1 505.1 506.1 507.1 508.1 509.1 510.1 511.1 512.1 513.1 514.1 515.1 516.1 517.1 518.1 519.1 520.1 521.1 522.1 523.1 524.1 525.1 526.1 527.1 528.1 529.1 530.1 531.1 532.1 533.1 534.1 535.1 536.1 537.1 538.1 539.1 540.1 541.1 542.1 543.1 544.1 545.1 546.1 547.1 548.1 549.1 550.1 551.1 552.1 553.1 554.1 555.1 556.1 557.1 558.1 559.1 560.1 561.1 562.1 563.1 564.1 565.1 566.1 567.1 568.1 569.1 570.1 571.1 572.1 573.1 574.1 575.1 576.1 577.1 578.1 579.1 580.1 581.1 582.1 583.1 584.1 585.1 586.1 587.1 588.1 589.1 590.1 591.1 592.1 593.1 594.1 595.1 596.1 597.1 598.1 599.1 600.1 601.1 602.1 603.1 604.1 605.1 606.1 607.1 608.1 609.1 610.1 611.1 612.1 613.1 614.1 615.1 616.1 617.1 618.1 619.1 620.1 621.1 622.1 623.1 624.1 625.1 626.1 627.1 628.1 629.1 630.1 631.1 632.1 633.1 634.1 635.1 636.1 637.1 638.1 639.1 640.1 641.1 642.1 643.1 644.1 645.1 646.1 647.1 648.1 649.1 650.1 651.1 652.1 653.1 654.1 655.1 656.1 657.1 658.1 659.1 660.1 661.1 662.1 663.1 664.1 665.1 666.1 667.1 668.1 669.1 670.1 671.1 672.1 673.1 674.1 675.1 676.1 677.1 678.1 679.1 680.1 681.1 682.1 683.1 684.1 685.1 686.1 687.1 688.1 689.1 690.1 691.1 692.1 693.1 694.1 695.1 696.1 697.1 698.1 699.1 700.1 701.1 702.1 703.1 704.1 705.1 706.1 707.1 708.1 709.1 710.1 711.1 712.1 713.1 714.1 715.1 716.1 717.1 718.1 719.1 720.1 721.1 722.1 723.1 724.1 725.1 726.1 727.1 728.1 729.1 730.1 731.1 732.1 733.1 734.1 735.1 736.1 737.1 738.1 739.1 740.1 741.1 742.1 743.1 744.1 745.1 746.1 747.1 748.1 749.1 750.1 751.1 752.1 753.1 754.1 755.1 756.1 757.1 758.1 759.1 760.1 761.1 762.1 763.1 764.1 765.1 766.1 767.1 768.1 769.1 770.1 771.1 772.1 773.1 774.1 775.1 776.1 777.1 778.1 779.1 780.1 781.1 782.1 783.1 784.1 785.1 786.1 787.1 788.1 789.1 790.1 791.1 792.1 793.1 794.1 795.1 796.1 797.1 798.1 799.1 800.1 801.1 802.1 803.1 804.1 805.1 806.1 807.1 808.1 809.1 810.1 811.1 812.1 813.1 814.1 815.1 816.1 817.1 818.1 819.1 820.1 821.1 822.1 823.1 824.1 825.1 826.1 827.1 828.1 829.1 830.1 831.1 832.1 833.1 834.1 835.1 836.1 837.1 838.1 839.1 840.1 841.1 842.1 843.1 844.1 845.1 846.1 847.1 848.1 849.1 850.1 851.1 852.1 853.1 854.1 855.1 856.1 857.1 858.1 859.1 860.1 861.1 862.1 863.1 864.1 865.1 866.1 867.1 868.1 869.1 870.1 871.1 872.1 873.1 874.1 875.1 876.1 877.1 878.1 879.1 880.1 881.1 882.1 883.1 884.1 885.1 886.1 887.1 888.1 889.1 890.1 891.1 892.1 893.1 894.1 895.1 896.1 897.1 898.1 899.1 900.1 901.1 902.1 903.1 904.1 905.1 906.1 907.1 908.1 909.1 910.1 911.1 912.1 913.1 914.1 915.1 916.1 917.1 918.1 919.1 920.1 921.1 922.1 923.1 924.1 925.1 926.1 927.1 928.1 929.1 930.1 931.1 932.1 933.1 934.1 935.1 936.1 937.1 938.1 939.1 940.1 941.1 942.1 943.1 944.1 945.1 946.1 947.1 948.1 949.1 950.1 951.1 952.1 953.1 954.1 955.1 956.1 957.1 958.1 959.1 960.1 961.1 962.1 963.1 964.1 965.1 966.1 967.1 968.1 969.1 970.1 971.1 972.1 973.1 974.1 975.1 976.1 977.1 978.1 979.1 980.1 981.1 982.1 983.1 984.1 985.1 986.1 987.1 988.1 989.1 990.1 991.1 992.1 993.1 994.1 995.1 996.1 997.1 998.1 999.1 1000.1 1001.1 1002.1 1003.1 1004.1 1005.1 1006.1 1007.1 1008.1 1009.1 1010.1 1011.1 1012.1 1013.1 1014.1 1015.1 1016.1 1017.1 1018.1 1019.1 1020.1 1021.1 1022.1 1023.1 1024.1 1025.1 1026.1 1027.1 1028.1 1029.1 1030.1 1031.1 1032.1 1033.1 1034.1 1035.1 1036.1 1037.1 1038.1 1039.1 1040.1 1041.1 1042.1 1043.1 1044.1 1045.1 1046.1 1047.1 1048.1 1049.1 1050.1 1051.1 1052.1 1053.1 1054.1 1055.1 1056.1 1057.1 1058.1 1059.1 1060.1 1061.1 1062.1 1063.1 1064.1 1065.1 1066.1 1067.1 1068.1 1069.1 1070.1 1071.1 1072.1 1073.1 1074.1 1075.1 1076.1 1077.1 1078.1 1079.1 1080.1 1081.1 1082.1 1083.1 1084.1 1085.1 1086.1 1087.1 1088.1 1089.1 1090.1 1091.1 1092.1 1093.1 1094.1 1095.1 1096.1 1097.1 1098.1 1099.1 1100.1 1101.1 1102.1 1103.1 1104.1 1105.1 1106.1 1107.1 1108.1 1109.1 1110.1 1111.1 1112.1 1113.1 1114.1 1115.1 1116.1 1117.1 1118.1 1119.1 1120.1 1121.1 1122.1 1123.1 1124.1 1125.1 1126.1 1127.1 1128.1 1129.1 1130.1 1131.1 1132.1 1133.1 1134.1 1135.1 1136.1 1137.1 1138.1 1139.1 1140.1 1141.1 1142.1 1143.1 1144.1 1145.1 1146.1 1147.1 1148.1 1149.1 1150.1 1151.1 1152.1 1153.1 1154.1 1155.1 1156.1 1157.1 1158.1 1159.1 1160.1 1161.1 1162.1 1163.1 1164.1 1165.1 1166.1 1167.1 1168.1 1169.1 1170.1 1171.1 1172.1 1173.1 1174.1 1175.1 1176.1 1177.1 1178.1 1179.1 1180.1 1181.1 1182.1 1183.1 1184.1 1185.1 1186.1 1187.1 1188.1 1189.1 1190.1 1191.1 1192.1 1193.1 1194.1 1195.1 1196.1 1197.1 1198.1 1199.1 1200.1 1201.1 1202.1 1203.1 1204.1 1205.1 1206.1 1207.1 1208.1 1209.1 1210.1 1211.1 1212.1 1213.1 1214.1 1215.1 1216.1 1217.1 1218.1 1219.1 1220.1 1221.1 1222.1 1223.1 1224.1 1225.1 1226.1 1227.1 1228.1 1229.1 1230.1 1231.1 1232.1 1233.1 1234.1 1235.1 1236.1 1237.1 1238.1 1239.1 1240.1 1241.1 1242.1 1243.1 1244.1 1245.1 1246.1 1247.1 1248.1 1249.1 1250.1 1251.1 1252.1 1253.1 1254.1 1255.1 1256.1 1257.1 1258.1 1259.1 1260.1 1261.1 1262.1 1263.1 1264.1 1265.1 1266.1 1267.1 1268.1 1269.1 1270.1 1271.1 1272.1 1273.1 1274.1 1275.1 1276.1 1277.1 1278.1 1279.1 1280.1 1281.1 1282.1 1283.1 1284.1 1285.1 1286.1 1287.1 1288.1 1289.1 1290.1 1291.1 1292.1 1293.1 1294.1 1295.1 1296.1 1297.1 1298.1 1299.1 1300.1 1301.1 1302.1 1303.1 1304.1 1305.1 1306.1 1307.1 1308.1 1309.1 1310.1 1311.1 1312.1 1313.1 1314.1 1315.1 1316.1 1317.1 1318.1 1319.1 1320.1 1321.1 1322.1 1323.1 1324.1 1325.1 1326.1 1327.1 1328.1 1329.1 1330.1 1331.1 1332.1 1333.1 1334.1 1335.1 1336.1 1337.1 1338.1 1339.1 1340.1 1341.1 1342.1 1343.1 1344.1 1345.1 1346.1 1347.1 1348.1 1349.1 1350.1 1351.1 1352.1 1353.1 1354.1 1355.1 1356.1 1357.1 1358.1 1359.1 1360.1 1361.1 1362.1 1363.1 1364.1 1365.1 1366.1 1367.1 1368.1 1369.1 1370.1 1371.1 1372.1 1373.1 1374.1 1375.1 1376.1 1377.1 1378.1 1379.1 1380.1 1381.1 1382.1 1383.1 1384.1 1385.1 1386.1 1387.1 1388.1 1389.1 1390.1 1391.1 1392.1 1393.1 1394.1 1395.1 1396.1 1397.1 1398.1 1399.1 1400.1 1401.1 1402.1 1403.1 1404.1 1405.1 1406.1 1407.1 1408.1 1409.1 1410.1 1411.1 1412.1 1413.1 1414.1 1415.1 1416.1 1417.1 1418.1 1419.1 1420.1 1421.1 1422.1 1423.1 1424.1 1425.1 1426.1 1427.1 1428.1 1429.1 1430.1 1431.1 1432.1 1433.1 1434.1 1435.1 1436.1 1437.1 1438.1 1439.1 1440.1 1441.1 1442.1 1443.1 1444.1 1445.1 1446.1 1447.1 1448.1 1449.1 1450.1 1451.1 1452.1 1453.1 1454.1 1455.1 1456.1 1457.1 1458.1 1459.1 1460.1 1461.1 1462.1 1463.1 1464.1 1465.1 1466.1 1467.1 1468.1 1469.1 1470.1 1471.1 1472.1 1473.1 1474.1 1475.1 1476.1 1477.1 1478.1 1479.1 1480.1 1481.1 1482.1 1483.1 1484.1 1485.1 1486.1 1487.1 1488.1 1489.1 1490.1 1491.1 1492.1 1493.1 1494.1 1495.1 1496.1 1497.1 1498.1 1499.1 1500.1 1501.1 1502.1 1503.1 1504.1 1505.1 1506.1 1507.1 1508.1 1509.1 1510.1 1511.1 1512.1 1513.1 1514.1 1515.1 1516.1 1517.1 1518.1 1519.1 1520.1 1521.1 1522.1 1523.1 1524.1 1525.1 1526.1 1527.1 1528.1 1529.1 1530.1 1531.1 1532.1 1533.1 1534.1 1535.1 1536.1 1537.1 1538.1 1539.1 1540.1 1541.1 1542.1 1543.1 1544.1 1545.1 1546.1 1547.1 1548.1 1549.1 1550.1 1551.1 1552.1 1553.1 1554.1 1555.1 1556.1 1557.1 1558.1 1559.1 1560.1 1561.1 1562.1 1563.1 1564.1 1565.1 1566.1 1567.1 1568.1 1569.1 1570.1 1571.1 1572.1 1573.1 1574.1 1575.1 1576.1 1577.1 1578.1 1579.1 1580.1 1581.1 1582.1 1583.1 1584.1 1585.1 1586.1 1587.1 1588.1 1589.1 1590.1 1591.1 1592.1 1593.1 1594.1 1595.1 1596.1 1597.1 1598.1 1599.1 1600.1 1601.1 1602.1 1603.1 1604.1 1605.1 1606.1 1607.1 1608.1 1609.1 1610.1 1611.1 1612.1 1613.1 1614.1 1615.1 1616.1 1617.1 1618.1 1619.1 1620.1 1621.1 1622.1 1623.1 1624.1 1625.1 1626.1 1627.1 1628.1 1629.1 1630.1 1631.1 1632.1 1633.1 1634.1 1635.1 1636.1 1637.1 1638.1 1639.1 1640.1 1641.1 1642.1 1643.1 1644.1 1645.1 1646.1 1647.1 1648.1 1649.1 1650.1 1651.1 1652.1 1653.1 1654.1 1655.1 1656.1 1657.1 1658.1 1659.1 1660.1 1661.1 1662.1 1663.1 1664.1 1665.1 1666.1 1667.1 1668.1 1669.1 1670.1 1671.1 1672.1 1673.1 1674.1 1675.1 1676.1 1677.1 1678.1 1679.1 1680.1 1681.1 1682.1 1683.1 1684.1 1685.1 1686.1 1687.1 1688.1 1689.1 1690.1 1691.1 1692.1 1693.1 1694.1 1695.1 1696.1 1697.1 1698.1 1699.1 1700.1 1701.1 1702.1 1703.1 1704.1 1705.1 1706.1 1707.1 1708.1 1709.1 1710.1 1711.1 1712.1 1713.1 1714.1 1715.1 1716.1 1717.1 1718.1 1719.1 1720.1 1721.1 1722.1 1723.1 1724.1 1725.1 1726.1 1727.1 1728.1 1729.1 1730.1 1731.1 1732.1 1733.1 1734.1 1735.1 1736.1 1737.1 1738.1 1739.1

G100 TWISTED EYE HOOK 100级 转腓钩

- ◆ Forged super alloy steel- Quenched and Tempered
- ◇ 高强度合金钢锻造- 淬火及回火处理
- ◆ 25% stronger than G50
- ◇ 比G50级产品强度提高25%
- ◆ Individually proof test at 2.5 times Working Load Limit
- ◇ 每件在工作压力的2.5倍进行验证测试
- ◆ Fatigue tested at 1.5 times Working Load Limit for 20000 cycles
- ◇ 在1.5倍工作压力下循环进行20000次疲劳测试
- ◆ Breakage test
- ◇ 对每一批次产品进行严格的破坏性测试
- ◆ 100% magnetic crack detection
- ◇ 100% 磁粉探伤检测
- ◆ Surface finish (表面处理): Powder painted (粉型)
- ◆ Colour code(色号): Blue(蓝色)RAL 5015

SLR1096-G100 TWISTED EYE HOOK

100级 转腓钩

SLR1096

ITEM NO.	WEIGHT kg	WLL (T)	B.L (T)	A	B	C	A1	x2	E	L
8-10	0.36	2.5	16	18±1	28±1	17±1	62±2	211±3	12.5±1	19±2
10-10	0.72	4	18	18±1	40±1.2	17.5±1	66±2	245±1.5	13±1.5	18.5±1
12-10	1.4	6.7	25.0	24±2	41±1.5	21±1	87±2.8	32±2	27±1.5	22±2
16-10	3.17	16	40	31±2	47.5±2	31±1	104±2.5	56±2	37±2	34.5±1

Ultra safe load is 4 times the Working Load Limit. 特别安全工作压力的4倍

Regular mark (常规标记): 10-1050147120-3L-B1-BATCH NUMBER (批号)



G100 EYE TYPE HOOK 100級 眼型滑鈎

- ◆ Forged super alloy steel- Quenched and Tempered
- 高級合金鋼在特殊合金鋼爐造成，經過熱處理
- ◆ 25% stronger than G80
- ◆ 比G80級強韌性超過25%
- ◆ Individually proof test at 2.5 times Working Load Limit
- 零件在工作拉力的2.5倍進行驗證測試
- ◆ Fatigue tested at 1.5 times Working Load Limit for 20000 cycles
- 在1.5倍工作拉力下進行20000次疲勞測試
- ◆ Breakage test
- ◆ 對每一批產品進行嚴格的破損試驗
- ◆ 100% magnetic crack detection
- 100% 進行磁粉探傷
- ◆ Surface finish (表面處理) : Powder coated (噴漆)
- ◆ Colour/codex color : Blue (藍色)RAL 9015

SLR1097-G100 EYE TYPE HOOK 100級 眼型滑鈎

SLR1097

ITEM NO.	WEIGHT (kg)	WLL (T)	RF (T)	A	E	M	N	H	K	L
6-10	0.27	1.4	5.6	9.5±1	20±1.5	20±2	17±1	19±1	51±2	136±2
8-10	0.326	2.8	10	18±1	27±1.5	35±2	26±1	23±1	118±2	134±2
10-10	1.22	4	16	19±1	31±2	110±2	54±1	36±1	149±2	179±3
13-10	3.43	6.7	26.5	23±2	40±2	135±3	38±1	37±1	172±3	227±3
15-10	3.81	10	40	27.5±2	44±2	181±3	41.5±2	41±2	185±3	257±3
20-10	3.3	16	64	27±2	62±2	187±3	61±2	52±2	225±4	311±4
22-10	6.1	15	75	32±2	72±2	180±3	67±2	59.5±2	245±4	337±4

1/6 (6x4) End is 4 times the Working Load Limit, 掛鈎拉力為工作拉力的4倍

Regular color (原色RAL) : 10-97 50141 42 32 35 55ALC H 72.8 82 35 (藍色)



WARNING 警告 This is a lifting device and must be used properly. Not for use as a permanent fastener.

G80 COMPONENTS 80级索具配件

- ◆ REGULAR MARK OF G80 components from SUR
- ◆ 来自于SUR品牌G80级索具配件打号标准
- ◆ For example 10-8 EYE SELF LOCK HOOK 10-8
- ◆ 以G80级眼型自锁钩10-8为例



Regular mark 常规标记:

MARK 标记	10	-8	WILL 3.15T	SUR	CE	10-1
DESCRIPTION 说明	10mm P.D. 10mm	8mm P.D. 8mm	WORKING LOAD LIMIT 工作负荷	MANUFACTURER 生产商	CE CERTIFICATE CE 认证	MARK NUMBER 标记号



G80 SELF-LOCK HOOK IMPROVED

改进型80级自锁钩

G80 SELF-LOCK HOOKS

(OUR ITEM CODE SLR081, SLR082, SLR083)

We make improvements on the basis of them.

We strongly recommend you to choose **IMPROVED ITEMS** instead of SLR081,SLR082,SLR083

对于我们的80级自锁安全钩
SLR081, SLR082, SLR083,
我们做了全面改进。
强烈建议你选用改进产品。

For example SLR081, it is improved to the following
以SLR081为例,改进后的产品如下



WARNING 警告 请仔细阅读产品说明书及警告标志, 并妥善保管。

G80 SELF-LOCK HOOK IMPROVED

改进型80级自锁

IMPROVEMENT NO.1 改进NO.1

Overall design: 总体设计

Appearance: Look Smooth And Beautiful

Mechanical behavior: Better performance

外观更流畅美观

机械性能更优异


IMPROVEMENT NO.2 改进NO.2



- ◆ The hook is opened. We make a new design to make sure the hook will not close before being inserted. It is very convenient to release. And it is more safe.

◇ 钩子打开后，我们做了一个新的设计保证钩子在未安装前不会闭合，所以更便于操作，也更安全。


IMPROVEMENT NO.3 改进NO.3



- ◆ The hook is opened completely. The raised square can avoid finger injury.

◇ 由于我们设计了一个凸起的方块避免操作时，即使钩子被完全打开，也不会对手指造成危害。

IMPROVEMENT NO.4 改进NO.4



- ◆ We make above convexe radian to protect finger.

◇ 我们设计了一个凸起的圆角来保护手指。



G80 EYE TYPE SAFETY HOOK 80级 眼型安全钩

- ◆ Forged super alloy steel- Quenched and Tempered
◊ 高强度合金钢锻造而成，经过回火处理
- ◆ Suitable for EN1218-2 G80 chain
◊ 与EN1218-2级链条配套使用
- ◆ Individually proof test at 2.5 times Working Load Limit
◊ 零件在工作拉力的2.5倍进行验证测试
- ◆ Fatigue tested at 1.5 times Working Load Limit for 20000 cycles
◊ 吊钩进行20000次疲劳测试
- ◆ Breakage test 对每一批次产品进行严格的破坏性测试
- ◆ 100% magnetic crack detection
◊ 100% 进行磁粉探伤
- ◆ Surface finish(表面处理): Powder coated (喷漆)
◆ Color code(色号): Red(红色) RAL3020 / Yellow(黄色) RAL1003



- ◆ G80 SELF-LOCK HOOK, IMPROVED
◊ 改进型80级自锁钩
- ◆ Positive lock latch is Self-Locking when hook is loaded
◊ 在负载下，钩子的锁钩会自动锁死，更安全

SLR737-EYE TYPE SAFETY HOOK 眼型安全钩

SLR737



ITEM NO.	WEIGHT kg	Wt lb	SL D	#	E	EL	LI	L	R	D	N	V
8-SLR-737-08	0.5	1.12	4.8	2x1	2x1	15x1	10x1	12x1	11x1	14x1	14x1	21x1
8-SLR-737-08	0.6	2	5	2x1	2x1	15x1	10x1	12x1	11x1	14x1	14x1	21x1
8-SLR-737-10	1.0	2.2	12	3x1.5	4x1.5	6x1.5	10x1	11x1	12x1	13x1	14x1	21x1
8-SLR-737-13	1.8	4	21	3x1.5	4x1.5	6x1.5	10x1	11x1	12x1	13x1	14x1	21x1
8-SLR-737-16	3.5	8	27	3x1.5	4x1.5	6x1.5	10x1	11x1	12x1	13x1	14x1	21x1
8-SLR-737-20	6.5	14	36	3x1.5	4x1.5	6x1.5	10x1	11x1	12x1	13x1	14x1	21x1
8-SLR-737-22	11.5	25	48	3x1.5	4x1.5	6x1.5	10x1	11x1	12x1	13x1	14x1	21x1
8-SLR-737-25	18	40	64	3x1.5	4x1.5	6x1.5	10x1	11x1	12x1	13x1	14x1	21x1
8-SLR-737-32	40	88	128	3x1.5	4x1.5	6x1.5	10x1	11x1	12x1	13x1	14x1	21x1

Useless hook is 4 times the Working Load Limit 無駄な力は作業荷重の4倍

Regular mark 常规标记:

MARK 标记	号	-S	WLL 0.15T	SLR	CE	18-1
DESCRIPTION 说明	CHAIN TYPE 链条式	GRADE: 45 强度等级	WORKING LOAD LIMIT 工作负荷	PRODUCTION 生产地	CE CERTIFIED CE 认证合格	WALZCHEN 生产厂商



WARNING 警告 Please refer to the instruction manual for safety information.

G80 SELFLOCK HOOK IMPROVED 改进型80级自锁钩

- ◆ Forged super alloy steel - Quenched and Tempered.
- ◇ 高强度合金钢锻造 - 淬火及回火处理。
- ◆ Suitable for EN818-2 G80 chain.
- ◇ 与EN818-2标准80级链条配合使用。
- ◆ Initially proof test at 2.5 times Working Load Limit.
- ◇ 零件在工作拉力2.5倍下进行验证测试。
- ◆ Fatigue tested at 1.5 times Working Load Limit for 20000 cycles.
- ◇ 抽样进行20000次疲劳测试。
- ◆ Breakage test for each product type with sample breaking test.
- ◆ 100% magnetic crack detection.
- ◇ 100% 进行磁粉探伤。
- ◆ Surface finish (表面处理) : Powder painted (喷漆)
- ◆ Colour code (色号) : Red (红色) :RAL 3020 / Yellow (黄色) :RAL 1020.

- ◆ Positive lock when it Self-Locking when hook is loaded.
- ◇ 在负载下，钩子的自锁结构会自动闭合，更安全。



SLR738-G80 SELFLOCK HOOK IMPROVED
80级改进型羊角型自锁安全钩

SLR738

ITEM NO.	WEIGHT kg/l	WLL (T)	SL (T)	A	B	E	E1	L1	L	H	N	M
6-8	3.47	1.0	4.8	35.0	35.1	13.0	28.1	30.0	134.0	23.1	33.0	13.0
718-8	6.5	2	8	72.0	72.1	16.0	58.1	60.0	268.0	48.1	68.0	28.0
10-8	13.0	4.0	16	128.0	128.1	20.0	96.1	100.0	432.0	96.1	128.0	56.0
13-8	25.0	8.0	32	256.0	256.1	32.0	192.1	200.0	864.0	192.1	256.0	112.0
16-8	5	16	64	512.0	512.1	40.0	384.1	400.0	1728.0	384.1	512.0	224.0
18(20)-8	12.5	3.5	14	280.0	280.1	45.0	450.1	475.0	2016.0	450.1	580.0	260.0
22-8	32.0	10	40	704.0	704.1	56.0	704.1	735.0	3200.0	704.1	896.0	400.0
26-8	72.0	22.5	90	1584.0	1584.1	70.0	1584.1	1665.0	7040.0	1584.1	2016.0	900.0
32-8	180	56.25	225	3960.0	3960.1	88.0	3960.1	4095.0	17640.0	3960.1	5040.0	2250.0

1. Initially test at 4 times the Working Load Limit 验证4倍工作拉力验证

Regular mark 常规标记:

MARK 标记	10	-8	WLL 3.5T	SLR	CE	18-1
DESCRIPTION 说明	10mm 10mm	8mm 8mm	WORKING LOAD LIMIT 工作力	SELF LOCKING 自锁	CE OFFICER CE 认证	18mm 18mm

NOT TO BE USED FOR LIFTING
不得用于起重

WARNING 警告



G80 SELFLOCK HOOK IMPROVED 改进型80级自锁钩

- ◆ Forged super alloy steel- Quenched and Tempered
○ 高强度合金特种合金钢锻造而成，经过热处理
- ◆ Suitable for EN1218-2 G80 chain
○ 与EN1218-2标准的链条配套使用
- ◆ Individually proof test at 2.5 times Working Load Limit
○ 零件在工作拉力的2.5倍进行验证测试
- ◆ Fatigue test at 1.5 times Working Load Limit for 20000 cycles
○ 吊钩进行20000次疲劳测试
- ◆ Breakage test 对每一批次产品进行严格的抽样破坏测试
- ◆ 100% magnetic crack detection
○ 100% 进行磁粉探伤
- ◆ Surface finish(表面处理): Powder coated (喷漆)
◆ Color code(色号): Red(红色)RAL3020 / Yellow(黄色)RAL1003

- ◆ Positive lock, locking Self-Locking when hook is closed

◆ 在其闭下，钩子能自动锁闭而自动锁紧，更安全

SLR739-G80 SELF-LOCKING HOOK
80级本角安全钩 (配双翼螺母)

SLR739

	ITEM NO.	WEIGHT kg	WLL T	RL (T)	A	B	E	E1	L1	L	H	N	M
4	8-SLR739-6	0.45	1.0	4.8	41.0	37.1	32.7	35.1	32.5	104.0	26.1	170.8	12.5
	8-SLR739-7/9	1.35	3	8	42.5	33.3	40.3	35.1	116.8	102.2	26.1	200.8	19.1
6	8-SLR739-10	1.42	3.15	8.0	42.5	40.1	45.3	45.2	116.2	102.2	30.1	211	19.1
	8-SLR739-13	1.80	5.0	10.0	46.5	45.1	47.5	47.2	126.4	106.4	40.1	221	19.1
8	8-SLR739-16	2	6	12	51.5	47.1	53.1	47.2	136.4	116.4	45.1	232	19.1
	8-SLR739-18/20	18	12.5	16	51.1	51.1	51.1	42.2	225.8	225.8	50.2	311	19.1
10	8-SLR739-22	17.8	15	18	51.1	47.1	50.1	42.2	225.8	225.8	50.2	311	20.1
	8-SLR739-26	21.2	17.5	20.5	51.1	47.1	49.1	46.1	225.8	225.8	50.2	311	20.1
12	8-SLR739-32	38	25	25	51.1	50.1	50.1	46.1	225.8	225.8	50.2	311	20.1

Ultimate load and force for Working Load Limit 破断力及工作拉力限值

Regular mark 常规标记:

MARK 标志	10	15	WLL 0.15T	SLR	CE	18-1
CE MARKING 标志	CE MARKING 标志	CE MARKING 标志	WLL 0.15T 工作拉力	SLR 自锁钩	CE CE 标志	18-1 生产批号



WARNING 警告 Please read the instruction manual before use.

G80 SELFLOCK HOOK IMPROVED 改进型80级自锁钩

- ◆ Forged super alloy steel - Quenched and Tempered
- ◇ 高强度合金钢锻造 - 淬火及回火处理
- ◆ Suitable for EN818-2 G80 chain
- ◇ 与EN818-2 80级索具规格配合使用
- ◆ Initially proof test at 2.5 times Working Load Limit
- ◇ 组件在工作拉力2.5倍下进行验证测试
- ◆ Fatigue tested at 1.5 times Working Load Limit for 20000 cycles
- ◇ 抽样进行20000次疲劳测试
- ◆ Breakage test at 1.5 times Working Load Limit for 20000 cycles
- ◇ 抽样进行20000次疲劳测试
- ◆ 100% magnetic crack detection
- ◇ 100% 进行磁粉探伤
- ◆ Surface finish (表面处理): Powder painted (喷漆)
- ◆ Colour code (色号): Red (红色) / RAL 3020 / Yellow (黄色) / RAL 1023

- ◆ Positive lock when it Self-Locking when hook is loaded

- ◇ 在负载下，钩子的自锁结构会自动锁死，更安全



SLR755-G80 SELFLOCK HOOK IMPROVED 改进型80级自锁钩

SLR755



ITEM NO.	WEIGHT kg	WLL (T)	SL (T)	A±1	B±1	E	E1	L1	L	H	N	M
6-B	0.71	1.1	445	35±1	32±1	32±1	38±1	70±1	70±1	35±1	15	27±1
71B-B	1.35	2.1	8	38±1	35±1	35±1	42±1	82±1	82±1	38±1	30	31±1
10-B	1.76	2.8	10	42±1	38±1	38±1	45±1	85±1	85±1	42±1	35±1	33±1
13-B	2.51	4.1	14	48±1	42±1	42±1	50±1	95±1	95±1	48±1	40±1	37±1
16-B	3.25	5.3	18	52±1	45±1	45±1	55±1	105±1	105±1	52±1	45±1	40±1
18(20)-B	3.9	6.3	20	55±1	48±1	48±1	58±1	110±1	110±1	55±1	50±1	42±1
22-B	5.2	8.5	25	62±1	52±1	52±1	65±1	125±1	125±1	62±1	55±1	45±1
26-B	6.8	11	30	68±1	58±1	58±1	72±1	135±1	135±1	68±1	60±1	48±1
32-B	9.1	15	40	75±1	65±1	65±1	80±1	150±1	150±1	75±1	65±1	52±1

1. Static load is 4 times the Working Load Limit 静态拉力是工作拉力的4倍

Regular mark 常规标记:

MARK 标记	10	-8	WLL 3.5T	SLR	CE	10-1
DESCRIPTION 描述	10 TON 10T 100KN	8 TON 8T 80KN	WORKING LOAD LIMIT 工作拉力	SHOCK LOAD TEST 冲击测试	CE OFF 100471 CE 认证	10 TON 10T 100KN

NOTICE: Please read the instruction carefully before use.

WARNING 警告



G80 SPECIAL EYE SELF-LOCKING HOOK 80级 异型眼型安全钩

- ◆ Forged super alloy steel- Quenched and Tempered
 - 高强度合金特种合金钢锻造而成，经过热处理
 - ◆ Suitable for EN138-2 G80 chain
 - 与EN138-2H级链环组合使用
 - ◆ Individually proof test at 2.5 times Working Load Limit
 - 零件在工作拉力的2.5倍进行验证测试
 - ◆ Fatigue tested at 1.5 times Working Load Limit for 20000 cycles
 - 在1.5倍工作拉力下进行20000次疲劳测试
 - ◆ Breakage test
 - 对每一件产品进行严格的破坏性破坏测试
 - ◆ 100% magnetic crack detection
 - 100% 进行磁粉探伤
 - ◆ Surface finish (表面处理): Powder coated (喷塑)
 - ◆ Colour code (色号): Blue (蓝色) RAL5015
- ◆ Pushed lock latch in Self-Locking when hook is loaded.
 ○ 在负载下，钩子的自锁结构会自动锁死，更安全



SLR077-G80 SPECIAL EYE SELF-LOCKING HOOK
80级 异型眼型安全钩

SLR077



ITEM NO.	WEIGHT kg	WLL (T)	B.L (T)	B+1.5	D+1.5	E+2	K+2	H+1	L+1	C+2
8-SLR77-78	0.69	3	8	23	26	34	13.1	22	11	40
8-SLR77-10	1.3	6.18	12.5	43	50	42	19.1	28	14.5	50
8-SLR77-13	2.19	9.3	21.3	60	68	60	26.4	37	17	59
8-SLR77-16	3.33	12	32	81	90	79	32.8	48	23	72

Working Load is 4 times the Working Load Limit (额定工作拉力为WLL的4倍)

Regular mark 常规标记:

MARK 标志	10	15	WLL 5.15T	SLR	CE	15-1
CE MARKING 标志	CE MARK 标志	CE MARK 标志	WORKING LOAD LIMIT 工作拉力	PRODUCTION 生产	CE MARKING CE 标志	WLL 5.15T 工作拉力



WARNING 警告 Please read the instruction manual before use.
使用前请仔细阅读说明书。

G80 U.S. TYPE EYE SELF-LOCKING HOOK 80级 美式眼型安全钩

- ◆ Forged super alloy steel- Quenched and Tempered
- ◇ 高强度合金钢材料经淬火和回火处理
- ◆ Individually proof test at 2.5 times Working Load Limit
- ◇ 每件产品工作拉力为2.5倍额定工作拉力
- ◆ Fatigue tested at 1.5 times Working Load Limit for 20000 cycles
- ◇ 在1.5倍工作拉力下连续进行20000次疲劳测试
- ◆ Breakage test
- ◇ 对每一批产品进行严格的破坏性测试
- ◆ 100% magnalux crack detection
- ◇ 100% 进行磁粉探伤
- ◆ With latch
- ◇ 每件产品均配有保险舌片
- ◆ Surface finish (表面处理): Powder painted (粉型)
- ◆ Colour code (色号): Red (红色) RAL3020
- Yellow (黄色) RAL1003



- ◆ Fasten lock latch & Self-Locking when hook is loaded
- ◇ 在负载下，由于可锁装置的咬合动作，使安全

SLR008-G80 U.S. TYPE EYE SELF-LOCKING HOOK
80级 美式眼型安全钩

SLR008



ITEM NO.	WEIGHT (Kg)	WLL (T)	BL (T)	B±1.5	D±1.5	H±1	K±2	L±3	φ±2
6-SLR008-6	0.45	1.2	1.1	20	14.5	20	100	130	64
8-SLR008-7.8	0.60	2	1.8	25	17	25	132	173	42
8-SLR008-10	1.35	3.2	2.9	42	32.5	37	171	217	55
8-SLR008-13	3.77	5.4	4.9	55	42	47	215	272	65
8-SLR008-16	5.5	8.2	7.3	75	57	62	255	320	75

Ultimate load is 4 times Eye Working Load Limit 极限拉力是工作拉力为4倍

Regular mark 常规标记:

MARK 标记	10	16	WLL 3.15T	SLR	CE	10-1
DESCRIPTION 说明	10mm 10T 100mm	16mm 16T 160mm	WORKING LOAD LIMIT 工作拉力	MARKED WITH S-9007	CE OFFICIAL 认证标志	MARK NUMBER 标记号

Not to be used for lifting
不得用于吊运

WARNING 警告



ITALY TYPE EYE SELF-LOCKING HOOK 意式眼型安全钩

- ◆ Forged super alloy steel - Quenched and tempered
○ 锻造合金钢经淬火及回火处理
- ◆ Individually proof test at 2.5 times Working Load Limit
○ 每件安全工作拉力之2.5倍进行验证测试
- ◆ Fatigue tested at 1.5 times Working Load Limit for 20000 cycles
○ 在1.5倍工作拉力下经体进行20000次疲劳测试
- ◆ Breakage test
○ 对每一件产品进行严格的破坏性断裂测试
- ◆ 100% magniflux crack detector
○ 100% 进行磁粉探伤
- ◆ With latch
○ 每件产品均配有保险齿片
- ◆ Surface finish (表面处理): Powder painted (喷漆)
◆ Color code (颜色): Red (红色)RAL3020
Yellow (黄色)RAL1015



- ◆ Positive lock when is closed - Locking when hook is loaded.
○ 在负荷下，钩子的保险销会自动闭锁，更安全

SLR289-ITALY TYPE EYE SELF-LOCKING HOOK 意式眼型安全钩

SLR289



ITEM NO.	WEIGHT (kg)	WLL (T)	BL (T)	A±1.5	B±1.5	C±1.5	E±1	K±2	L±2	φ±2
8-SLR289-7.8	0.81	2	8	29	31	29	30	110	142	25.0
8-SLR289-10	1.1	3.15	12.8	32	40	40	34	130	101	25
8-SLR289-18	3.67	9	21.0	65	91	56	70	220	256	33

Working Load is 4 times the Working Load Limit (依据安全工作拉力之4倍)

Regular mark 常规标记:

MARK 标志	号	-S	WLL 5.15T	SLR	CE	18-1
CE MARKING 标志	CLASS 5.15T 等级	CLASS 5.15T 等级	WORKING LOAD LIMIT 工作拉力	MANUFACTURER 制造商	CE CERTIFIED CE 认证	WATCH REAR SIDE 后侧检查



WARNING 警告 Please refer to the instruction manual for safety information.

G80 EYE SELF-LOCKING HOOK 80级 眼型安全钩

- ◆ Forged super alloy steel- Quenched and Tempered
◇ 高强度合金材料经淬火及回火处理
- ◆ Suitable for EN818-2 G80 chain
◇ 与EN818-2 G80级链条配合使用
- ◆ Individually proof test at 2.5 times Working Load Limit
◇ 每件按工作拉力的2.5倍进行验证测试
- ◆ Fatigue tested at 1.5 times Working Load Limit for 20000 cycles
◇ 在1.5倍工作拉力下每件进行20000次疲劳测试
- ◆ Breakage test
◇ 对每一批次产品进行严格的破坏测试
- ◆ 100% magnificus crack detection
◇ 100% 进行裂纹检测
- ◆ Surface finish (表面处理) : Powder-plated (粉末)
- ◆ Colour code (色码) : Blue (蓝色) RAL5015

- ◆ Positive lock lock at Self-Locking screw hook is locked.
◇ 在色码下, 钩子的自锁结构会自锁闭合, 很安全

SLR336-G80 EYE SELF-LOCKING HOOK
80级 眼型安全钩

SLR336



ITEM NO.	WEIGHT (kg)	WLL (T)	RL (T)	B±1.5	D±1.5	K±2	H±1	L±3	Φ±2
8-SLR336-6	0.48	1.12	4.44	20	22	110.5	20	141	54
8-SLR336-7/8	0.75	2	8	35	25	156	24	173	49
8-SLR336-10	1.25	3.15	12.0	45	32	189	28	210	58
8-SLR336-13	2.5	5.2	21.2	54	40	208	41	235	68
8-SLR336-14	3.4	6	22	60.5	50	204.0	50	228	65
8-SLR336-18/20	5.47	12.5	50	74.6	61	214	62	273	10
8-SLR336-22	11.95	16	63	87	72	220	85	418	10
8-SLR336-25	17.25	21.2	84.5	95	80	205	74	422	110
8-SLR336-32	40.7	26.5	105	116	105	471.8	96	512.5	155

U-Block Hook is 4 times the Working Load Limit 钩型拉力器工作拉力为4倍

Regular mark 常规标记:

MARK 标记	10	-8	WLL 3.15T	SLR	CE	18-1
DESCRIPTION 说明	CHAIN RING 链条环	SHACKLE 卸扣	WORKING LOAD LIMIT 工作拉力	MARKING ITEM 标记项目	CE OFFICIAL CE 认证	MARK NUMBER 标记号码



G80 SELF-LOCK HOOK 80级自锁钩

- ◆ Forged super alloy steel- Quenched and Tempered
- ◇ 高强度合金钢经淬火及回火处理
- ◆ Inductively proof test at 2.5 times Working Load Limit
- ◇ 经感应工作拉力倍2.5倍进行验证测试
- ◆ Fatigue tested at 1.5 times Working Load Limit for 20000 cycles
- ◇ 经疲劳进行20000次疲劳测试
- ◆ Breakage test
- ◇ 对每一件次产品进行严格的材料破坏测试
- ◆ 100% magnetic crack detection
- ◇ 100% 进行磁粉探伤



SLR765-G80 EUROPEAN TYPE EYE SELF-LOCKING HOOK
80 级欧式型安全钩

SLR765

ITEM NO.	WEIGHT (KG)	WLL (T)	B.L (T)	Ø	D±1	E±1	H±1	R±2	M±2	L±3
8-SLR-765-08	0.5	1.12	4.48	21	43	29	30	170	70	143
8-SLR-765-08	0.5	1.12	4.48	21	43	29	30	170	70	143
8-SLR-765-10	1.5	3.15	12.6	34.3	68.6	45	30	189	108	212.5
8-SLR-765-13	2.7	5.3	21.3	40	80	53.5	30	206	126.5	270
8-SLR-765-16	5.7	9	32	50	100	67	30	254	170.5	331
8-SLR-765-20	7.0	12.5	39	60	120	80	30	277	192.5	360
8-SLR-765-22	11.2	16	60	70	134	88	30	319.5	216	417

(Minimum load is 4 times the Working Load Limit 最小拉力是工作拉力的4倍)

◆ Please mark / 请做标记: 10-3-SLR-AT-130 SLR-80AT-1114809 (重量)

- ◆ Forged super alloy steel- Quenched and Tempered
- ◇ 高强度合金钢经淬火及回火处理
- ◆ Inductively proof test at 2.5 times Working Load Limit
- ◇ 经感应工作拉力倍2.5倍进行验证测试
- ◆ Fatigue tested at 1.5 times Working Load Limit for 20000 cycles
- ◇ 经疲劳进行20000次疲劳测试
- ◆ Breakage test
- ◇ 对每一件次产品进行严格的材料破坏测试
- ◆ 100% magnetic crack detection
- ◇ 100% 进行磁粉探伤



SLR770-EYE SELF-LOCKING HOOK
80 级眼型安全钩

SLR770

ITEM NO.	WEIGHT (kg)	WLL (T)	B.L (T)	B±1	E±1	Ø±1	H±1	K±2	L±1
8-SLR770-08	0.81	2	8	33.5	36	48	27	138	12
8-SLR770-10	1.41	3.15	12.6	40	40	50	30.5	160	15
8-SLR770-13	2.01	4.2	16.8	48	48	64	33	200	20
8-SLR770-16	4.45	8	32	60.5	60	77	45	250	27

(Minimum load is 4 times the Working Load Limit 最小拉力是工作拉力的4倍)

◆ Please mark / 请做标记: 10-3-SLR-AT-130 SLR-80AT-1114809 (重量)



WARNING 警告 This product is not to be used for lifting personnel.

G80 SELF-LOCK HOOK 80级自锁钩

With side trigger
开关在侧面



- ◆ Forged super alloy steel - Quenched and Tempered
◦ 高强度合金钢材料经淬火及回火处理
- ◆ Suitable for EN318-2 G80 chain
◦ 与EN318-2标准80级链配合使用
- ◆ Individually proof test at 2.5 times Working Load Limit
◦ 每件经工作拉力的2.5倍进行验证测试
- ◆ Failure tested at 1.5 times Working Load Limit for 20000 cycles
◦ 在1.5倍工作拉力下抽样进行20000次疲劳测试
- ◆ Breakage Test - 10 times per batch to ensure strict control of the breaking point
◦ 每批10次破坏测试以确保严格的断裂点控制
- ◆ 100% magnification crack detection - 100% 进行磁粉探伤
- ◆ Surface finish (表面处理) : Powder painted (喷漆)
- ◆ Colour/finish (色号) : Red (红色) (RAL3020) / Yellow (黄色) (RAL1003)

- ◆ Positive identification Self-Locking when hook is closed.
◦ 在关闭下, 钩子的自锁结构会自动锁定, 更安全

SLR663-G80 SELF-LOCKING HOOK 80级埋入式半圆安全钩

SLR663

ITEM CODE 货号	WEIGHT (KG)	WLL (T)	B.L (T)	A±0.5	B±0.5	C±0.1	E±0.5	M±0.5	H±0.3	L±1.5
SLR-053-7/8-8	0.702	2	8	27	8	11.5	32.5	16	20	184
SLR-053-10-8	2.25	3.15	12.8	48	12	14.7	44.3	115	22	200
SLR-063-12-8	4.57	5.5	21.2	60	15	16.5	49	153	25	250

Working load is 4 times the Working Load Limit 使用拉力是工作拉力的4倍

Regular mark 常规标记:

MARK 标记	10	±8	WLL 3.15T	SLR	CE	18-1
DESCRIPTION 说明	TYPE 型号	GRADE 等级	WORKING LOAD LIMIT 工作拉力	MANUFACTURER 生产商	CE CERTIFICATE CE 证书	BATCH NUMBER 批号

G80 U.S. TYPE CLEVIS SELF-LOCKING HOOK 80级美式羊角安全钩

- ◆ Forged super alloy steel- Quenched and Tempered
◇ 高级合金钢经特殊冶金锻造而成，经过热处理
- ◆ Industrially proof load at 2.5 times Working Load Limit
◇ 工业级工作拉力为2.5倍额定荷载
- ◆ Fatigue tested at 1.5 times Working Load Limit for 20000 cycles
◇ 在1.5倍工作拉力下进行20000次疲劳测试
- ◆ Breakage test
◇ 对每一批次产品进行严格的破坏性测试
- ◆ 100% magnetic crack detection
◇ 100% 进行磁力探伤
- ◆ With latch
◇ 每个产品均配有闭锁舌片
- ◆ Surface finish (表面处理): Powder coated (喷塑)
- ◆ Colour code (色号): Red (红色) RAL3020
Yellow (黄色) RAL1015

- ◆ Positive indication in Self-Locking when hook is loaded.
◇ 在负载下，钩子的闭锁结构会自动锁合，更安全

SLR009-G80 U.S. TYPE CLEVIS SELF-LOCKING HOOK
80级 美式羊角安全钩

SLR009



ITEM NO.	WEIGHT (Kg)	WLL (T)	B.L (T)	A±0.5	B±1.5	H±1	K±2	L±3	Ø±2
8-SLR9-6	0.48	1.2	4.3	9	20	21	47	122	34
8-SLR9-7B	0.66	2	8	10	25	30	159	195	42
8-SLR9-10	1.4	3.2	12.8	12	42	51	142	200	55
8-SLR9-13	3.65	5.4	21.6	16	55	61	175	245	65
8-SLR9-15	5.0	7.5	32.8	18.5	65	72	204	295	70

Working Load is 4 times the Working Load Limit (额定工作拉力为额定荷载4倍)

Regular mark 常规标记:

MARK 标志	10	15	WLL 3.2T	SLR	CE	15-1
CE MARKING 标志	CE MARK 标志	CE MARK 标志	WORKING LOAD LIMIT 工作拉力	PRODUCT 产品	CE MARKING CE 标志	WLL 15.0T 工作拉力



WARNING 警告 Please read the instruction manual before use.
使用前请仔细阅读说明书。

G80 SPECIAL CLEVIS SELF-LOCKING HOOK 80级 异型羊角安全钩

- ◆ Forged super alloy steel- Quenched and Tempered
- ◇ 高强度合金钢锻造和合金钢热处理, 经过淬硬
- ◆ Suitable for EN818-2 G80 chain
- ◇ 与EN818-2标准40号链条配合使用
- ◆ Individually proof test at 2.5 times Working Load Limit
- ◇ 每件在工作拉力2.5倍下进行验证测试
- ◆ Fatigue tested at 1.5 times Working Load Limit for 20000 cycles
- ◇ 在1.5倍工作拉力下维持运行20000次疲劳测试
- ◆ Breakage test
- ◇ 对每一批产品进行严格的抽样破坏测试
- ◆ 100% magnetic crack detection
- ◇ 100% 磁粉探伤检测
- ◆ Surface finish (表面处理): Powder painted (粉型)
- ◆ Colour code (色号): Blue (蓝色) RAL5010.
- ◆ Positive lock with a Self-Locking when hook is opened
- ◇ 在此钩下, 钩子的自动锁定会自由锁定, 更安全



SLR078-G80 SPECIAL CLEVIS SELF-LOCKING HOOK
80级 异型羊角安全钩

SLR078



ITEM NO.	WEIGHT (kg)	WLL (T)	BL (T)	A±1.5	B±1.5	E±2	K±2	H±1	L±1	Φ±2
8-SLR78-78	6.66	5	5	9.5	39	34	131	22	95.0	40
8-SLR78-10	1.25	1.15	12.0	43	42	101	26	52.0	50	
8-SLR78-11	2.15	1.8	21.2	75	90	119	185.4	31	225	50
8-SLR78-16	3.8	3	32	115.5	81	70	235	32	295	72
8-SLR008-16	5.5	4.2	33.8	67	91	92	286	220	78	

Ultimate load is 4 times the Working Load Limit 极限拉力是工作拉力4倍

Regular mark 常规标记:

MARK 标记	10	-8	WLL 3.15T	SLR	CE	10-1
DESCRIPTION 说明	CHAIN RING 圆环	CHAIN RING 圆环	WORKING LOAD LIMIT 工作力	MARKING CODE 标记	CE OFFERED CE 认证	MARK NUMBER 标记

NOTICE: Please read the instruction manual carefully before use.

WARNING 警告



ITALY TYPE CLEVIS SELF-LOCKING HOOK 意式羊角安全钩

- ◆ Forged super alloy steel - Quenched and tempered
- 锻造合金钢经淬火及回火处理
- ◆ Individually proof test at 2.5 times Working Load Limit
- 每件安全工作拉力之2.5倍进行验证测试
- ◆ Fatigue tested at 1.5 times Working Load Limit for 20000 cycles
- 在1.5倍工作拉力下经体进行20000次疲劳测试
- ◆ Breakage test
- 对每一件产品进行严格的破坏性断裂测试
- ◆ 100% magniflux crack detector
- 100% 进行磁粉探伤
- ◆ With latch
- 每件产品均配有保险齿扣
- ◆ Surface finish (表面处理): Powder painted (喷漆)
- ◆ Colour code(颜色): Red(红色)RAL3020/Yellow (黄色)RAL1003



- ◆ Pushing lock takes to SELF-LOCKING when handle is knotted.
- 在压力下，钩子的自锁部和安全齿扣合，要安全

SLR248-ITALY TYPE CLEVIS SELF-LOCKING HOOK
意式羊角安全钩

SLR248



ITEM NO.	WEIGHT (Kg)	WLL (T)	B.L (T)	A ± 1.5	B ± 1.5	E ± 2	K ± 2	L ± 3	Ø ± 2
8-SLR248-7.8	0.64	2	8	5.5	20	33	94	132	20.5
8-SLR248-10	1.14	3.15	12.5	12.5	40	54	105	174	45
8-SLR248-18	3.45	8	21.8	15.5	58	70	182	250	75

Working Load is 4 times the Working Load Limit (安全工作拉力是4倍)

Regular mark 常规标记:

MARK 标记	10	15	WLL 3.2T	SLR	CE	18-1
CE MARKING 标记	CE MARK 标记	CE MARK 标记	WORKING LOAD LIMIT 工作拉力	MANUFACTURER 制造商	CE CERTIFIED CE 认证	WATCH REAR SIDE 后侧检查



WARNING 警告 Read and understand the instructions before use.

G80 CLEVIS SELF-LOCKING HOOK 80级 羊角安全钩

- ◆ Forged super alloy steel- Quenched and Tempered
- ◇ 高强度合金材料经淬火及回火处理
- ◆ Suitable for EN818-2 G80 chain
- ◇ 与EN818-2 2级G80链搭配使用
- ◆ Individually proof test at 2.5 times Working Load Limit
- ◇ 零件按工作拉力的2.5倍进行验证测试
- ◆ Fatigue tested at 1.5 times Working Load Limit for 20000 cycles
- ◇ 在1.5倍工作拉力下循环进行20000次疲劳测试
- ◆ Breakage test
- ◇ 对每一批次产品进行严格的破坏测试
- ◆ 100% magniflex crack detection
- ◇ 100% 进行微裂纹检测
- ◆ Surface finish (表面处理) : Powder painted (喷涂)
- ◆ Colour code (色码) : Blue (蓝色)RAL5015

- ◆ Positive lock lock at Self-Locking screw hook is locked.
- ◇ 在负载下, 钩子的自锁结构会自动锁合, 更安全

SLR335-G80 CLEVIS SELF-LOCKING HOOK 80级 羊角安全钩

SLR335



ITEM NO.	WEIGHT (kg)	WLL (T)	B.L (T)	A ±1.5	B ±1.5	K ±2	H ±1	L ±3	φ ±2
8-SLR335-0	0.5	1.12	4.48	7.5	29	09	29	131	50
8-SLR335-7/8	0.3	2	6	9.5	35	110.0	34	100	48
8-SLR335-10	1.42	3.15	12.5	12	42	144	29	104	52
8-SLR335-13	3	5.2	21.2	18	54	181.5	41	251	69
8-SLR335-16	5.5	8	32	17.5	63.5	215	50	242	68
8-SLR335-18/20	8.75	12.5	50	25	94.5	295	62	343	90
8-SLR335-22	12.3	16	64	25.5	95	312	66	361	96
8-SLR335-28	20.0	21.2	84.8	33	110	317	74	448	110

Working Load is 4 times the Working Load Limit 安全工作能力是极限力的4倍

Regular mark 常规标记:

MARK 标记	10	-8	WLL 3.15T	SLR	CE	18-1
DESCRIPTION 说明	GRADE 10 10级钢	GRADE 8 8级钢	WORKING LOAD LIMIT 工作拉力	MARKING ITEM 标记项目	CE CERTIFICATE CE 认证书	MARK NUMBER 标记号



G80 EUROPEAN TYPE CLEVIS SELF-LOCKING HOOK 80级欧式羊角安全钩

- ◆ Forged super alloy steel- Quenched and Tempered
- ◆ 高强度合金钢经淬火及回火处理
- ◆ Industrially proof test at 2.5 times Working Load Limit
- ◆ 工业级工作拉力经2.5倍进行验证测试
- ◆ Fatigue tested at 1.5 times Working Load Limit for 20000 cycles
- ◆ 疲劳进行20000次疲劳测试
- ◆ Breakage test
- ◆ 对每一件次产品进行严格的破坏性测试
- ◆ 100% magnifying crack detection
- ◆ 100% 进行缺陷检测




SLR766-G80 EUROPEAN TYPE CLEVIS SELF-LOCKING HOOK
80 级欧式羊角安全钩

SLR766

ITEM NO.	WEIGHT (KG)	WLL (T)	B.L (T)	A±0.5	B±1	E±1	H±1	R±2	M±2	L±3
B-SLR-766-08	0.6	1.12	4.57	7.5	32	26	20	95	29	131
B-SLR-766-08	0.8	1.5	8	8.5	36	30.5	25	120	31	145
B-SLR-766-10	1.8	3.15	12.0	12	48	46	30	144	50.5	196.8
B-SLR-766-12	2.8	5.5	21.3	15	70	53.5	40.5	167	74.5	291
B-SLR-766-16	5.0	8	32	17.0	70	62	50.0	217	120.6	385
B-SLR-766-20	9.0	12.5	50	23	85	70.5	62	235	152.8	567.6
B-SLR-766-22	12.1	15	63	25.5	96	90	66	276.5	205	811

G80 CLEVIS SELF-LOCKING HOOK G80 羊角安全钩

- ◆ Forged super alloy steel- Quenched and Tempered
- ◆ 高强度合金钢经淬火及回火处理
- ◆ Industrially proof test at 2.5 times Working Load Limit
- ◆ 工业级工作拉力经2.5倍进行验证测试
- ◆ Fatigue tested at 1.5 times Working Load Limit for 20000 cycles
- ◆ 疲劳进行20000次疲劳测试
- ◆ Breakage test
- ◆ 对每一件次产品进行严格的破坏性测试
- ◆ 100% magnifying crack detection
- ◆ 100% 进行缺陷检测



SLR771-CLEVIS SELF-LOCKING HOOK
G80 羊角安全钩

SLR771

ITEM NO.	WEIGHT (kg)	WLL (T)	B.L (T)	A±1	B±1	E±1	Ø±1	H±1	K±2	L±3
B-SLR771-08	0.75	2	8	9.5	32.5	35	45	21	115	90.5
B-SLR771-10	1.47	3.15	13.0	13.3	48	46	50	30.9	55.1	154
B-SLR771-12	2.55	5.5	21.3	15	62	66	58	20	175	244
B-SLR771-16	4.21	9	32	18.5	67.5	66	77	40	250	335

[Working Load is 4 times the Working Load Limit 使用拉力是工作拉力4倍]

★ Please mark / 请标注: 1) 10-3 3611327 02 SLR 766 (H) NL002 (英/美)



WARNING 警告 This product is not to be used for lifting personnel.

G80 SELF-LOCKING HOOK 80级 特殊羊角安全钩

- ◆ Forged super alloy steel- Quenched and Tempered
- ◇ 高强度高韧性合金钢锻造而成，经过热处理
- ◆ Individually proof test at 2.5 times Working Load Limit
- ◇ 每件按工作能力的2.5倍进行验证测试
- ◆ Fatigue tested at 1.5 times Working Load Limit for 20000 cycles
- ◇ 钩体进行20000次疲劳测试
- ◆ Breakage test
- ◇ 对每一批产品进行严格的破坏性测试
- ◆ 100% magnetic crack detection
- ◇ 100% 进行磁粉探伤

SLR489-G80 SELF-LOCKING HOOK 80级 特殊羊角安全钩

SLR489




ITEM NO.	WEIGHT (kg)	WLL (T)	B.L. (T)	A±1	B±1	E±2	E1±2	L1±3	L±3
B-SLR489-10	0.02	4.2	10.5	13	43	26	44	118	100

1. Working Load is 4 times the Working Load Limit 使用能力是工作能力的4倍

G80 ANGLE ROTATED SAFETY HOOK 80级 羊角旋转安全钩

- ◆ Forged super alloy steel- Quenched and Tempered
- ◇ 高强度高韧性合金钢锻造而成，经过热处理
- ◆ Individually proof test at 2.5 times Working Load Limit
- ◇ 每件按工作能力的2.5倍进行验证测试
- ◆ Fatigue tested at 1.5 times Working Load Limit for 20000 cycles
- ◇ 钩体进行20000次疲劳测试
- ◆ Breakage test
- ◇ 对每一批产品进行严格的破坏性测试
- ◆ 100% magnetic crack detection
- ◇ 100% 进行磁粉探伤
- ◆ With Drawing 带图纸



SLR007-G80 ANGLE ROTATED SAFETY HOOK 80级 羊角旋转安全钩

SLR007

ITEM NO.	WEIGHT (kg)	WLL (T)	B.L. (T)	Φ	B	C	L	K	E	F
B-SLR007-05	0.26	5.12	4.43	34±1	6±1	32±2	181.6±0.8	145±0.5	32±0.5	26±0.2
B-SLR007-718	1.3	9	8	60±1	90±1	38.7±0.7	730±0.7	540±0.4	85±0.7	30±0.1

1. Working Load is 4 times the Working Load Limit 使用能力是工作能力的4倍

- ◆ Regular mark 请标注: P: 100-8 751127 C: SLR + BATCH/批号/炉号


NOTICE: This product is not to be used for lifting or pulling.

WARNING 警告



G80 SELF-LOCK HOOK 80级自锁钩

- ◆ Forged super alloy steel- Quenched and Tempered.
○ 高强度合金钢经淬火及回火处理，经过防处理。
- ◆ Suitable for EN1678-2 G80 chain.
○ 与EN1678-2 80级链条配合使用。
- ◆ Individually proof test at 2.5 times Working Load Limit.
○ 零件在工作拉力的2.5倍进行验证测试。
- ◆ Fatigue tested at 1.5 times Working Load Limit for 20000 cycles.
○ 吊钩进行20000次疲劳测试。
- ◆ Breakage test 对每一批次产品进行严格的抽样破坏测试。
○ 100% 进行破坏测试。
- ◆ Surface finish (表面处理): Powder coated (漆膜)
○ 100% 进行镀锌处理。
- ◆ Colour code (颜色): Red (红色) RAL 3020
Yellow (黄色) RAL 1003.



- ◆ Positive lock, which is Self-Locking when hook is loaded.
○ 在负载下，钩子的自锁结构会自动闭合，很安全。
- ◆ With Latching 带锁紧

SLR042-SWIVEL SELF-LOCK HOOK WITH BEARING

带轴承旋转安全钩

SLR042

ITEM NO.	WEIGHT (KG)	WLL (T)	BL (T)	A	B	C	L1	L	T	E	M2	N	#15
8-SLR-42-05	0.77	1.32	442	12.5±0.3	11.5±0.8	17.8±0.2	89±0.5	134±0.2	38±0.7	33±0.2	15±0.2	15±0.5	34
8-SLR-42-08	1.1	2	3	18±1	13±0.8	20±0.2	130±0.5	160±0.2	51±1	40±0.7	20±0.2	20±0.5	34
8-SLR-42-15	2.1	3.75	12.9	22±1	15.5±0.5	21±0.2	174±0.5	235±0.2	65±0.8	45±1	30±0.2	25±1	58
8-SLR-42-15	4	5.5	21.2	28±2	21±1	28±1	222±0.5	283±0.2	82±0.8	62±1	42±0.5	32±1	75
8-SLR-42-15	7.3	9	32	41±2	27±0.1	40±0.2	341.5±0.4	430±0.4	122±2	85±0.4	58±0.2	42±0.2	90
8-SLR-42-20	11.8	12.5	42	70±2	25.5±1	70±1	480±0.5	600±0.5	182±3	122±0.4	100±0.4	72±1	90
8-SLR-42-22	18	16	57±0.5	104±0.5	33±0.5	97±0.4	604±0.5	764±0.5	219±0.5	159±0.5	132±0.4	102±0.2	110
8-SLR-42-28	21.5	21.2	76.5	125±0.4	42±0.2	115±0.4	744±0.5	907±0.5	254±0.5	180±0.5	152±0.5	116±1	110

UL loads load 5-8 times the Working Load Limit 吊钩的拉力是工作拉力的4-8倍

Regular mark 常规标记:

MARK 标志	15	15	15	WLL 0.15T	SLR	CE	15-1
CE MARKING 标志	CE MARKING 标志	CE MARKING 标志	CE MARKING 标志	WLL 0.15T 工作拉力	SLR 自锁钩	CE CE MARKING 标志	15-1 吊钩



WARNING 警告

Do not use this hook for lifting people or other loads.


G80 U.S. TYPE SWIVEL SELF-LOCKING HOOK 80级 美式旋转安全钩

- ◆ Forged super alloy steel- Quenched and Tempered
- ◇ 高强度合金钢锻造 淬火回火处理
- ◆ Individually proof test at 2.5 times Working Load Limit
- ◇ 每件独立工作力为2.5倍额定工作力测试
- ◆ Fatigue tested at 1.5 times Working Load Limit for 20000 cycles
- ◇ 在1.5倍工作力下连续进行20000次疲劳测试
- ◆ Breakage test
- ◇ 对每一批产品进行严格的破坏性测试
- ◆ 100% magniflux crack detection
- ◇ 100% 进行磁粉探伤
- ◆ With latch
- ◇ 每件产品均配有保险舌片
- ◆ Surface finish (表面处理): Powder painted (粉型)
- ◆ Colour code (色号): Red (红色) RAL3020
Yellow (黄色) RAL1003

- ◆ Fasten lock with a Self-Locking after hook is closed
- ◇ 在关闭后，由于自锁机构的咬合而锁定，更安全
- ◆ Can be Reused under Non-critical Conditions
- ◇ 在非关键条件下可重复使用(为)

SLR010-G80 U.S. TYPE SWIVEL SELF-LOCKING HOOK 80级 美式旋转安全钩

SLR010



ITEM NO.	WEIGHT (kg)	WLL (T)	S.L. (T)	A±0.5	B±1.5	C±2	D±1	H±1	K±2	L±3	Φ±2
8-SLR10-7M	1.2	2	9	25	55	30	13	29	195	103	42
8-SLR10-10	2	3.2	12.8	35.5	42	42	15.5	31	218	216	55
8-SLR10-13	4.5	5.4	21.0	41	55	50	17	41	291	310	55
8-SLR10-15	7.35	8.2	32.8	50	65	71	21.5	52	321	329	70

Ultimate load is 4 times the Working Load Limit 极限拉力是工作力为4倍

- ◆ Page 10/16 (详细图) / 15-3 VAL-2.2T (T: 54 R - GAT OH NUMBER (型号)

SLR010-G80 U.S. TYPE SWIVEL SELF-LOCKING HOOK 80级 美式旋转安全钩 A型

SLR010



ITEM NO.	WEIGHT (kg)	WLL (T)	S.L. (T)	A±0.5	B±1.5	C±2	D±1	H±1	K±2	L±3	Φ±2
8-SLR10-7M-A	0.5	2	9	N/A	55	30	15.5	29	144	173	42

Ultimate load is 4 times the Working Load Limit 极限拉力是工作力为4倍

- ◆ Page 10/16 (详细图) / 15-3 VAL-2.2T (T: 54 R - GAT OH NUMBER (型号)



G80 SPECIAL SWIVEL SELF-LOCKING HOOK 80级 异型旋转安全钩

- ◆ Forged super alloy steel - Quenched and tempered
○ 锻造高强度合金钢经淬火及回火处理
- ◆ Suitable for G80 chain
○ 适用于G80链条
- ◆ Individually proof test at 2.5 times Working Load Limit
○ 每件吊钩在工作拉力极限2.5倍进行验证测试
- ◆ Fatigue tested at 1.5 times Working Load Limit for 20000 cycles
○ 有1.5倍工作拉力下运转20000次疲劳测试
- ◆ Breakout test
○ 对每一批次产品进行严格的抽样破坏测试
- ◆ 100% magnetic crack detection
○ 100% 磁粉探伤检测
- ◆ Surface finish (表面处理): Powder painted (喷漆)
◆ Colour code (颜色): Blue (蓝色)RAL5010
- ◆ Positive lock takes to Self-Locking when hook is loaded
○ 在负载下，钩子的自锁机构和锁齿咬合，更安全
- ◆ Can be Rotated Under Non-tension Conditions
○ 在非负载条件下可旋转调节方向



SLR343-G80 SPECIAL SWIVEL SELF-LOCKING HOOK 80级 异型旋转安全钩

SLR343



ITEM NO.	WEIGHT kg	WLL ID	SL (T)	A±2	B±2	C±1	D±0.5	E±2	H±1	K±3	L±3	Ø±2
8-SLR343-4	0.76	1.12	4.48	34	32.1	22.6	11.5	25	10	160	185.6	36
8-SLR343-7/8	1.02	2	6	27.5	35	38	18	34	22	181	219	40
8-SLR343-10	1.75	3.15	12.5	34	43	42	19.5	42	28	213	254	50
8-SLR343-12	2.22	6.3	25.2	41	50	50	17	50	31	250	300	56
8-SLR343-16	5.28	8	32	55	61	70	21.6	66	33	300	375	72

Ullensgeijde is a forged Working Load Limit (WLL) hook 80级吊钩工作拉力的4倍

Regular mark 常规标记:

MARK 标志	10	15	WLL 5.15T	SLR	CE	16-1
DESCRIPTION 说明	CHAIN SIZE 链条尺寸	CHAIN AS 链条尺寸	WORKING LOAD LIMIT 工作拉力	PRODUCTION 生产地	CE CERTIFIED CE 认证	WATCH REAR SIDE 后侧标识



WARNING 警告 This is a lifting device and must be used in accordance with the instructions.

G80 U.S. TYPE SHANK SELF-LOCKING HOOK 80级 美式直杆安全钩

- ◆ Forged super alloy steel- Quenched and Tempered
- ◇ 高强度合金钢锻造- 淬火回火处理
- ◆ Individually proof test at 2.5 times Working Load Limit
- ◇ 每件安全工作拉力为2.5倍额定工作载荷
- ◆ Fatigue tested at 1.5 times Working Load Limit for 20000 cycles
- ◇ 在1.5倍工作拉力下连续进行20000次疲劳测试
- ◆ Breakage test
- ◇ 对每一件产品进行严格的破坏性测试
- ◆ 100% magniflux crack detection
- ◇ 100% 进行磁粉探伤
- ◆ With latch
- ◇ 每件产品均配有保险舌片
- ◆ Surface finish (表面处理): Powder painted (粉型)
- ◆ Colour code (色号): Red (红色) RAL3020
- Yellow (黄色) RAL1003

◆ Fasten lock latch & SELF-LOCKING when hook is loaded

◇ 在受荷下, 由于可锁紧机构会锁死钩舌, 更安全

SLR011-G80 U.S. TYPE SHANK SELF-LOCKING HOOK 80级 美式直杆安全钩

SLR011



ITEM NO.	WEIGHT (Kg)	WLL (T)	BL (T)	A±0.5	B±1.5	C±2	H±1	L±3	Ø±2
8-SLR011-78	1.27	5	0	25.4	38	51.5	29	109	42
8-SLR011-10	2.15	8.2	12.5	29	42	76.5	34	143	56

Ultimate limit is 4 times the Working Load Limit 极限拉力是工作载荷的4倍


◆ Regular color (常规颜色): 316, 316L, 317, 317L, 318, 318L, 319, 319L, 321, 321L, 322, 322L, 323, 323L, 324, 324L, 325, 325L, 326, 326L, 327, 327L, 328, 328L, 329, 329L, 330, 330L, 331, 331L, 332, 332L, 333, 333L, 334, 334L, 335, 335L, 336, 336L, 337, 337L, 338, 338L, 339, 339L, 340, 340L, 341, 341L, 342, 342L, 343, 343L, 344, 344L, 345, 345L, 346, 346L, 347, 347L, 348, 348L, 349, 349L, 350, 350L, 351, 351L, 352, 352L, 353, 353L, 354, 354L, 355, 355L, 356, 356L, 357, 357L, 358, 358L, 359, 359L, 360, 360L, 361, 361L, 362, 362L, 363, 363L, 364, 364L, 365, 365L, 366, 366L, 367, 367L, 368, 368L, 369, 369L, 370, 370L, 371, 371L, 372, 372L, 373, 373L, 374, 374L, 375, 375L, 376, 376L, 377, 377L, 378, 378L, 379, 379L, 380, 380L, 381, 381L, 382, 382L, 383, 383L, 384, 384L, 385, 385L, 386, 386L, 387, 387L, 388, 388L, 389, 389L, 390, 390L, 391, 391L, 392, 392L, 393, 393L, 394, 394L, 395, 395L, 396, 396L, 397, 397L, 398, 398L, 399, 399L, 400, 400L, 401, 401L, 402, 402L, 403, 403L, 404, 404L, 405, 405L, 406, 406L, 407, 407L, 408, 408L, 409, 409L, 410, 410L, 411, 411L, 412, 412L, 413, 413L, 414, 414L, 415, 415L, 416, 416L, 417, 417L, 418, 418L, 419, 419L, 420, 420L, 421, 421L, 422, 422L, 423, 423L, 424, 424L, 425, 425L, 426, 426L, 427, 427L, 428, 428L, 429, 429L, 430, 430L, 431, 431L, 432, 432L, 433, 433L, 434, 434L, 435, 435L, 436, 436L, 437, 437L, 438, 438L, 439, 439L, 440, 440L, 441, 441L, 442, 442L, 443, 443L, 444, 444L, 445, 445L, 446, 446L, 447, 447L, 448, 448L, 449, 449L, 450, 450L, 451, 451L, 452, 452L, 453, 453L, 454, 454L, 455, 455L, 456, 456L, 457, 457L, 458, 458L, 459, 459L, 460, 460L, 461, 461L, 462, 462L, 463, 463L, 464, 464L, 465, 465L, 466, 466L, 467, 467L, 468, 468L, 469, 469L, 470, 470L, 471, 471L, 472, 472L, 473, 473L, 474, 474L, 475, 475L, 476, 476L, 477, 477L, 478, 478L, 479, 479L, 480, 480L, 481, 481L, 482, 482L, 483, 483L, 484, 484L, 485, 485L, 486, 486L, 487, 487L, 488, 488L, 489, 489L, 490, 490L, 491, 491L, 492, 492L, 493, 493L, 494, 494L, 495, 495L, 496, 496L, 497, 497L, 498, 498L, 499, 499L, 500, 500L, 501, 501L, 502, 502L, 503, 503L, 504, 504L, 505, 505L, 506, 506L, 507, 507L, 508, 508L, 509, 509L, 510, 510L, 511, 511L, 512, 512L, 513, 513L, 514, 514L, 515, 515L, 516, 516L, 517, 517L, 518, 518L, 519, 519L, 520, 520L, 521, 521L, 522, 522L, 523, 523L, 524, 524L, 525, 525L, 526, 526L, 527, 527L, 528, 528L, 529, 529L, 530, 530L, 531, 531L, 532, 532L, 533, 533L, 534, 534L, 535, 535L, 536, 536L, 537, 537L, 538, 538L, 539, 539L, 540, 540L, 541, 541L, 542, 542L, 543, 543L, 544, 544L, 545, 545L, 546, 546L, 547, 547L, 548, 548L, 549, 549L, 550, 550L, 551, 551L, 552, 552L, 553, 553L, 554, 554L, 555, 555L, 556, 556L, 557, 557L, 558, 558L, 559, 559L, 560, 560L, 561, 561L, 562, 562L, 563, 563L, 564, 564L, 565, 565L, 566, 566L, 567, 567L, 568, 568L, 569, 569L, 570, 570L, 571, 571L, 572, 572L, 573, 573L, 574, 574L, 575, 575L, 576, 576L, 577, 577L, 578, 578L, 579, 579L, 580, 580L, 581, 581L, 582, 582L, 583, 583L, 584, 584L, 585, 585L, 586, 586L, 587, 587L, 588, 588L, 589, 589L, 590, 590L, 591, 591L, 592, 592L, 593, 593L, 594, 594L, 595, 595L, 596, 596L, 597, 597L, 598, 598L, 599, 599L, 600, 600L, 601, 601L, 602, 602L, 603, 603L, 604, 604L, 605, 605L, 606, 606L, 607, 607L, 608, 608L, 609, 609L, 610, 610L, 611, 611L, 612, 612L, 613, 613L, 614, 614L, 615, 615L, 616, 616L, 617, 617L, 618, 618L, 619, 619L, 620, 620L, 621, 621L, 622, 622L, 623, 623L, 624, 624L, 625, 625L, 626, 626L, 627, 627L, 628, 628L, 629, 629L, 630, 630L, 631, 631L, 632, 632L, 633, 633L, 634, 634L, 635, 635L, 636, 636L, 637, 637L, 638, 638L, 639, 639L, 640, 640L, 641, 641L, 642, 642L, 643, 643L, 644, 644L, 645, 645L, 646, 646L, 647, 647L, 648, 648L, 649, 649L, 650, 650L, 651, 651L, 652, 652L, 653, 653L, 654, 654L, 655, 655L, 656, 656L, 657, 657L, 658, 658L, 659, 659L, 660, 660L, 661, 661L, 662, 662L, 663, 663L, 664, 664L, 665, 665L, 666, 666L, 667, 667L, 668, 668L, 669, 669L, 670, 670L, 671, 671L, 672, 672L, 673, 673L, 674, 674L, 675, 675L, 676, 676L, 677, 677L, 678, 678L, 679, 679L, 680, 680L, 681, 681L, 682, 682L, 683, 683L, 684, 684L, 685, 685L, 686, 686L, 687, 687L, 688, 688L, 689, 689L, 690, 690L, 691, 691L, 692, 692L, 693, 693L, 694, 694L, 695, 695L, 696, 696L, 697, 697L, 698, 698L, 699, 699L, 700, 700L, 701, 701L, 702, 702L, 703, 703L, 704, 704L, 705, 705L, 706, 706L, 707, 707L, 708, 708L, 709, 709L, 710, 710L, 711, 711L, 712, 712L, 713, 713L, 714, 714L, 715, 715L, 716, 716L, 717, 717L, 718, 718L, 719, 719L, 720, 720L, 721, 721L, 722, 722L, 723, 723L, 724, 724L, 725, 725L, 726, 726L, 727, 727L, 728, 728L, 729, 729L, 730, 730L, 731, 731L, 732, 732L, 733, 733L, 734, 734L, 735, 735L, 736, 736L, 737, 737L, 738, 738L, 739, 739L, 740, 740L, 741, 741L, 742, 742L, 743, 743L, 744, 744L, 745, 745L, 746, 746L, 747, 747L, 748, 748L, 749, 749L, 750, 750L, 751, 751L, 752, 752L, 753, 753L, 754, 754L, 755, 755L, 756, 756L, 757, 757L, 758, 758L, 759, 759L, 760, 760L, 761, 761L, 762, 762L, 763, 763L, 764, 764L, 765, 765L, 766, 766L, 767, 767L, 768, 768L, 769, 769L, 770, 770L, 771, 771L, 772, 772L, 773, 773L, 774, 774L, 775, 775L, 776, 776L, 777, 777L, 778, 778L, 779, 779L, 780, 780L, 781, 781L, 782, 782L, 783, 783L, 784, 784L, 785, 785L, 786, 786L, 787, 787L, 788, 788L, 789, 789L, 790, 790L, 791, 791L, 792, 792L, 793, 793L, 794, 794L, 795, 795L, 796, 796L, 797, 797L, 798, 798L, 799, 799L, 800, 800L, 801, 801L, 802, 802L, 803, 803L, 804, 804L, 805, 805L, 806, 806L, 807, 807L, 808, 808L, 809, 809L, 810, 810L, 811, 811L, 812, 812L, 813, 813L, 814, 814L, 815, 815L, 816, 816L, 817, 817L, 818, 818L, 819, 819L, 820, 820L, 821, 821L, 822, 822L, 823, 823L, 824, 824L, 825, 825L, 826, 826L, 827, 827L, 828, 828L, 829, 829L, 830, 830L, 831, 831L, 832, 832L, 833, 833L, 834, 834L, 835, 835L, 836, 836L, 837, 837L, 838, 838L, 839, 839L, 840, 840L, 841, 841L, 842, 842L, 843, 843L, 844, 844L, 845, 845L, 846, 846L, 847, 847L, 848, 848L, 849, 849L, 850, 850L, 851, 851L, 852, 852L, 853, 853L, 854, 854L, 855, 855L, 856, 856L, 857, 857L, 858, 858L, 859, 859L, 860, 860L, 861, 861L, 862, 862L, 863, 863L, 864, 864L, 865, 865L, 866, 866L, 867, 867L, 868, 868L, 869, 869L, 870, 870L, 871, 871L, 872, 872L, 873, 873L, 874, 874L, 875, 875L, 876, 876L, 877, 877L, 878, 878L, 879, 879L, 880, 880L, 881, 881L, 882, 882L, 883, 883L, 884, 884L, 885, 885L, 886, 886L, 887, 887L, 888, 888L, 889, 889L, 890, 890L, 891, 891L, 892, 892L, 893, 893L, 894, 894L, 895, 895L, 896, 896L, 897, 897L, 898, 898L, 899, 899L, 900, 900L, 901, 901L, 902, 902L, 903, 903L, 904, 904L, 905, 905L, 906, 906L, 907, 907L, 908, 908L, 909, 909L, 910, 910L, 911, 911L, 912, 912L, 913, 913L, 914, 914L, 915, 915L, 916, 916L, 917, 917L, 918, 918L, 919, 919L, 920, 920L, 921, 921L, 922, 922L, 923, 923L, 924, 924L, 925, 925L, 926, 926L, 927, 927L, 928, 928L, 929, 929L, 930, 930L, 931, 931L, 932, 932L, 933, 933L, 934, 934L, 935, 935L, 936, 936L, 937, 937L, 938, 938L, 939, 939L, 940, 940L, 941, 941L, 942, 942L, 943, 943L, 944, 944L, 945, 945L, 946, 946L, 947, 947L, 948, 948L, 949, 949L, 950, 950L, 951, 951L, 952, 952L, 953, 953L, 954, 954L, 955, 955L, 956, 956L, 957, 957L, 958, 958L, 959, 959L, 960, 960L, 961, 961L, 962, 962L, 963, 963L, 964, 964L, 965, 965L, 966, 966L, 967, 967L, 968, 968L, 969, 969L, 970, 970L, 971, 971L, 972, 972L, 973, 973L, 974, 974L, 975, 975L, 976, 976L, 977, 977L, 978, 978L, 979, 979L, 980, 980L, 981, 981L, 982, 982L, 983, 983L, 984, 984L, 985, 985L, 986, 986L, 987, 987L, 988, 988L, 989, 989L, 990, 990L, 991, 991L, 992, 992L, 993, 993L, 994, 994L, 995, 995L, 996, 996L, 997, 997L, 998, 998L, 999, 999L, 1000, 1000L, 1001, 1001L, 1002, 1002L, 1003, 1003L, 1004, 1004L, 1005, 1005L, 1006, 1006L, 1007, 1007L, 1008, 1008L, 1009, 1009L, 1010, 1010L, 1011, 1011L, 1012, 1012L, 1013, 1013L, 1014, 1014L, 1015, 1015L, 1016, 1016L, 1017, 1017L, 1018, 1018L, 1019, 1019L, 1020, 1020L, 1021, 1021L, 1022, 1022L, 1023, 1023L, 1024, 1024L, 1025, 1025L, 1026, 1026L, 1027, 1027L, 1028, 1028L, 1029, 1029L, 1030, 1030L, 1031, 1031L, 1032, 1032L, 1033, 1033L, 1034, 1034L, 1035, 1035L, 1036, 1036L, 1037, 1037L, 1038, 1038L, 1039, 1039L, 1040, 1040L, 1041, 1041L, 1042, 1042L, 1043, 1043L, 1044, 1044L, 1045, 1045L, 1046, 1046L, 1047, 1047L, 1048, 1048L, 1049, 1049L, 1050, 1050L, 1051, 1051L, 1052, 1052L, 1053, 1053L, 1054, 1054L, 1055, 1055L, 1056, 1056L, 1057, 1057L, 1058, 1058L, 1059, 1059L, 1060, 1060L, 1061, 1061L, 1062, 1062L, 1063, 1063L, 1064, 1064L, 1065, 1065L, 1066, 1066L, 1067, 1067L, 1068, 1068L, 1069, 1069L, 1070, 1070L, 1071, 1071L, 1072, 1072L, 1073, 1073L, 1074, 1074L, 1075, 1075L, 1076, 1076L, 1077, 1077L, 1078, 1078L, 1079, 1079L, 1080, 1080L, 1081, 1081L, 1082, 1082L, 1083, 1083L, 1084, 1084L, 1085, 1085L, 1086, 1086L, 1087, 1087L, 1088, 1088L, 1089, 1089L, 1090, 1090L, 1091, 1091L, 1092, 1092L, 1093, 1093L, 1094, 1094L, 1095, 1095L, 1096, 1096L, 1097, 1097L, 1098, 1098L, 1099, 1099L, 1100, 1100L, 1101, 1101L, 1102, 1102L, 1103, 1103L, 1104, 1104L, 1105, 1105L, 1106, 1106L, 1107, 1107L, 1108, 1108L, 1109, 1109L, 1110, 1110L, 1111, 1111L, 1112, 1112L, 1113, 1113L, 1114, 1114L, 1115, 1115L, 1116, 1116L, 1117, 1117L, 1118, 1118L, 1119, 1119L, 1120, 1120L, 1121, 1121L, 1122, 1122L, 1123, 1123L, 1124, 1124L, 1125, 1125L, 1126, 1126L, 1127, 1127L, 1128, 1128L, 1129, 1129L, 1130, 1130L, 1131, 1131L, 1132, 1132L, 1133, 1133L, 1134, 1134L, 1135, 1135L, 1136, 1136L, 1137, 1137L, 1138, 1138L, 1139, 1139L, 1140, 1140L, 1141, 1141L, 1142, 1142L, 1143, 1143L, 1144, 1144L, 1145, 1145L, 1146, 1146L, 1147, 1147L, 1148, 1148L, 1149, 1149L, 1150, 1150L, 1151, 1151L, 1152, 1152L, 1153, 1153L, 1154, 1154L, 1155, 1155L, 1156, 1156L, 1157, 1157L, 1158, 1158L, 1159, 1159L, 1160, 1160L, 1161, 1161L, 1162, 1162L, 1163, 1163L, 1164, 1164L, 1165, 1165L, 1166, 1166L, 1167, 1167L, 1168, 1168L, 1169, 1169L, 1170, 1170L, 1171, 1171L, 1172, 1172L, 1173, 1173L, 1174, 1174L, 1175, 1175L, 1176, 1176L, 1177, 1177L, 1178, 1178L, 1179, 1179L, 1180, 1180L, 1181, 1181L, 1182, 1182L, 1183, 1183L, 1184, 1184L, 1185, 1185L, 1186, 1186L, 1187, 1187L, 1188, 1188L, 1189, 1189L, 1190, 1190L, 1191, 1191L, 1192, 1192L, 1193, 1193L, 1194, 1194L, 1195, 1195L, 1196, 1196L, 1197, 1197L, 1198, 1198L, 1199, 1199L, 1200, 1200L, 1201, 1201L, 1202, 1202L, 1203, 1203L, 1204, 1204L, 1205, 1205L, 1206, 1206L, 1207, 1207L, 1208, 1208L, 1209, 1209L, 1210, 1210L, 1211, 1211L, 1212, 1212L, 1213, 1213L, 1214, 1214L, 1215, 1215L, 1216, 1216L, 1217, 1217L, 1218, 1218L, 1219, 1219L, 1220, 1220L, 1221, 1221L, 1222, 1222L, 1223, 1223L, 1224, 1224L, 1225, 1225L, 1226, 1226L, 1227, 1227L, 1228, 1228L, 1229, 1229L, 1230, 1230L, 1231, 1231L, 1232, 1232L, 1233, 1233L, 1234, 1234L, 1235, 1235L, 1236, 1236L, 1237, 1237L, 1238, 1238L, 1239, 1239L, 1240, 1240L, 1241, 1241L, 1242, 1242L, 1243, 1243L, 1244, 1244L, 1245, 1245L, 1246, 1246L, 1247, 1247L, 1248, 1248L, 1249, 1249L, 1250, 1250L, 1251, 1251L, 1252, 1252L, 1253, 1253L, 1254, 1254L, 1255, 1255L, 1256, 1256L, 1257, 1257L, 1258, 1258L, 1259, 1259L, 1260, 1260L, 1261, 1261L, 1262, 1262L, 1263, 1263L, 1264, 1264L, 1265, 1265L, 1266, 1266L, 1267, 1267L, 1268, 1268L, 1269, 1269L, 1270, 1270L, 1271, 1271L, 1272, 1272L, 1273, 1273L, 1274, 1274L, 1275, 1275L, 1276, 1276L, 1277, 1277L, 1278, 1278L, 1279, 1279L, 1280, 1280L, 1281, 1281L, 1282, 1282L, 1283, 1283L, 1284, 1284L, 1285, 1285L, 1286, 1286L, 1287, 1287L, 1288, 1288L, 1289, 1289L, 1290, 1290L, 1291, 1291L, 1292, 1292L, 12

G80 SWIVEL SELF-LOCKING HOOK WITH BEARING 80级 带轴承旋转安全钩

- ◆ Forged super alloy steel - Quenched and tempered
 - 锻造合金钢经淬火及回火处理
- ◆ Suitable for ENR16-2 G80 chain
 - 与ENR16-2级链条配合使用
- ◆ Individually proof test at 2.5 times Working Load Limit
 - 组件按工作压力的2.5倍进行验证测试
- ◆ Fatigue tested at 1.5 times Working Load Limit for 20000 cycles
 - 在1.5倍工作压力下循环进行20000次疲劳测试
- ◆ Breakout test
 - 对每一批次产品进行严格的拉伸断裂测试
- ◆ 100% magnetic crack detection
 - 100% 磁粉探伤检测
- ◆ Surface finish (表面处理): Powder painted (喷漆)
 - ◆ Colour code (颜色): Blue (蓝色)RAL5015
- ◆ Positive lock takes to Self-Locking when hook is loaded
 - 在负载下，钩子的自锁机构和锁扣组合，更安全
- ◆ Can be Rotated Under Non-tidal Conditions
 - 在非承浪条件下可旋转调节方向

SLR490-G80 SWIVEL SELF-LOCKING HOOK WITH BEARING
80级 带轴承旋转安全钩

SLR490



ITEM NO.	WEIGHT Økg	WLL (T)	B.L (T)	A±0.5	B±1.5	C±2	D±1	K±2	H±1	L±5	Φ±2
8-SLR490-8	0.78	1.02	4.45	37	29	32.5	11.5	101	20	100	38
8-SLR490-7/8	1.23	2	8	45	35	39	13	201.0	24	242	40
8-SLR490-10	2.14	3.15	12.5	54	40	42	15.5	235	26	294.5	52
8-SLR490-13	3.39	5.2	17.2	65.5	54	55	17	254	41	340	56
8-SLR490-16	7.52	11	32	107.0	80.5	81	21.0	347	50	422	68

Working Load is 4 times the Working Load Limit (依据在自重工作压力4倍以内)

Regular mark 常规标记:

MARK 标志	号	-S	WLL 5.15T	SLR	CE	16-1
CE MARKING 标志	CLASS 5.15T 等级	CLASS 5.15T 等级	WORKING LOAD LIMIT 工作压力	PRODUCT 产品	CE MARKING CE 标志	WLL 5.15T 工作压力



WARNING 警告 Please refer to the instruction manual for safety information.

G80 SELF-LOCK HOOK 80级自锁钩

- ◆ Forged super alloy steel- Quenched and Tempered
- ◆ 高强度高强度特种合金钢锻造而成，经过热处理
- ◆ Individually proof test at 2.5 times Working Load Limit
- ◆ 每件按工作拉力的2.5倍进行验证测试
- ◆ Fatigue tested at 1.5 times Working Load Limit for 20000 cycles
- ◆ 钩体进行20000次疲劳测试
- ◆ Breakage test: 对每一批次的产品进行严格的破坏测试
- ◆ 100% magniflux crack detection: 100% 进行磁粉探伤
- ◆ Can be Rotated under Tension-load Condition!
- ◆ 在承受拉力下可旋转钩体方向!



SLR-767 G80 EUROPEAN TYPE SWIVEL SELF-LOCKING HOOK
80 级欧式旋转安全钩

SLR767

ITEM NO.	WEIGHT (kg)	WLL (T)	B.L (T)	B±1.5	C±2	D±1	E±1.5	H±1	M±2	L±3.5
8-SLR767-04	μ5	1.12	44t	92.6	23	11.5	24	24	70	164
8-SLR767-08	1.1	2	8	36	29.5	13	28	33	10	229
8-SLR767-10	2	3.15	12.5	42	34	15.5	40	33	102	260
8-SLR767-13	4	6.3	21.2	50	41	17	53.5	40.5	136.5	327
8-SLR767-16	8.8	8	32	71	58	21.5	61	50.0	170.5	433
8-SLR767-20	12.5	12.5	55	72	64	24	75.5	62	182.5	490
8-SLR767-22	17.1	15	60	97	98	32	83	65	205	545

Load Limit is 4 times the Working Load Limit 额定拉力是工作拉力的4倍

- ◆ Regular mark (常规标识): ①-④ WLL ⑤-⑦ C±2 ⑧ D±1 ⑨ E±1.5 ⑩ H±1 ⑪ M±2 ⑫ L±3.5

- ◆ Forged super alloy steel- Quenched and Tempered
- ◆ 高强度高强度特种合金钢锻造而成，经过热处理
- ◆ Individually proof test at 2.5 times Working Load Limit
- ◆ 每件按工作拉力的2.5倍进行验证测试
- ◆ Fatigue tested at 1.5 times Working Load Limit for 20000 cycles
- ◆ 钩体进行20000次疲劳测试
- ◆ Breakage test: 对每一批次的产品进行严格的破坏测试
- ◆ 100% magniflux crack detection: 100% 进行磁粉探伤
- ◆ Can be Rotated under Tension-load Condition!
- ◆ 在承受拉力下可旋转钩体方向!



SLR772-SWIVEL SELF-LOCKING HOOK
80 级异型旋转安全钩

SLR772

ITEM NO.	WEIGHT (kg)	WLL (T)	B.L (T)	A±2	B±2.5	C±1	D±0.5	E±0.5	F±1	G	H±0.5	K±2.5
8-SLR772-08	1.05	2	8	214	28.5	36	13	45	37	32	25	139
8-SLR772-10	1.2	3.15	12.5	204	30	42	15.5	55.5	47.5	46	30.5	214
8-SLR772-13	3.34	5.2	21.2	204	48	30	19	64	62.5	69	38	276
8-SLR772-16	5.55	8	32	400	69	60	23	90	70	91	40	328

Load Limit is 4 times the Working Load Limit 额定拉力是工作拉力的4倍

- ◆ Regular mark (常规标识): ①-④ WLL ⑤-⑦ C±1 ⑧ D±0.5 ⑨ E±0.5 ⑩ F±1 ⑪ G ⑫ H±0.5 ⑬ K±2.5



G80 SELF-LOCK HOOK FOR WEB SLING WITH HALF LINK 80级 带半环吊带自锁钩

- ◆ Forged super alloy steel- Quenched and Tempered
- ◆ 高强度合金钢经淬火及回火处理, 经过防腐蚀
- ◆ Industrially proof load at 2.5 times Working Load Limit
- ◆ 工业级工作部为2.5倍额定载荷
- ◆ Fatigue tested at 1.5 times Working Load Limit for 20000 cycles
- ◆ 在1.5倍工作部力下疲进行20000次疲劳测试
- ◆ Breakage test
- ◆ 对每一批产品进行严格的破坏性测试
- ◆ 100% magnetic crack detection
- ◆ 100% 进行磁力探伤
- ◆ With latch
- ◆ 每个产品均配有防脱舌片
- ◆ Surface finish (表面处理): Powder coated (喷塑)
- ◆ Colour code (色号): Red (红色) RAL3020
- ◆ Yellow (黄色) RAL1015



- ◆ Positive indication in SELF-LOCKING when hook is locked.
- ◆ 锁紧后, 钩子的自锁钩会自动闭合, 更安全

SLR110-G80 SELF-LOCK HOOK FOR WEB SLING WITH HALF LINK 80级 带半环吊带自锁钩

SLR110



ITEM NO. 型号	WEIGHT (kg)	WLL (T)	S.L. (T)	A±1.5	H±1	W±1.5	T±1	Ø±1.5	L±3
8-SLR110-10	1.5	3.15	12.5	25.5	25.5	47	81	56	125
8-SLR110-13	3.27	3.3	17.3	20	40	51.5	70	70	250

(Breaks load is 4 times the Working Load Limit 破断力是工作部力的4倍)

- ◆ Puller code (吊钩码): 10-R3LL3-15T CE SLR + WATCH NUMBER (钩号)

Regular mark 常规标记:

MARK 标志	10	13	WLL 3.15T	SLR	CE	15-1
CE MARKING 标志	CE MARK 标志	CE MARK 标志	WORKING LOAD LIMIT 工作部力	MANUFACTURER 生产商	CE MARKING CE 标志	WATCH NUMBER 钩号



WARNING 警告 This is a lifting device and can be dangerous if not used properly.

G80 SELF-LOCK HOOK 80级自锁钩

- ◆ Forged super alloy steel- Quenched and Tempered
- ◇ 高强度合金钢材料经热处理而成，经过热处理
- ◆ Breakage test
- ◇ 对每一批次产品进行严格的破坏性测试
- ◆ 100% magnetism crack detection
- ◇ 100% 进行磁粉探伤
- ◆ Surface finish (表面处理):
- ◇ Powder painted (喷漆)
- ◆ Colour code(颜色): Red (红色) RAL3020
- Yellow (黄色) RAL1003



SLR089-G80 SHORT CLEVIS SELF-LOCK HOOK FOR WEB SLING 短体羊角吊带自锁钩


SLR089

ITEM NO. 型号	WEIGHT (kg) 重量	WLL (T) 工作拉力	B.L (T)	E±2	A±2	S±1.5	L±2	M±2	T±1.5
8-SLR089-2.2T	1.04	2.2	8.8	50	16	95	120	125	50

Ultimate loads 4 times the Working Load Limit 破断力为工作拉力的4倍

- ◆ Regular mark (钢印): WLL 2.2T CE: SLR = BATCH NUMBER (批号)

- ◆ Forged super alloy steel- Quenched and Tempered
- ◇ 高强度合金钢材料经热处理而成，经过热处理
- ◆ Breakage test
- ◇ 对每一批次产品进行严格的破坏性测试
- ◆ 100% magnetism crack detection
- ◇ 100% 进行磁粉探伤
- ◆ Surface finish (表面处理): Powder painted (喷漆)
- ◆ Colour code(颜色): Red (红色) RAL3020
- Yellow (黄色) RAL1003



SLR236-G80 LONG CLEVIS SELF-LOCK HOOK FOR WEB SLING 长体羊角吊带自锁钩

SLR236

ITEM NO. 型号	WEIGHT (kg) 重量	WLL (T) 工作拉力	B.L (T)	A±1.5	E±1.5	L±3
8-SLR236-2.2T	2.2	2.2	8.8	64	60	245

Ultimate loads 4 times the Working Load Limit 破断力为工作拉力的4倍

- ◆ Regular mark (钢印): WLL 2.2T CE: SLR = BATCH NUMBER (批号)




CLEVIS SLING HOOK 羊角滑钩

- ◆ Forged super alloy steel- Quenched and Tempered.
- ◆ 高强度特种合金钢锻造而成，经热处理。
- ◆ Suitable for EN15-2 Q345 steel.
- ◆ 与EN15-2 Q345钢完美配合使用。
- ◆ Individually proof test at 2.5 times Working Load Limit.
- ◆ 经单独工作拉力的2.5倍进行验证测试。
- ◆ Fatigue tested at 1.5 times Working Load Limit for 20000 cycles.
- ◆ 经单独进行20000次疲劳测试。
- ◆ Breakage test 对每一批次产品进行严格的破坏性测试。
- ◆ 100% mechanical creep detection.
- ◆ 100% 进行蠕变测试。
- ◆ All body pins are 100% individually inspected and tested.
- ◆ 所有销轴进行100%测试，确保质量和使用寿命。
- ◆ With rust touch, each product can be treated with rust touch.
- ◆ Surface finish (表面处理): Powder plating (喷漆)
- ◆ Color (颜色): Red (红色) RAL3020 / Yellow (黄色) RAL1020.



SLR012 - G80 CLEVIS SLING HOOK WITH CAST LATCH G80级羊角滑钩

SLR012



ITEM No.	WEIGHT (kg)	WLL (T)	RL (T)	A+0.5	B+1.5	D+1	H+2	L+1	E+2
SLR12-6	0.32	1.12	4.42	2	32	33	23	75	25
SLR12-7/8	0.43	2	6	0.5	50	37	25	86.4	25
SLR12-10	0.56	3.15	12.9	12.5	40	48	31	104	39
SLR12-13	1.3	6.3	21.2	11.5	60.5	57	42.5	128	47.5
SLR12-16	3.4	8	32	21.5	70.8	65	54	150	65
SLR12-20	6	12.5	50	34	72	70	69	150	59
SLR12-22	11.6	15	60	36	91	101	82	181	79
SLR12-26	14.5	21.2	84.5	50	117	115	75	200	111
SLR12-32	37	31.5	120	35	136	140	102	217	124

Ultimate hook is 4 times the Working Load Limit 钩的拉力是工作拉力的4倍

- ◆ Replace code (代码): 12-5 WLL 5.15T CE SLR - BATCH NUMBER (批号)

SP-SLR012 - LOAD PIN 销轴配件 (销轴+弹性圆柱销)



ITEM CODE	SIZE	ITEM CODE	SIZE
SLR12-6	6-8	SLR12-20	20-8
SLR12-7/8	7/8-5	SLR12-22	22-8
SLR12-10	10-7	SLR12-26	26-8
SLR12-13	13-8	SLR12-32	32-8
SLR12-16	16-8		

SP-SLR012 - CAST LATCH KIT 铸造舌片配件 (铸造舌片+弹簧+弹丝+螺母)



ITEM CODE	SIZE	ITEM CODE	SIZE
SLR12-6	6-8	SLR12-20	20-8
SLR12-7/8	7/8-5	SLR12-22	22-8
SLR12-10	10-7	SLR12-26	26-8
SLR12-13	13-8	SLR12-32	32-8
SLR12-16	16-8		



WARNING 警告 This is a lifting device and should be used in accordance with the instructions.

CLEVIS SLING HOOK 羊角滑钩

- Forged super alloy steel - Quenched and Tempered.
- 高强度合金钢锻造，合金钢经淬火、回火处理。
- Suitable for EN818-2 350 class.
- 符合EN818-2 350级高强度合金钢使用。
- Individually proof test at 2.5 times Working Load Limit.
- 每件在工作拉力2.5倍进行验证测试。
- Fatigue tested at 1.5 times Working Load Limit for 20070 cycles
- 钩体进行20070次疲劳测试。
- Breakage test 对每一款产品进行严格的破坏性测试。
- 100% magniflux crack detection.
- 100% 进行磁粉探伤。
- With latch, 每件产品均配有锁扣设计。
- Surface finish (表面处理) : Powder painted (喷漆)
- Colour code (色号) : Red (红色) : RAL3020 / Yellow (黄色) : RAL3009.



SLR333 - G80 CLEVIS SLING HOOK WITH CAST LATCH 80级款式羊角滑钩

SLR333



ITEM NO.	WEIGHT (kg)	WLL (T)	B.L. (T)	A ±0.5	B ±1.2	E ±1	H ±2	M ±1	L ±2
SLR333-6	0.3	1.12	4.18	8	32	18.5	20	68	158
SLR333-7/8	0.55	2	8	12.5	35.5	24	25	87.4	120.9
SLR333-10	0.90	3.15	12.5	12.5	40	25	30	106.2	153.5
SLR333-12	1.52	5.1	25.2	18	50	30	41.8	130	194.8
SLR333-16	3.43	8	47	25.0	65.0	40	48.3	155.3	226
SLR333-20	6.29	12.5	95	34.5	80	61.6	51	180	251

Ultimate load by 4 times the Working Load Limit 极限拉力为工作拉力的4倍

SP-SLR333 - LOAD PIN 销轴配件 (钢轴+弹性尼龙柱销)



ITEM CODE 货号	SIZE 规格	ITEM CODE 货号	SIZE 规格
SP-SLR333-6	6-8	SP-SLR333-20	20-8
SP-SLR333-7/8	10-8		
SP-SLR333-10	10-8		
SP-SLR333-12	12-8		
SP-SLR333-16	16-8		

Regular mark 常规标记:

MARK 标记	10	-8	WLL 3.15T	SLR	CE	18-1
ORIGIN PIN 产地	SP-3000	SP-3000	WALL 3.15T 1.8T 2.0T	WALL 3.15T 1.8T 2.0T	CE OFF 18-1 18-1 18-1	FOR 18-1 18-1 18-1



CLEVIS SLING HOOK

羊角滑钩


- ◆ Forged super alloy steel- Quenched and Tempered.
- ◆ 高强度合金材料经淬火及回火处理，强度高且稳定。
- ◆ Suitable for EN15-2 Q355 steel.
- ◆ 与EN15-2 Q355钢完美配合使用。
- ◆ Individually proof test at 2.5 times Working Load Limit.
- ◆ 经单独工作拉力2.5倍进行验证测试。
- ◆ Fatigue tested at 1.5 times Working Load Limit for 20000 cycles.
- ◆ 抽样进行20000次疲劳测试。
- ◆ Breakage test 对每一款产品进行严格的抽样破坏测试。
- ◆ 100% mechanical crack detection.
- ◆ 100% 进行探伤检测。
- ◆ All body pins are 100% individually inspected and tested.
- ◆ 所有销轴进行100%测试，确保使用便捷可靠。
- ◆ With cast tooth, each product has cast safety teeth.
- ◆ Surface finish(表面处理): Powder painted(喷漆)
- ◆ Color code(颜色): iRed(红色) RAL3020 / Yellow(黄色) RAL1003.



SLR247-ITALIAN TYPE CLEVIS SLIP HOOK

意式羊角滑钩

SLR247



ITEM NO.	WEIGHT (KG)	WLL (T)	B.L (T)	A#2	B#2	E#2	M#3	L#3
8-SLR-247-7B	1.58	2	8	5.5	58.5	25.9	80.4	120
8-SLR-247-10	1.53	2.55	12.5	12.5	40.5	32	110	108
8-SLR-247-12	2.1	3.4	24.2	19.5	34	41	123	202
8-SLR-247-16	2.52	2	32	19.6	66.5	44	108	140

1. Always load it at lower the Working Load Limit 始终别超过工作拉力范围
 always Working Load Limit is based on safe pull 表格所列工作拉力是在安全情况下工作拉力。

Regular mark 常规标记:

MARK 标志	号	-8	WLL 3.15T	SLR	CE	18-1
CE MARKING 标志	号 规格号	CLASS: 45 200202L	WORKING LOAD LIMIT 工作拉力	PRODUCT 产品	CE MARKING CE 标志	WLL 3.15T 工作拉力



WARNING 警告 Please read the instruction manual before use.

CLEVIS SLING HOOK

羊角滑钩


- ◆ Forged super alloy steel-Quenched and Tempered
- ◇ 高强度合金钢锻造-淬火回火处理
- ◆ Suitable for EN818-2 Q235 chain
- ◇ 与EN818-2标准A2钢链配合使用
- ◆ Individually proof test at 2.5 times Working Load Limit
- ◇ 每件在工作拉力的2.5倍进行验证测试
- ◆ Fatigue tested at 1.5 times working load limit for 20000 cycles
- ◇ 在1.5倍工作拉力下连续进行20000次疲劳测试
- ◆ Breakage test
- ◇ 对同一批次产品进行严格的破坏性测试
- ◆ 100% magnetic crack detection
- ◇ 100%进行磁粉探伤
- ◆ All load pins are 100% individually inspected and tested
- ◇ 所有销轴进行100%测试, 确保无缺陷后使用
- ◆ Surface finish (表面处理): ◇ Powder painted (喷漆)
- ◆ Colour code (颜色):
- ◇ Red (红色) RAL3020
- ◇ Yellow (黄色) RAL1023



SLR104-CLEVIS SLING HOOK

羊角滑钩

SLR104



ITEM NO.	WEIGHT (KG)	WLL (T)	ØL (T)	A*2	B*2	M*2	H*3	K*3	L*3
S-SLR-104-6	0.4	1.5	9	7	31	18	20.5	27	110
S-SLR-104-7.5	0.54	2	11	9.2	35	20	22	34	124
S-SLR-104-10	1	3.55	12.5	12.5	41	23.5	25.5	111	163
S-SLR-104-13	1.59	5.3	21.2	16.5	57	32	38	158	216
S-SLR-104-16	3.85	8	32	18.5	74	34.5	45.5	103	246
S-SLR-104-20	7.55	12.5	51.2	24	81.5	42	71	168	509

Ultimate Load is 4 times the Working Load (ULB 4倍于工作拉力的4倍)

Allow Working Load Limit is based on safe pull value of the working force in the state of the working place.

Regular mark 常规标记:

MARK 标记	10	-8	WLL 3.5T	SLR	CE	18-1
DESCRIPTION 描述	SIZE 规格	GRADE 等级	WORKING LOAD LIMIT 工作拉力	MARKING 标记	CE OFF HICATE CE 认证	PAINT NUMBER 漆号

WARNING 警告

WARNING 警告



HORNS LOADING HOOK 羊角加载钩

- ◆ Forged super alloy steel-Quenched and Tempered
 - 高强度合金特殊合金锻造而成，经过热处理
- ◆ Suitable for EN18-2 Q80 chain
 - 与EN18-248系列的链条配套使用
- ◆ Individually proof test of 2.5 times Working Load Limit
 - 零件在工作拉力的2.5倍进行验证测试
- ◆ Fatigue tested at 1.5 time working load limit for 20000 cycles
 - 在1.5倍工作拉力下进行20000次疲劳测试
- ◆ Breakage test
 - 对每一件产品进行严格的破坏性测试
- ◆ 100% magnetic particle detection
 - 100%磁粉探伤检测
- ◆ All steel parts are 100% individually inspected and tested
 - 所有钢铁进行100%测试，确保用料的健全品质
- ◆ Surface finish (表面处理) : > Powder plastcoat (喷漆)
 - ◆ Color code (色号) :
 - Red (红色) /RAL3000
 - Yellow (黄色) /RAL1003



SLR312-HORNS LOADING HOOK
羊角加载钩

SLR312



ITEM NO.	WEIGHT (KG)	WLL (T)	SL (T)	A±2	B±2	E±2	M±3	I±3
8-SLR-312-06	0.43	1.12	4.41	8	31	28	30	132
8-SLR-312-08	0.60	2	9	25	37	26	34	157
8-SLR-312-10	1.1	3.15	13.2	12.5	47.5	34	50	175.5
8-SLR-312-12	2.4	6.4	25.2	16	85.6	40	134.5	210
8-SLR-312-16	4.40	8	32	16.5	75	47.5	162.5	254

Ultimate Load is 4 times the Working Load Limit 极限拉力是工作拉力的4倍

- ◆ Regular mark 常规标记: 10-S-WLLS-15T-CE-SLR-RATCH-NUMBER (批号)

Regular mark 常规标记:

MARK 标志	10	-S	WLLS-15T	SLR	CE	18-1
CE MARK 11M 标志	CE MARK 11M 标志	CE MARK 11M 标志	WLLS-15T-CE-SLR-RATCH-NUMBER 批号	SLR 312	CE MARK 11M 标志	WLLS-15T-CE-SLR-RATCH-NUMBER 批号



WARNING 警告

Do not use this hook for lifting or lowering loads. It is not designed for this purpose.

G80 CLEVIS HOOKS 80级 羊角钩

- ◆ Forged super alloy steel - Quenched and Tempered
- ◇ 高强度合金钢锻造，淬火回火处理
- ◆ Individually proof test at 2.5 times Working Load Limit
- ◇ 每件钩工作前为2.5倍额定载荷测试
- ◆ Fatigue tested at 1.5 times Working Load Limit for 20000 cycles
- ◇ 每件进行20000次疲劳测试
- ◆ Breakage test
- ◇ 对每一批次产品进行严格的破坏性测试
- ◆ 100% magniflux crack detection
- ◇ 100% 进行磁粉探伤



SLR848-G80 CLEVIS SLING HOOK WITH LATCH
YOKE羊角钩

SLR848

ITEM NO.	WEIGHT (kg)	WLL (T)	B.L (T)	A*1	B*1	C*1	E*1.5	M*2	N*1	H*1	L*3
B-SLR848-6	0.3	1.32	4.43	6	25.5	18	29	60	15.5	10.2	112.2
B-SLR848-7/8	0.524	2	5	9	33	20	30	64	20	12.8	140
B-SLR848-10	1.19	3.75	12.0	12	44	25.5	36	105	24	16	147.9
B-SLR848-13	2.32	5.8	21.2	15	57	34	48	132.3	30	20	210.0
B-SLR848-16	3.62	9	32	18.5	67	41.5	62	161	41.5	31	260
B-SLR848-18/20	5.72	12.5	50	23	83	51	73	187	45	36	292

Ultimate load is 4 times the Working Load Limit 破断力是工作载荷的4倍

- ◆ Regular mark (常规标记): 10-5 V0113 1TT CE SLR + DATA PLATE (型号)

Regular mark 常规标记:

MARK 标记	10	-6	WLL 3.5T	SLR	CE	10-1
DESCRIPTION 描述	2013-08070	2013-08070	WORKING LOAD LIMIT 工作载荷	MANUFACTURER'S MARK	CE CERTIFIED CE 认证	NATCH NUMBER 序列号



G80 CLEVIS SLIP HOOK 羊角滑钩

- ◆ Forged super alloy steel-Quenched and Tempered
 - 高强度合金钢淬火及回火处理，经过防腐蚀
- ◆ Suitable for EN18-2 G80 chain
 - 与EN18-246号的链条配套使用
- ◆ Individually proof test of 2.5 times Working Load Limit
 - 零件在工作拉力的2.5倍进行验证测试
- ◆ Fatigue tested at 1.5 time working load limit for 20000 cycles
 - 在1.5倍工作拉力下循环进行20000次疲劳测试
- ◆ Breakage test
 - 对每一件产品进行严格的破坏性测试
- ◆ 100% magnetic particle detection
 - 100%磁粉探伤检测
- ◆ All steel parts are 100% individually inspected and tested
 - 所有钢铁进行100%测试，确保使用的便是原所
- ◆ Surface finish (表面处理) : > Powder plastcoat (喷漆)
 - ◆ Color code (色号) :
 - Red / 红色 / RAL3009
 - Yellow (黄色) / RAL1003



SLR329-G80 CLEVIS SLIP HOOK

羊角滑钩

SLR329



ITEM NO.	WEIGHT (KG)	W.L (T)	B.L (T)	A*2	B*2	E*2	M*3	N*3	H*3	L*3	K*3
8-SLR-329-00	0.3	1.12	4.48	7.5	32	32	74	12	20.0	121	38
8-SLR-329-7H	0.5	9	9	0.5	56	25	83	18	23.5	147	44
8-SLR-329-10	0.55	9.19	10.8	12	48	34	107	20	30	175.5	120
8-SLR-329-13	1.80	5.3	21.2	15	50	41.5	154	20.5	37.8	210.5	148
8-SLR-329-16	3.45	8	33	17.5	70	46	186	34	42.0	248	170
8-SLR-329-20	6.75	11.5	61	28	80	62	198	48	54	322	210.5
8-SLR-329-22	6.65	15	84	35.5	85	69	209	44	58	375.5	250

Lifting load is 4 times the Working Load Limit 吊钩拉力是工作拉力的4倍

- ◆ Regular mark (常规标记) : 1H-B L L S 15T L E SLR + BATCH NUMBER (批号)

Regular mark 常规标记:

MARK 标记	1H	-B	L L S 15T	SLR	CE	1H-1
吊钩的吊钩号	吊钩的吊钩号	吊钩的吊钩号	吊钩的吊钩号	吊钩的吊钩号	吊钩的吊钩号	吊钩的吊钩号



WARNING 警告

此吊钩只适用于吊钩，不得用于其他用途。

CLEVIS SLING HOOK

羊角滑钩

- ◆ Forged super alloy steel-Quenched and Tempered
- ◇ 锻造高强度合金钢经淬火、回火处理
- ◆ Suitable for EN818-2 Q235 chain
- ◇ 与EN818-2标准A级链条配合使用
- ◆ Individually proof test at 2.5 times Working Load Limit
- ◇ 每件在工作拉力的2.5倍进行验证测试
- ◆ Fatigue tested at 1.5 times working load limit for 20000 cycles
- ◇ 在1.5倍工作拉力下做持续运行20000次疲劳测试
- ◆ Breakage test
- ◇ 对每一批产品进行严格的破坏性测试
- ◆ 100% magnetic crack detection
- ◇ 100%进行磁粉探伤
- ◆ All load pins are 100% individually inspected and tested
- ◇ 所有销轴进行100%测试，确保无裂纹和拉伤
- ◆ Surface finish (表面处理) : Powder painted (喷漆)
- ◆ Colour code (色号) : Red (红色) RAL3020
Yellow (黄色) RAL1006



SLR069-CLEVIS SLING HOOK

羊角滑钩

SLR069



ITEM NO.	WEIGHT (LBS)	WLL (lbs)	S.L (lbs)	A±2	B±2	E±2	C±3	L±3
8-SLR-09-114	1.1	2000	14000	11.5	88	26	42	137.5
8-SLR-09-218	2.05	2100	21400	14.5	117	38	53	176
8-SLR-09-112	4.05	2200	21500	17.8	120	47	61	217.5
8-SLR-09-518	6.15	15100	22400	25.8	161.5	62	76	263
8-SLR-09-214	12.12	21200	113200	24.5	167	55	62.5	204

Ultimate lbs is 4 times the Working Load Limit 破断拉力是工作拉力的4倍

Allow Working Load Limit is based on safe pull 额定工作拉力是在额定状态下工作拉力

Regular mark 常规标记:

MARK 标记	8-8	-8	WLL 3.2T	SLR	CE	18-1
DESCRIPTION 说明	SLR 说明	SLR 80 说明	WORKING LOAD LIMIT 工作力	MAXIMUM 最大值	CE OFF HICATE CE 认证	FOR CE HICATE 说明



G80 CLEVIS GRAB HOOK 80级 羊角滑钩


- ◆ Forged super alloy steel- Quenched and Tempered
- 高强度合金钢锻造而成，经过热处理
- ◆ Suitable for EN1678-2 G80 chain
- 与EN1678-2标准规格链条配合使用
- ◆ 100% magnetic crack detection
- 100% 进行磁粉探伤
- ◆ All used parts are 100% individually inspected and tested
- 所有部件进行100%测试，确保所有的使用品质
- ◆ Surface finish (表面处理): Powder painted (喷漆)
- ◆ Colour code (色号): Red (红色) RAL3020
- Yellow (黄色) RAL1005



SLR014-CLEVIS SLING HOOK

羊角滑钩

SLR014



ITEM NO.	WEIGHT (KG)	WLL (T)	B.L (T)	A±2	B±2	E±2	H±3	K±3	L±3
8-SLR-14-67	0.55	1.6	11.4	3	36	24	28	50	144
8-SLR-14-7	0.72	1.6	11.4	8	37.5	31	32	55	150
8-SLR-14-8	0.91	2	8	10	42	38	33.5	117	153
8-SLR-14-10	1.32	3.15	12.5	12	50	42	41	125	161.5
8-SLR-14-13	3.3	5.3	21.1	15	60	48	46	137	254.5
8-SLR-14-16	4.9	8	32	19.5	67	66	49.5	212	292

Ultimate load is 4 times the Working Load Limit 破断力是工作拉力4倍

Allow working Load Limit is broken in this point 请参照到工作拉力破断点以下工作拉力

- ◆ Ring size mark (环圈号): 10-1 V.L.L. 1ST CE-SLR = BATCH NUMBER (批号)



WARNING 警告

Do not use this product if you find any damage or defect.

CLEVIS SLING HOOK

羊角滑钩

- ◆ Forged super alloy steel—Quenched and Tempered
 - ◇ 高强度耐热性特殊合金钢锻造而成，经过热处理
- ◆ Individually proof test at 2.5 times Working Load Limit
 - ◇ 每件按工作负荷力的2.5倍进行验证测试
- ◆ Fatigue tested at 1.5 times Working Load Limit for 20000 cycles
 - ◇ 抽样进行20000次疲劳测试
- ◆ Breakage test
 - ◇ 对每一批次产品进行严格的破坏性测试
- ◆ 100% magnifying crack detection
 - ◇ 100% 进行裂纹检测



SLR580—CLEVIS SLING HOOK

羊角滑钩

SLR580

ITEM NO.	WEIGHT (KG)	WLL (LBS)	B.L (LBS)	A±2	B±2	E±2	M±3	L±3
S-SLR-580-10	1.2	7350	7500	43	12.5	33.7	113	170

Ultimate load is 4 times the Working Load Limit 破断力为工作负荷力的4倍

- ◆ Regular code (常规型号): 30-5 (1/2" LBS) 10-11

- ◆ Forged super alloy steel—Quenched and Tempered
 - ◇ 高强度耐热性特殊合金钢锻造而成，经过热处理
- ◆ Individually proof test at 2.5 times Working Load Limit
 - ◇ 每件按工作负荷力的2.5倍进行验证测试
- ◆ Fatigue tested at 1.5 times Working Load Limit for 20000 cycles
 - ◇ 抽样进行20000次疲劳测试
- ◆ Breakage test
 - ◇ 对每一批次产品进行严格的破坏性测试
- ◆ 100% magnifying crack detection
 - ◇ 100% 进行裂纹检测



SLR554—G80 UK TYPE CLEVIS HOOK

UK 羊角钩

SLR554

ITEM NO.	WEIGHT (KG)	WLL (T)	B.L (T)	A±0.5	B±1	R	E±1	F	g	H±0.5	M±1	L±2
S-SLR554-8	0.45	2	8	1.5	30.5	85	15	28	20.5	32	±5	140


Ultimate load is 4 times the Working Load Limit 破断力为工作负荷力的4倍

- ◆ Regular code (常规型号): 10-11 WLL 12 (13) LBS + BATCH/NUMB (批号)



G80 CLEVIS GRAB HOOK 80级 羊角钩

- ◆ Forged super alloy steel- Quenched and Tempered
◇ 高强度高韧性特殊合金钢锻造而成，经过热处理
- ◆ Individually proof-tested at 2.5 times Working Load Limit
◇ 每件按工作力为2.5倍进行验证测试
- ◆ Fatigue tested at 1.5 times Working Load Limit for 20000 cycles
◇ 按样进行20000次疲劳测试
- ◆ Breakage test
◇ 对每一件产品进行严格的破坏性测试
- ◆ 100% magnetic flux crack detection
◇ 100% 进行磁粉探伤



SLR883-DIN1916 CLEVIS SLING HOOK 迷你钩羊角形钩

SLR883

ITEM NO.	WEIGHT(KG)	WLL(T)	B.L(T)	A+1.00	B±2	C±1	E±2	L±3	K±3	M±2	N±0.5	H±0.5
20MT	1.57	5	20	20	42	34.2	34	160	110	115	18	40.5

CLEVIS SHORTENING HOOK 羊角短钩

- ◆ Forged super alloy steel- Quenched and Tempered
◇ 高强度高韧性特殊合金钢锻造而成，经过热处理
- ◆ Individually proof-tested at 2.5 times Working Load Limit
◇ 每件按工作力为2.5倍进行验证测试
- ◆ Fatigue tested at 1.5 times Working Load Limit for 20000 cycles
◇ 按样进行20000次疲劳测试
- ◆ Breakage test
◇ 对每一件产品进行严格的破坏性测试
- ◆ 100% magnetic flux crack detection
◇ 100% 进行磁粉探伤



SLR338-CLEVIS SHORTENING HOOK 羊角短钩

SLR338

ITEM NO.	WEIGHT (KG)	WLL (T)	B.L (T)	A	B	E	M	L	L'
5-SLR338-06	0.18	1.12	4.45	7.5±1	32.0±2	3±1	45.0±2	78±3	48±2
5-SLR338-7/8	0.30	2	5	8.5±1	38±2	11±1	50±2	108±3	66.5±2
5-SLR338-10	0.35	3.15	12.5	15±1	48±2	15±1	75±3	127±3	74.5±3
5-SLR338-13	2	6.3	21.2	15±1	55±2	15.0±1	100±2	173±4	92.9±3
5-SLR338-16	3.6	8	22	18±2	70±3	20±2	123.5±4	203.0±5	125.0±4
5-SLR338-18/20	5.0	12.5	30	23±2	80±4	25±2	157±4	255±5	151±4
5-SLR338-22	7.8	19	30	25.5±2	95±4	28±2	171±5	279±6	175.5±5

Life span is 4 times the Working Load Limit 使用寿命是工作力为4倍
 Allow Working Load Limit is based on ideal use 使用所到工作力是理想使用下的工作力

★ Regular mark (标准标记) : 10-A WLL 15T CLEVIS HOOK NUMBER (吨数)




WARNING 警告

Do not use for lifting or pulling loads
 Do not use for lifting or pulling loads

G80 EYE SHORTENING GRAB HOOK 80级 眼型抓钩

- ◆ Forged super alloy steel - Quenched and Tempered
- ◇ 锻造超合金钢经淬火和回火处理
- ◆ Suitable for EN818-2 G80 chain
- ◇ 与EN818-2标准40级链条配合使用
- ◆ Initially proof test at 2.5 times Working Load Limit
- ◇ 零件在工作拉力2.5倍下进行验证测试
- ◆ Fatigue tested at 1.5 time working load limit for 20000 cycles
- ◇ 在1.5倍工作拉力下进行20000次疲劳测试
- ◆ Breakage test
- ◇ 对同一批次产品进行严格的破坏性测试
- ◆ 100% magnetic crack detection
- ◇ 100%进行磁粉探伤
- ◆ Surface finish (表面处理): ◇ Powder painted (喷漆)
- ◆ Colour code (色号):
- ◇ Red (红色) RAL3020
- ◇ Yellow (黄色) RAL1020



SLR331-EYE SHORTENING GRAB HOOK

眼型抓钩

SLR331

ITEM NO.	WEIGHT (KG)	WLL (T)	RL (T)	Ø#2	E#2	D#2	B#3	L#3
B-SLR-331-05	0.25	1.12	4.42	15	8	8	40	105
B-SLR-331-7.5	0.4	2	7.5	17	11	9.5	52	127
B-SLR-331-10	0.6	3.15	12.2	20	13	12	78	126
B-SLR-331-13	1.2	6.3	24.2	25	16	15	100	167
B-SLR-331-16	2.7	8	32	30.5	20	15	122	193
B-SLR-331-18(20)	4.8	12.5	50	35	25	23	150.5	208
B-SLR-331-22	6.4	15	60	42	26	27	166	209

Use see body 4 times the Working Load Limit 眼型抓钩工作拉力4倍

After the Working Load Limit is based on hook pull 有效载荷的工作拉力是在钩拉后工作拉力

- ◆ Regular mark (常规标记): 10-1 WLL 3.15T CE SUR BATH 18.0/95% (红色)


Regular mark 常规标记:

MARK 标记	10	-8	WLL 3.15T	SUR	CE	18-1
DESCRIPTION 描述	Size 规格	Grade 80 80级钢	Working Load Limit 工作拉力	Material 18-1 B-9002	CE OFF 18-1 CE 认证	Factor 18-1 安全系数



G80 CONTAINER HOOK 80级集装箱吊钩

- ◆ Forged super alloy steel- Quenched and Tempered
- ◆ 高强度合金钢经淬火及回火处理
- ◆ Inductively proof test at 2.5 times Working Load Limit
- ◆ 采用非工作应力2.5倍进行磁致伸缩测试
- ◆ Fatigue tested at 1.5 times Working Load Limit for 20000 cycles
- ◆ 吊钩进行20000次疲劳测试
- ◆ Breakage test
- ◆ 对每一批次产品进行严格的抽样破坏测试
- ◆ 100% magnaflex crack detection
- ◆ 100% 进行磁粉探伤



SLR472-G80 CONTAINER HOOK 80级集装箱吊钩


SLR472

ITEM NO.	WEIGHT (kg)	WLL (T)	S.L (T)	A	B	C	D	E	F
8-8	1.5	5	20	91	64.5	61.4	32	127	148

Ultimate limit is 4 times the Working Load Limit 破断力是工作应力的4倍

- ◆ Regular mark (常规标记) : WLL(T) SLR + 5047 (吨位/吊钩号)

- ◆ Forged super alloy steel- Quenched and Tempered
- ◆ 高强度合金钢经淬火及回火处理
- ◆ Inductively proof test at 2.5 times Working Load Limit
- ◆ 采用非工作应力2.5倍进行磁致伸缩测试
- ◆ Fatigue tested at 1.5 times Working Load Limit for 20000 cycles
- ◆ 吊钩进行20000次疲劳测试
- ◆ Breakage test
- ◆ 对每一批次产品进行严格的抽样破坏测试
- ◆ 100% magnaflex crack detection
- ◆ 100% 进行磁粉探伤



SLR277-G80 CONTAINER HOOK 80级集装箱吊钩

SLR277

(Not for recommendation) 不做推荐

ITEM NO.	WEIGHT (kg)	WLL (T)	S.L (T)	A	B	C	D
SLR-277-12mm	1.41	5	20	17.0	47	23	105

Ultimate limit is 4 times the Working Load Limit 破断力是工作应力的4倍

- ◆ Regular mark (常规标记) : WLL(T) SLR + 5047 (吨位/吊钩号)



WARNING 警告 This is a lifting equipment and must be used properly, not abuse.

G80 CLEVIS GRAB HOOK 80级 羊角滑钩

- ◆ Forged super alloy steel - Quenched and Tempered
- 高强度高韧性特种合金钢锻造而成，经过热处理
- ◆ Suitable for EN1219-2 G80 class
- 与EN1219-2标准30级吊索配合使用
- ◆ 100% magnetic crack detection
- 100% 磁粉探伤检测
- ◆ All load pins are 100% individually inspected and tested
- 所有销轴进行100%测试，确保无缺陷隐患
- ◆ Surface finish (表面处理): Powder painted (喷漆)
- ◆ Colour code (色号): Red (红色) RAL3020
- Yellow (黄色) RAL1003



SLR237-G80 CLEVIS FOUNDRY HOOK 80级羊角大开口钩

SLR237

ITEM NO.	WEIGHT (kg)	WLL (T)	B.L (T)	A±0.5	B±1.2	M±2	E±1	G±1	N±0.5	H±2	L±2
SLR237-7/8	1.1	2	3	9.6	37	125	33.4	13	19	31.6	165
SLR237-10	2.5	3.15	52.6	18	46	156	76.5	24	32	48	109

Ultimate Load is 4 times the Working Load (极限拉力是工作拉力4倍)

- ◆ Regular mark (常规标识): 10-K WLL (T) CE SLR + BATCH NUMBER (批号)

- ◆ Forged super alloy steel - Quenched and Tempered
- 高强度高韧性特种合金钢锻造而成，经过热处理
- ◆ Individually proof test at 2.5 times Working Load Limit
- 每件按工作力为2.5倍进行检验测试
- ◆ Fatigue tested at 1.5 times Working Load Limit for 25000 cycles
- 吊钩进行25000次疲劳测试
- ◆ Breakage test
- 对每一件次产品进行严格的破坏性测试
- ◆ 100% magnetic crack detection
- 100% 磁粉探伤检测



SLR024-G80 CLEVIS C HOOK 80级钩型C型羊角钩

SLR024

ITEM NO.	WEIGHT (kg)	WLL (T)	B.L (T)	A±0.5	B±1.5	E±1	H±1	K±2	L±2.5
SLR024-7/8	0.57	2	3	9.6	37	20	29	51	139
SLR024-10	1.4	3.15	15.6	15	46	25.5	36.5	127	159
SLR024-13	3	5.3	21.2	15.5	59	33.5	42	149.5	249
SLR024-16	5.42	8	32	15.5	72	42.5	55	200	329

Ultimate Load is 4 times the Working Load (极限拉力是工作力4倍)

- ◆ Regular mark (常规标识): 10-K WLL (T) CE SLR + BATCH NUMBER (批号)

G80 CLEVIS C HOOK 80级 C型羊角钩

- ◆ Forged super alloy steel- Quenched and Tempered
- ◆ 高级合金钢经特殊合金热处理而成，经过热处理
- ◆ Suitable for EN1678-2 G80 chain
- ◆ 与EN1678-2级索具规格配合使用
- ◆ Individually proof test at 2.5 times Working Load Limit
- ◆ 零件按工作拉力的2.5倍进行验证测试
- ◆ Fatigue tested at 1.5 times Working Load Limit for 20000 cycles
- ◆ 材料进行20000次疲劳测试
- ◆ Breakage test ①对每一批次产品进行严格的破坏性测试
- ◆ 100% magnetic crack detection ② 100% 进行磁粉探伤
- ◆ Surface finish (表面处理) : Powder painted (喷漆)
- ◆ Colour code (颜色) : Red (红色) RAL3020
- ◆ Yellow (黄色) RAL1023



SLR102-G80 CLEVIS C HOOK 80级C型羊角钩

SLR102


Not for lifting only for logging 不能用于起重，仅用于森林采伐业

ITEM NO.	WEIGHT (kg)	WLL (T)	B.L (T)	B±1.2	A±0.5	E±0.5	H±1	M±2	N±0.5	L±2
SLR102-6	0.413	1.12	4.48	31	8	8.5	18	54.5	25	31
SLR102-7/8	0.413	2	8	35	9.5	9.5	18	72.7	22.2	45.5
SLR102-10	0.97	3.15	12.8	44	12	13	22	95.3	33.7	117
SLR102-13	1.75	5.3	21.2	55	16	16	31	170	40	105

Ultimate load is 4 times the Working Load Limit 极限拉力是工作拉力的4倍

- ◆ Regular work (常规工作) : 70-9 DE SLR (SATELLITE NUMBER) (数量)

- ◆ Forged super alloy steel- Quenched and Tempered
- ◆ 高级合金钢经特殊合金热处理而成，经过热处理
- ◆ Individually proof test at 2.5 times Working Load Limit
- ◆ 零件按工作拉力的2.5倍进行验证测试
- ◆ Fatigue tested at 1.5 times Working Load Limit for 20000 cycles
- ◆ 材料进行20000次疲劳测试
- ◆ Breakage test ①对每一批次产品进行严格的破坏性测试
- ◆ 100% magnetic crack detection ② 100% 进行磁粉探伤
- ◆ 100% 进行磁粉探伤



SLR230-CLEVIS C HOOK 羊角C型钩

SLR230


ITEM NO.	WEIGHT (KG)	LC(KN)	MBL(KN)	A±1	B±0.5	C±0.5	E±0.3	H±0.3	G±0.3	L±1
8-SLR-230-7-10	1.42	45	90	75	6.5	25	11.5	19.5	24	30
8-SLR-230-8-10	5.43	50	100	35.5	10	25.4	10.3	19	23.4	33
8-SLR-230-10-10	9.54	55	110	41	12	26	13	22	23	130



WARNING 警告: This is a lifting device and should be used in accordance with the instructions.

G80 CLEVIS C HOOK 80级C型羊角钩

- ◆ Forged super alloy steel-Quenched and Tempered
- ◇ 高强度高品质特殊合金钢锻造而成，经过热处理
- ◆ Individually proof test at 2.5 times Working Load Limit
- ◇ 每件按工作拉力的2.5倍进行验证测试
- ◆ Fatigue tested at 1.5 times Working Load Limit for 20000 cycles
- ◇ 每件进行20000次疲劳测试
- ◆ Breakage test
- ◇ 对每一件产品进行严格的拉伸破坏测试
- ◆ 100% magnetic crack detection
- ◇ 100% 进行磁粉探伤




SLR913-CLEVIS C HOOK
羊角 C 型钩

SLR913

ITEM CODE	WEIGHT (kg)	WLL (kN)	BP (kN)	A±0.5	B±1	C±1	D±1	E±1	L±2
8-SLR913-718	0.45	45	60	8.5	14.5	14.5	11.5	11.5	95.0

- ◆ Forged super alloy steel-Quenched and Tempered
- ◇ 高强度高品质特殊合金钢锻造而成，经过热处理
- ◆ Individually proof test at 2.5 times Working Load Limit
- ◇ 每件按工作拉力的2.5倍进行验证测试
- ◆ Fatigue tested at 1.5 times Working Load Limit for 20000 cycles
- ◇ 每件进行20000次疲劳测试
- ◆ Breakage test
- ◇ 对每一件产品进行严格的拉伸破坏测试
- ◆ 100% magnetic crack detection
- ◇ 100% 进行磁粉探伤



SLR881-C TYPE CLEVIS FOREST HOOK
C 型羊角钩

SLR881


ITEM NO. 型号	WEIGHT (kg) 重量	LC (kN)	B.L (kN)	A±1	B±1.5	C±1	D±1	E±1.5	H±0.5	W±0.5	L±2
10-SLR881-8	0.47	40	120	0.6	11.8	20	20	10.5	28.5	16.2	100.0



CLEVIS SLING HOOK

羊角滑钩

- ◆ Forged super alloy steel- Quenched and Tempered
- ◇ 高强度和韧性特种合金钢锻造而成，经过热处理
- ◆ Individually proof test at 2.5 times Working Load Limit
- ◇ 每件钩工作拉力在2.5倍额定载荷测试
- ◆ Fatigue tested at 1.5 times Working Load Limit for 20000 cycles
- ◇ 钩钩进行20000次疲劳测试
- ◆ Breakage test
- ◇ 对每一批次产品进行严格的破坏性测试
- ◆ 100% magnaflex crack detection
- ◇ 100% 进行磁粉探伤



SLR673-NEW TYPE CLEVIS SLIP HOOK WITH LATCH

新款带舌片羊角滑钩


SLR673

ITEM NO.	WEIGHT (KG)	WLL/lbs	B.L./ft	A±1	B±0.5	h±1	L±1.5	E±1	M±0.5	Ø±0.6
8-SLR673-114	0.22	2750	1118mm	25	11	10.8	100	20	15	8.6

CLEVIS LARGE OPENING HOOK

羊角大开口钩

- ◆ Forged super alloy steel- Quenched and Tempered
- ◇ 高强度和韧性特种合金钢锻造而成，经过热处理
- ◆ Individually proof test at 2.5 times Working Load Limit
- ◇ 每件钩工作拉力在2.5倍额定载荷测试
- ◆ Fatigue tested at 1.5 times Working Load Limit for 20000 cycles
- ◇ 钩钩进行20000次疲劳测试
- ◆ Breakage test
- ◇ 对每一批次产品进行严格的破坏性测试
- ◆ 100% magnaflex crack detection
- ◇ 100% 进行磁粉探伤



SLR507- G80 CLEVIS LARGE OPENING HOOK

G80级羊角大开口钩

SLR507

ITEM NO.	WEIGHT (KG)	WLL (T)	B.L (T)	A±1	B±1	E±1.5	M±1.5	L±2
8-SLR507-12	2	5.3	2132	15.5	40.9	74	154	215

Ultimate limit is 4 times the Working Load Limit 破断力为额定工作拉力四倍

★ Regular hook (常规钩): 10-3" WLL 3-15T CE SLR > (吊钩) 常规钩 (普通)



WARNING 警告 See the Safety Manual for more information.

G80 EYE SLING HOOK 80级 眼型滑钩

- ◆ Forged super alloy steel- Quenched and Tempered
- ◇ 锻造高强度合金钢经热处理，经过应力退
- ◆ Suitable for EN818-2 G80 chain
- ◇ 与EN818-2标准40级链条配合使用
- ◆ Individually proof test at 2.5 times Working Load Limit
- ◇ 每件在工作拉力2.5倍进行验证测试
- ◆ Fatigue tested at 1.5 times Working Load Limit for 20070 cycles
- ◇ 抽样进行2000次疲劳测试
- ◆ Breakage test 对每一款次产品进行严格的破坏性测试
- ◆ 100% magnetic crack detection
- ◇ 100% 进行磁粉探伤
- ◆ With cast latch
- ◇ 每件产品均配有铸造保险舌片
- ◆ Surface finish: 表面抛丸; Powder coated (喷漆)
- ◆ Colour code: 颜色: Red (红色) RAL3020 / Yellow (黄色) RAL1003



SLR013-G80 EYE SLING HOOK WITH LATCH 80级眼型滑钩

SLR013



ITEM NO.	WEIGHT (KG)	WLL (T)	ELL (T)	B+1.5	E+2	D+2	A+3	L+2
8-SLR-18-06	0.1	1.52	4.48	5	21.5	30	20	104
8-SLR-18-7/8	0.4	2	5	11	27.5	34	26	125
8-SLR-18-10	0.9	3.58	12.4	15	37.2	39	31	167
8-SLR-18-13	2.7	5.2	21.2	18	38.8	51	40	214
8-SLR-18-16	5.2	8	30	23	42	62	50	250
8-SLR-18-20	9.8	12.5	50	24	44.8	74.8	60	295
8-SLR-18-22	12.9	16	70	30	50	68	68	348
8-SLR-18-26	19	21.2	84.8	35	55	84	84	394
8-SLR-18-32	29.0	31.0	138	37	102	100	84	440

Life safety load 5.4 times Eye Working Load Limit and 4 times Eye Working Load Limit

◆ Regular marking: 10-178 3.15T CE 30M + SAF CHROMIUM (镀铬)

SP-SLR013 - CAST LATCH KITS SLR013的铸造舌片配件

ITEM CODE 货号	SIZE 规格	ITEM CODE 货号	SIZE 规格
SP-SLR013-6	6-5	SP-SLR013-20	20-5
SP-SLR013-7/8	7/8-5	SP-SLR013-22	22-5
SP-SLR013-10	10-5	SP-SLR013-26	26-5
SP-SLR013-13	13-5	SP-SLR013-32	32-5
SP-SLR013-14	14-5		

1 SET = Cast Latch + SCREW + NUT + SPRING + OAL WASHERS

1套 = 铸造舌片 + 螺帽 + 螺母 + 弹簧 + 标准垫片

Regular mark 常规标记:

MARK 标记	10	-8	WLL 3.15T	SLR	CE	10-1
DESCRIPTION 描述	SIZE 规格	THICKNESS 厚度	WORKING LOAD LIMIT 工作力	MARKING WITH 标记	CE OFF IN CATE CE 认证	SAFETY NUMBER 安全号



G80 EYE SLING HOOK 80级 眼型滑钩

- ◆ Forged super alloy steel- Quenched and Tempered
◆ 高级合金钢经淬火及回火处理而成，强度高且稳定
- ◆ Suitable for EN18-2 G80 chain
◆ 与EN18-2级索具规格兼容使用
- ◆ Individually proof test of 2.5 times Working Load Limit
◆ 零件在工作拉力范围内进行验证测试
- ◆ Fatigue tested at 1.5 times Working Load Limit for 20000 cycles
◆ 吊钩进行20000次疲劳测试
- ◆ Breakage test 对每一批次产品进行严格的破坏性测试
- ◆ 100% magnetic crack detection
◆ 100% 进行磁粉探伤
- ◆ With cast (with)
◆ 每件产品均配有铸造保险舌片
- ◆ Surface finish 表面处理: Powder painted (喷漆)
◆ Colour code (颜色): Red (红色) RAL3020 / Yellow (黄色) RAL5005



SLR334 - EYE SLING HOOK WITH LATCH 眼型滑钩

SLR334



ITEM NO.	WEIGHT (KG)	WLL (T)	B.L (T)	M+2	A+2	E+2	H+3	B+3	L+3	D+3
8-SLR-334-05	0.3	1.12	4.45	10.5	9	18.5	23	64	95	12
8-SLR-334-7/8	0.65	2	8	25	11	29	27	84	134.5	24
8-SLR-334-10	1.05	3.15	12.8	34	14	39	35	107.5	167.5	29
8-SLR-334-13	1.75	5.3	21.2	42.5	17.5	48	40	124.5	207.5	35
8-SLR-334-16	3.2	8	32	52	22	49	48	150.5	255	50
8-SLR-334-20	5.3	12.5	40	62	26	61.5	56	167	300	60

Utilize the centre 4 times the Working Load Limit 使用中心力最大工作拉力为4倍

- ◆ Regular mark 常规标记: 10-8 HLLS 10T CE SLR + B17C3 SLR334 (型号)

SP-SLR334&SLR333 -CAST LATCH KITS SLR333和SLR334的铸造舌片配件



ITEM CODE 货号	SIZE 规格	ITEM CODE 货号	SIZE 规格
SP-SLR334-6	6-8	SP-SLR334-20	20-18
SP-SLR334-7/8	7/8-8		
SP-SLR334-10	10-9		
SP-SLR334-13	13-8		
SP-SLR334-16	16-9		

TRET = CAST LATCH + SCREW + NUT + SPRING (GALVANIZED)

1套 = 铸造舌片 + 螺栓 + 螺母 + 弹簧 (电镀锌)

Regular mark 常规标记:

MARK 标志	10	-8	WLL 3.15T	SLR	CE	18-1
CE MARKING 标志	符合 EN12282	CE MARK 标志	EN12282-1:2000 工作拉力	EN12282-1:2000 工作拉力	CE MARKING 标志	EN12282-1:2000 工作拉力



WARNING 警告 This is a lifting device and must be used in accordance with the instructions.

G80 EYE SLING HOOK WITH LATCH 80级 眼型货钩

- Forged super alloy steel - Quenched and Tempered.
- 锻造高强度合金钢经淬硬、回火处理。
- Suitable for EN1678-2 G80 chain.
- 与EN1678-2标准40吨级索具配合使用。
- Individually proof test at 2.5 times Working Load Limit.
- 每件在工作拉力的2.5倍进行验证测试。
- Fatigue tested at 1.5 times Working Load Limit for 20070 cycles
- 抽样进行20000次疲劳测试。
- Breakage test 对每一款次产品进行严格的破坏性测试。
- 100% magnetic crack detection.
- 100% 进行磁粉探伤。
- With latch, 每件产品均配有锁扣设计。
- Surface finish 表面处理: Powder painted (喷漆)
- Colour code (色号): Red (红色): RAL3020 / Yellow (黄色): RAL3005.



SLR039 - G80 EYE SLING HOOK WITH LATCH 80级眼型货钩

SLR039



ITEM NO.	WEIGHT (kg)	WLL (T)	B.L (T)	D±1	E±1.5	H±1	K±2	L±1
8-SLR039-6	0.32	1.12	4.48	12	22	30.5	82	142
8-SLR039-7.5	0.41	2	8	22	25	29	106.5	142
8-SLR039-10	0.64	3.15	12.6	31	27	28	129	193
8-SLR039-13	1.21	5.0	21.2	39	35.5	40	148	264
8-SLR039-16	3.35	8	32	51	44	45	187.5	355
8-SLR039-18/20	5.1	12.8	50	62	58	57	211.5	317
8-SLR039-23	9.07	15	60	73	67	68	212	393
8-SLR039-26	13	21.2	84.8	89	83	N/A	215	433
8-SLR039-32	26.8	31.5	120	98	95	91	297	495.5

Ultimate load is 4 times the Working Load Limit (破断力为工作拉力的4倍)

- Regular Mark (标准): 8P-3 WLL & T/C E SLR + BATCH NUMBER (批号)

SP-SLR039 & SLR040 - LATCH KIT

SLR039和SLR040的古片配件 (古片+弹夹+螺栓+螺母)



ITEM CODE 货号	SIZE 规格	ITEM CODE 货号	SIZE 规格
SP-SLR039-6	6-8	SP-SLR039-20	20-8
SP-SLR039-7.5	7.5-8	SP-SLR039-22	22-8
SP-SLR039-10	10-8	SP-SLR039-26	26-8
SP-SLR039-13	13-8	SP-SLR039-32	32-8
SP-SLR039-16	16-8		

Regular mark 常规标记:

MARK 标记	10	-8	WLL 3.15T	SLR	CE	18-1
DESCRIPTION 描述	SIZE 规格	THICKNESS 厚度	WORKING LOAD LIMIT 工作力	MARKING CODE 标记代码	CE CERTIFICATE CE 认证	BATCH NUMBER 批号

NOT FOR REUSE AFTER REMOVAL FROM ORIGINAL POSITION


WARNING 警告



EYE SLING HOOK

眼型滑钩

- ◆ Forged super alloy steel- Quenched and Tempered
- ◇ 高强度合金特殊合金钢锻造而成，经过热处理
- ◆ Individually proof test at 2.5 times Working Load Limit
- ◇ 每件在工作拉力的2.5倍进行验证测试
- ◆ Fatigue tested at 1.5 times Working Load Limit for 20000 cycles
- ◇ 抽样进行1.5倍工作拉力的20000次疲劳测试
- ◆ Breakage test- 对每一批次产品进行严格的抽样破坏测试
- ◆ 100% magnified crack detection 100% 进行缺陷探伤
- ◆ Surface finish (表面处理) : Powder plating (涂层)
- ◆ Colour code (色号) : Red (红色) RAL3020
- Yellow (黄色) RAL1003



SLR847-EYE SLING HOOK WITH LATCH


SLR847

眼型滑钩

ITEM CODE	WEIGHT (kg)	WLL (T)	BL (T)	A±1	E±1.5	M±2	N±1	H±1	L±3	Φ±2
8-SLR847-8	0.22	1.18	4.46	9.5	29	70	12	15	110	21
8-SLR847-718	0.005	2	8	16	27	26	24	27.5	144	25
8-SLR847-10	1.22	2.95	12.6	12	38	102	24	23	100	34
8-SLR847-13	2.43	5.9	21.2	28	40	130.7	56	37	227	42
8-SLR847-16	3.64	8	32	34.5	44	161	41.5	41	257	52
8-SLR847-1820	5.9	12.5	50	27	62	187	48	50	301	60
8-SLR847-22	9.1	18	70	32	72	240	57	59.5	367	72

Minimum load is at least the Working Load Limit 最小能力是工作拉力的两倍

- ◆ Forged super alloy steel- Quenched and Tempered
- ◇ 高强度合金特殊合金钢锻造而成，经过热处理
- ◆ Individually proof test at 2.5 times Working Load Limit
- ◇ 每件在工作拉力的2.5倍进行验证测试
- ◆ Fatigue tested at 1.5 times Working Load Limit for 20000 cycles
- ◇ 抽样进行1.5倍工作拉力的20000次疲劳测试
- ◆ Breakage test- 对每一批次产品进行严格的抽样破坏测试
- ◆ 100% magnified crack detection 100% 进行缺陷探伤
- ◆ Surface finish (表面处理) : Powder plating (涂层)
- ◆ Colour code (色号) : Red (红色) RAL3020
- Yellow (黄色) RAL1003



SLR864-EYE SLING HOOK WITH CAST LATCH

SLR864

眼型滑钩 带铸舌

ITEM NO.	WEIGHT (kg)	WLL (T)	BL (T)	A±1	E±1.5	M±2	N±1	L±3	Φ±2	Φ'±2
8-8	0.3	1.12	4.34	10	30	77	2.5	120	18	20
718-8	0.005	2	8	16	29	81	9.2	153	21	25
10-8	1.25	2.95	12.6	12	38	112	12	148	21	34
13-8	2.25	5.3	21.2	18.5	30	131	16.5	233	27	43
16-8	3.7	8	32	24.5	48	190.5	20.2	264	40	50



WARNING 警告: This is a lifting device and should be used in accordance with the instructions.

G80 EYE FOUNDRY HOOK 80级 眼型大开口钩

- ◆ Forged super alloy steel- Quenched and Tempered
- ◇ 高强度合金钢锻造- 淬火回火处理
- ◆ Suitable for EN818-2 G80 class
- ◇ 符合EN818-2标准A2级规格配合使用
- ◆ Individually proof test at 2.5 times Working Load Limit
- ◇ 每件在工作拉力2.5倍进行验证测试
- ◆ Fatigue tested at 1.5 times Working Load Limit for 20000 cycles
- ◇ 钩体进行1.5倍工作拉力20000次疲劳测试
- ◆ Breakage test
- ◇ 对每一挂次产品进行严格的钩体破坏测试
- ◆ 100% magnetic crack detection
- ◇ 100% 磁粉探伤检测
- ◆ Surface finish (表面处理): Powder painted (喷漆)
- ◆ Colour code (色号): Red (红色) RAL3020
- Yellow (黄色) RAL1003



SLR116-G80 EYE FOUNDRY HOOK G80 眼型大开口钩

SLR116

RECOMMENDED 推荐产品 With flat on eye 钩眼处有压扁



ITEM NO.	WEIGHT (kg)	WLL (T)	S.L. (T)	Φ ±1	L ±3	B ±2	R ±2	E ±1	Φ1 ±1	H ±2	M
8-SLR116-1.12T	0.152	1.12	4.48	25	135	150	102.7	49	15	17	19
8-SLR116-2.5T	0.39	2	7.5	34	185.5	190	120.5	70	15	19	20
8-SLR116-3.2T	1.3	3.2	12.8	37.5	190	193.5	155	79	15	25	21
8-SLR116-5.3T	2.32	5.3	21.2	41	207.5	195	174	90	16	29	29
8-SLR116-8T	4	8	32	45	215	218	195	105	22	37	40
8-SLR116-12.5T	7.3	12.5	50	50	235	252	242	114	25	41	57
8-SLR116-16T	11.4	16	64	54	274	275	275	121	27	50	55

Ultimate load is 4 times the Working Load Limit. 钩眼处力量工作拉力4倍。

- ◆ Regular mark (常规标记): 10-8 WLL 3.15T CE SLR BATCH NUMBER 2009

Regular mark 常规标记:

MARK 标记	10	-8	WLL 3.15T	SLR	CE	10-1
DESCRIPTION 说明	SIZE 尺寸	GRADE 80 强度级	WORKING LOAD LIMIT 工作力	MANUFACTURE 生产国	CE OFFER 认证 CE 认证	FACTORY NUMBER 厂号

NOTES: 1. ALL DIMENSIONS ARE IN MILLIMETERS

WARNING 警告



ALLOY EYE HOOK 异型眼型抓钩

- ◆ Large throat opening and small cross area
- ◇ 大开口，小截面，更方便连接和放入。
- ◆ Forged alloy steel-high strength and good ductility
- ◇ 优质合金钢锻造而成，强度高且韧性好。
- ◆ Only for general hoist (NOT for overhead lifting)
- ◇ 仅用于一般吊钩，不得用于吊上起重作业。



SLR220-ALLOY EYE HOOK

SLR220

异型眼型抓钩

ITEM NO.	WEIGHT (KG)	WLL (T)	B ₁ (T)	Ø±2	B±2	E±2	H±3	L±3	P±3
8-SLR-220-3.2T	0.54	3.2	12.8	31	97	40	29.3	172.5	23
8-SLR-220-8.8T	5.17	8.8	36.7	51	95	75	32.5	189	35

Ultimate load is 4 times the Working Load Limit 极限负荷是工作负荷的4倍

- ◆ Regular mark (常规标记): WLL 3.2T OR 8.8T

3040 EYE HOIST HOOK 3040系列眼型吊钩

- ◆ Forged super alloy steel- Quenched and Tempered
- ◇ 高强度易切削特种合金(预制造而成，经过热处理)
- ◆ Inductively proof test at 2.5 times Working Load Limit
- ◇ 素钩在工作负荷的2.5倍进行磁致伸缩测试
- ◆ Breakage test
- ◇ 对每一批次产品进行严格的破坏性测试
- ◆ 100% magnetic crack detection
- ◇ 100% 进行磁粉探伤



SLR368-3040 EYE HOIST HOOK

SLR368

3040系列眼型吊钩

WITH LARGE OPENING 大开口

ITEM CODE	WEIGHT (kg)	WLL (T)	BF (T)	N±1	Ø±1	E±1	M±2	H±1	L±2
8-SLR368-08T	0.76	8	31	16	96	41	104.5	32.5	154
8-SLR368-50T	1.32	50	12.5	10	52	24.0	115.5	22.5	100
8-SLR368-72T	2.56	72	21.2	23.5	23	60	162	47	227.5

Ultimate load is 4 times the Working Load Limit 极限负荷是工作负荷的4倍

- ◆ Regular mark (常规标记): WLL 8T OR 50T OR 72T



WARNING 警告 Do not use for lifting people or for any other purpose.

G80 EYE FOUNDRY HOOK 80级 小眼滑钩

- ◆ Forged super alloy steel- Quenched and Tempered
- ◇ 高强度耐热性材料合金钢锻造而成，经过热处理
- ◇ Individually proof test at 2.5 times Working Load Limit
- ◇ 每件按工作压力的2.5倍进行验证测试
- ◆ Fatigue tested at 1.5 times Working Load Limit for 20000 cycles
- ◇ 抽样进行20000次疲劳测试
- ◆ Breakout test
- ◇ 对每一批次产品进行严格的破断试验
- ◆ 100% magnetic crack detection
- ◇ 100% 进行磁粉探伤
- ◆ Surface finish (表面处理) : Powder painted (镀锌)
- ◆ Colour code (颜色) : Red (红色) RAL3020
Yellow (黄色) RAL1003



SLR015-G80 EYE FOUNDRY TYPE G80 小眼滑钩

SLR015



ITEM NO.	WEIGHT (kg)	WLL (T)	SL (IT)	E=1.2	A=1	D=1	H=1	M=1	N=0.5	K=2	L=2
8-SLR015-5	1.10	1.8	1.4	63.5	22	12	33	25.4	18	125	90
8-SLR015-6	1.90	3	2	81.3	25	18	33	35.4	18	178	90
8-SLR015-10	2.05	5.2	4	96.5	32	28	33	42.5	25	180	100
8-SLR015-13	3.25	6.4	5.0	108	35.8	32	40.5	48.1	25	171	105
8-SLR015-16	5.20	8.2	6.4	110	36	32	52	45	32	125	115
8-SLR015-20	6.1	10.8	8.2	115	40	38	58	50.5	34	125	120
8-SLR015-22	11.5	15.5	11.2	122.5	45	45	68	57	40	158	121
8-SLR015-25	16.5	21.6	16.4	140	50	50.5	72	65	45	182	142
8-SLR015-32	26.0	32.8	25.2	162.5	60.5	61.5	81.4	80	50	177	161

Ultimate tensile strength 1/2 times 90% minimum Load 破断后力量工作压力的4倍

Regular mark 常规标记:

MARK 标记	10	-8	WLL 3.2T	SLR	CE	18-1
DESCRIPTION 描述	Size 规格	GRADE NO 规格号	WORKING LOAD LIMIT 工作力	MARKING WITH 6-6002	CE OFF 18-1471 CE 认证	FOR CH. NUMBER 18-1471


NOTICE: ALWAYS USE THE PRODUCT WITH THE PROPER METHOD

WARNING 警告



G80 EYE SLING HOOK 80级 眼型滑钩

- ◆ Forged super alloy steel- Quenched and Tempered
◊ 高强度合金特种合金钢锻造而成，经回火处理
- ◆ Individually proof test at 2.5 times Working Load Limit
◊ 每件按工作压力的2.5倍进行验证测试
- ◆ Fatigue tested at 1.5 times Working Load Limit for 20000 cycles
◊ 按样进行20000次疲劳测试
- ◆ Breakage test 对每一批次产品进行严格的破坏性测试
- ◆ 100% magnetic crack detection 100% 进行磁粉探伤
- ◆ Surface finish (表面处理) : Powder painted (喷漆)
- ◆ Colour code (色号) : Red (红色) RAL3020
Yellow (黄色) RAL1003



SLR056-G80 EYE SLING HOOK 80级 眼型滑钩


SLR056

ITEM NO.	WEIGHT (kg)	WLL (T)	B.L. (T)	ø1	D±1	E±1.5	F±1	H±1	L±2	M±2
8-SLR056-08	0.4	0	8	17.8	11	31	23	25.0	118	95
8-SLR056-10	0.7	3.2	12.8	21.5	12.5	37.5	28	30.8	142	108
8-SLR056-13	1.32	5.4	21.8	27	17	45	38	37.8	172	127
8-SLR056-16	2.11	8.2	32.8	30	20	52.5	40	43.5	200	150

WLL means load is 4 times the Working Load Limit 使用额定工作压力的4倍

- ◆ Particular mark (采购标志) : WLL 1T OR SLR+RATCH NUMBER (色号)

- ◆ Forged super alloy steel- Quenched and Tempered
◊ 高强度合金特种合金钢锻造而成，经回火处理
- ◆ Individually proof test at 2.5 times Working Load Limit
◊ 每件按工作压力的2.5倍进行验证测试
- ◆ Fatigue tested at 1.5 times Working Load Limit for 20000 cycles
◊ 按样进行20000次疲劳测试
- ◆ Breakage test 对每一批次产品进行严格的破坏性测试
- ◆ 100% magnetic crack detection 100% 进行磁粉探伤
- ◆ Surface finish (表面处理) : Powder painted (喷漆)
- ◆ Colour code (色号) : Red (红色) RAL3020
Yellow (黄色) RAL1003



SLR218-EYE SLING HOOK 眼型滑钩

SLR218

ITEM NO.	WEIGHT (kg)	WLL (T)	B.L. (T)	ø1±1	ø2±1.5	D±1	E±1.5	F±1	H±1	K±2	L±2
SLR-218	0.434	1	4	20.5	31	11.5	20.5	17	59.8	68	129.5

WLL means load is 4 times the Working Load Limit 使用额定工作压力的4倍

- ◆ Particular mark (采购标志) : WLL 1T OR SLR+RATCH NUMBER (色号)



WARNING 警告 Do not use this equipment if you are not a qualified person.

EYE SLING HOOK

眼型滑钩

- ◆ Forged super alloy steel- Quenched and Tempered
- ◇ 高强度合金钢锻造- 淬火回火处理
- ◆ Individually proof test at 2.5 times Working Load Limit
- ◇ 每件独立工作能力的2.5倍进行验证测试
- ◆ Fatigue tested at 1.5 times Working Load Limit for 200,000 cycles
- ◇ 材料进行200,000次疲劳测试
- ◆ Breakage test 对每一件产品进行严格的破坏性测试
- ◆ 100% magnasonic crack detection 100% 进行超声波探伤
- ◆ Surface finish (表面处理): Powder painted (喷漆)
- ◆ Colour code (颜色): Red (红色) RAL3009

Yellow (黄色) RAL1003



SLR175-G80 EYE SLING HOOK

80级 眼型滑钩

SLR175


ITEM NO.	WEIGHT (kg)	WLL (T)	S.L (T)	Ø1±1	Ø2±1	Ø±1	E±1.5	F±1	H±1	K±1	L±2
B-SLR175-6	0.4	1.12	4.42	22	20	10	20	17	22	46	124
B-SLR175-7W	0.62	2	8	25	24	11.5	26	18.3	24.8	47	143.5
B-SLR175-10	0.99	3.15	12.8	28.6	28	13.6	34	25	32	50.6	117.6
B-SLR175-13	2.35	5.3	21.2	30.5	40	15	41	33	41.5	78	225.5

Ultimate load is 4 times the Working Load Limit 破断力是工作能力的4倍

- ◆ Regular color (常规颜色): 15-BW (RAL 1003) SLR-G80 (RAL 3009) (黄色)

- ◆ Forged super alloy steel- Quenched and Tempered
- ◇ 高强度合金钢锻造- 淬火回火处理
- ◆ Individually proof test at 2.5 times Working Load Limit
- ◇ 每件独立工作能力的2.5倍进行验证测试
- ◆ Fatigue tested at 1.5 times Working Load Limit for 200,000 cycles
- ◇ 材料进行200,000次疲劳测试
- ◆ Breakage test 对每一件产品进行严格的破坏性测试
- ◆ 100% magnasonic crack detection 100% 进行超声波探伤
- ◆ Surface finish (表面处理): Powder painted (喷漆)
- ◆ Colour code (颜色): Red (红色) RAL3009

Yellow (黄色) RAL1003



SLR219-EYE SLING HOOK

眼型滑钩

SLR219

ITEM NO.	WEIGHT (kg)	WLL (T)	S.L (T)	Ø1±1	Ø2±1.5	Ø±1	E±1.5	F±1	H±1	K±1.5	L±2
SLR219-6	0.516	1.12	4.45	18.5	18	10	21	19	20	92	117


Ultimate load is 4 times the Working Load Limit 破断力是工作能力的4倍

- ◆ Regular color (常规颜色): 15-BW (RAL 1003)



G80 EYE SLING HOOK 80级 眼型滑钩

- ◆ Forged super alloy steel- Quenched and Tempered
○ 高强度合金钢铸造成型，经过热处理
- ◆ Individually proof tested at 2.5 times Working Load Limit
○ 每件按工作能力的2.5倍进行验证测试
- ◆ Fatigue tested at 1.5 times Working Load Limit for 20,000 cycles
○ 每件进行20000次疲劳测试
- ◆ Breakage test- 对每一件产品进行严格的破坏性测试
- ◆ 100% magnetic crack detection- 100% 进行磁粉探伤
- ◆ Surface finish (表面处理) : Powder painted (喷漆)
- ◆ Colour code (色号) : Red (红色) RAL3020
Yellow (黄色) RAL1005



- ◆ Pinhole included (带防顶钩) when is needed
○ 在需要下，钩子的顶部结构会自成一体，更安全

SLR302-G80 EYE SLING HOOK 80级 眼型滑钩


SLR302

ITEM NO.	WEIGHT (kg)	WLL (T)	B.L (T)	A±1	Φ±1	D±1	E±1.5	F±1	H±1	L±2
8-SLR302-6	0.25	1.12	4.45	20	21	9	26	54.5	22.2	121.5
8-SLR302-7.5	0.65	2	8	25	23	11	24	10	32	147.5
8-SLR302-10	1.05	3.15	12.6	30	25	13	22	28.5	35	164
8-SLR302-13	2	5.3	21.2	43	30	16	20	27.5	42.5	225
8-SLR302-16	3.75	8	32	50	45	20	18	35.5	54	295

(Minimum load is 4 times the Working Load Limit 最小使用力是工作能力的4倍)

- ◆ Product mark (产品标记) : 01-3 WLL: 5.3 T (3.5 SLR 4047013-16 M20 (6mm))

- ◆ Forged super alloy steel- Quenched and Tempered
○ 高强度合金钢铸造成型，经过热处理
- ◆ Individually proof tested at 2.5 times Working Load Limit
○ 每件按工作能力的2.5倍进行验证测试
- ◆ Fatigue tested at 1.5 times Working Load Limit for 20,000 cycles
○ 每件进行20000次疲劳测试
- ◆ Breakage test- 对每一件产品进行严格的破坏性测试
- ◆ 100% magnetic crack detection- 100% 进行磁粉探伤



SLR315-G80 EYE SLING HOOK 80级 眼型滑钩

SLR315

ITEM NO.	WEIGHT (kg)	WLL (T)	B.L (T)	A±1	B±1	E±1.5	F±1	H±1	L±2	Φ±1
8-SLR315-6	0.21	1.12	4.45	20.5	21	24	15	14	114.5	15
8-SLR315-7.5	0.60	2	8	25.5	26	29.7	19.5	25.5	135.5	20
8-SLR315-10	0.90	3.15	12.6	35	37.5	34	23	27.7	155.7	28
8-SLR315-13	1.25	5.3	21.2	48.5	47.5	43	32	34.5	210	45

(Minimum load is 4 times the Working Load Limit 最小使用力是工作能力的4倍)

- ◆ Product mark (产品标记) : 01-3 WLL: 5.3 T (3.5 SLR 4047013-16 M20 (6mm))



WARNING 警告 This product is not to be used for lifting personnel. (本产品不得用于吊运人员)

G80 EYE SLING HOOK 80级 眼型滑钩

- Forged super alloy steel - Quenched and Tempered
- 高强度合金钢材料经淬火及回火处理
- Suitable for E8815-2 G80 chain
- 与E8815-2 G80级链条配合使用
- Individually proof test at 2.5 times Working Load Limit
- 组件按工作拉力的2.5倍进行验证测试
- Fatigue tested at 1.5 times Working Load Limit for 20000 cycles
- 在1.5倍工作拉力下组件进行20000次疲劳测试
- Breakage test
- 对每一批次产品进行严格的破坏性测试
- 100% magnetic crack detection
- 100% 进行磁粉探伤
- Surface finish (表面处理) : Powder painted (粉末)
- Colour code (色码) : Red (红色) : RAL3020
- Yellow (黄色) : RAL1003



SLR332-G80 EYE SLING HOOK
80级 眼型滑钩

SLR332



ITEM NO.	WEIGHT (kg)	WLL (T)	SL (T)	ø1±1	ø2±1	D±1	E±1.6	F±1	H±1	L±1
8-SLR332-6	0.26	1.32	4.40	20	25	9	22	19	29.6	120
8-SLR332-7/8	0.5	2	9	25.6	34	11.5	25	19	33.5	138.5
8-SLR332-10	0.85	3.15	12.0	32.5	38	15.5	34	20	39	175.5
8-SLR332-13	1.95	5.3	17.7	38.5	48	19	41	23.5	37	212
8-SLR332-16	3.45	8	28	50	58	24	44	34	42.5	240
8-SLR332-18/20	6.60	12.5	50	60	61	28.5	52	40.5	54.5	310
8-SLR332-22	10.20	15	50	68	80	31.5	60	44	75	375.5

Ultimate load is 8 times the Working Load Limit 破断拉力是工作拉力的8倍

- Tagging system (识别系统) : 10-A WLL 3.15T CE SLR-HATCHER 882R (标准)



G80 EYE SLING HOOK 80级 眼型滑钩

- ◆ Forged super alloy steel- Quenched and Tempered
◊ 高强度合金钢特殊合金钢锻造而成，经过热处理
- ◆ Individually proof test at 2.5 times Working Load Limit
◊ 每件按工作力极限2.5倍进行验证测试
- ◆ Fatigue test at 1.5 times Working Load Limit for 2000 cycles
◊ 每件进行2000次疲劳测试
- ◆ Breakage test 对每一件次产品进行严格的破坏强度测试
- ◆ 100% magnalux crack detection 100% 进行磁粉探伤
- ◆ Surface finish (表面处理) : Powder painted (喷漆)
- ◆ Colour code (色号) : Red (红色) RAL3020
Yellow (黄色) RAL1020



SLR380-G80 EYE SLING HOOK 80级 眼型滑钩


SLR380

ITEM NO.	WEIGHT (kg)	WLL (T)	B.L (T)	A±1	Φ±1	D±1	E±1.5	F±1	H±1	L±2	M±2
8-SLR380-6/7	0.45	1.5	8	25.4	25	10.2	27	10.5	34.4	180	57
8-SLR380-8	0.63	2	8	25.3	25	12	30.5	21	28	195.5	20
8-SLR380-10	1.25	3.15	12.6	58	30	18	40	27	34	195	124
8-SLR380-12	3.02	5.4	21.8	44.0	40	14	44	34	42	325	143.5

(Working Load is 4 times the Working Load Limit 使用拉力是工作力极限4倍)

- ◆ Particular mark (采购标记) : 3-0 WLL 2.5 SLR + BATCH NUMBER (色号)

- ◆ Forged super alloy steel- Quenched and Tempered
◊ 高强度合金钢特殊合金钢锻造而成，经过热处理
- ◆ Individually proof test at 2.5 times Working Load Limit
◊ 每件按工作力极限2.5倍进行验证测试
- ◆ Fatigue test at 1.5 times Working Load Limit for 2000 cycles
◊ 每件进行2000次疲劳测试
- ◆ Breakage test 对每一件次产品进行严格的破坏强度测试
- ◆ 100% magnalux crack detection 100% 进行磁粉探伤
- ◆ Surface finish (表面处理) : Powder painted (喷漆)
- ◆ Colour code (色号) : Red (红色) RAL3020
Yellow (黄色) RAL1020



SLR631-EYE SLING HOOK 眼型滑钩

SLR631

ITEM NO.	WEIGHT (kg)	WLL (T)	B.L (T)	A±1	B±1	E±1.5	L±2	Φ±1
SLR631-6T	2.21	6	24	46	35.6	57.5	227	42

(Working Load is 4 times the Working Load Limit 使用拉力是工作力极限4倍)


- ◆ Particular mark (采购标记) : WLL 2.5 SLR + BATCH NUMBER (色号)



WARNING 警告

Do not use for lifting people or other loads exceeding the rated capacity.

FORGED EYE HOOK 锻造眼钩



- ◆ Forged upper alloy steel. Quenched and Tempered. 合金钢锻造，经过热处理。
- ◆ Breakage test 对每一批产品进行严格的破坏性测试。
- ◆ 100% magnetize crack detection, 100% 进行磁粉检测 With cast iron 配备铸铁面衬
- ◆ Grade Q235 等级为Q235, Surface finish 表面处理 1 ; Powder plating 喷涂

SLR327 - DIN7541 EYE HOOK

50级标准7541型眼钩

SLR327

ITEM NO.	WEIGHT (kg)	WLL (T)	B.L (T)	A±1	B±2	C±0.5	D±1	E±2
8-SLR327-H17	0.15	0.5	2	18	32	9	18	85
8-SLR327-H20	0.2	1	4	25	38	12.5	25	107
8-SLR327-H21	0.3	1.25	5	280	39	14	28.5	150
8-SLR327-H22	1.1	1.6	6.4	31.5	39	16.5	32	174
8-SLR327-H23	1.3	2	8	35	39	16	37	190
8-SLR327-H24	2	2.5	10	41	40	21	41	212
8-SLR327-H25	3.4	3	12	49.5	44	25	47.5	250
8-SLR327-H26	5.8	4	16	59	55.5	26	49.4	275

Reg. & mark (英及品记) : WLL 27 02

◆ Regular mark 常规标记:

MARK 标记	75	-8	WLL 0.5T	SLR	CE	18-1
DESCRIPTION 描述	50级 235	50级, 20 450级	50级, 20, 450级 235级	50级, 20, 450级 235级	CE, OFF 18-1 CE, 18-1	18-1 18-1



FISHING AND OVERSEAS RIGGING

渔业索具

- ◆ Forged super alloy steel- Quenched and Tempered
- ◇ 高强度锻造合金钢经热处理，经过防锈处理
- ◆ Individually proof test at 2.5 times Working Load Limit
- ◇ 每件渔具工作力在2.5倍进行验证测试
- ◆ Fatigue tested at 1.5 times Working Load Limit for 20000 cycles
- ◇ 抽样进行20000次疲劳测试
- ◆ Breakage test
- ◇ 对每一件产品进行严格的材料破坏测试
- ◆ 100% magnetic crack detection
- ◇ 100% 进行磁粉探伤




SLR023- ALLOY FORGED G HOOK 合金钢锻造G型钩

SLR023

ITEM NO.	WEIGHT (kg)	WLL (T)	BL (T)	Φ±1	B±1.5	C±1	E±0.5	L±2
8-SLR023-4.2T	0.2	4.2	11	27.5	30	20	15.3	126.5
8-SLR023-6.4T	2.0	6.4	32	31	116.5	32	20	179

Ultimate Load is 5 times the Working Load Limit 破断能力是工作能力的5倍
Regular mark (标准标记): 8-SLR023-4.2T SLR - BATCH NUMBER 标准

- ◆ Forged super alloy steel- Quenched and Tempered
- ◇ 高强度锻造合金钢经热处理，经过防锈处理
- ◆ Individually proof test at 2.5 times Working Load Limit
- ◇ 每件渔具工作力在2.5倍进行验证测试
- ◆ Fatigue tested at 1.5 times Working Load Limit for 20000 cycles
- ◇ 抽样进行20000次疲劳测试
- ◆ Breakage test
- ◇ 对每一件产品进行严格的材料破坏测试
- ◆ 100% magnetic crack detection
- ◇ 100% 进行磁粉探伤



SLR066- FISHING AND OVERSEAS RIGGING G型板钩

SLR066

ITEM NO.	WEIGHT (kg)	WLL (T)	BL (T)	A	E	F	L	Φ
8-SLR066-1.0T	0.3	1	5	17±1	11.5±1	37±1	64±2	17.5±1
8-SLR066-1.5T	0.5	1.5	7.5	18±1	13±1	37±1	107±2	20±1
8-SLR066-3.2T	0.9	3.2	16	20±2	15±1	40±2	121±2	25±2
8-SLR066-5.6T	3.1	5.6	28	30±2	25.5±2	57.7±2	189±4	35±2

Ultimate Load is 5 times the Working Load Limit 破断能力是工作能力的5倍
Regular mark (标准标记): 8-SLR023-4.2T SLR




WARNING 警告

SLR023-4.2T SLR023-6.4T SLR066-1.0T SLR066-1.5T SLR066-3.2T SLR066-5.6T

FISHING AND OVERSEAS RIGGING

渔业索具

- ◆ Forged super alloy steel- Quenched and Tempered
- ◇ 高强度合金钢锻造并淬火回火处理
- ◆ Individually proof test at 2.5 times Working Load Limit
- ◇ 每件按工作压力的2.5倍进行验证测试
- ◆ Fatigue tested at 1.5 times Working Load Limit for 20000 cycles
- ◇ 材料进行20000次疲劳测试
- ◆ Breakage test
- ◇ 对每一件产品进行严格的破坏性测试
- ◆ 100% magnifical crack detection
- ◇ 100% 进行裂纹探伤



SLR087- ALLOY FORGED DV HOOK
合金锻造DV钩


SLR087

ITEM NO.	WEIGHT (kg)	WLL (T)	BL (T)	Φ±1	B±1.5	E±0.1	H±1	L±2
8-SLR087-1.5T	0.5	1.5	7.5	28	51	3	35	100
8-SLR087-3.0T	1.73	3	15	30	72	3	41	110
8-SLR087-5.0T	1.2	5	20	35	84	3	42	137
8-SLR087-8.0T	2.04	8	40	42	90	3	42	163

Ultimate load is 5 times the Working Load Limit 破断力是工作压力的5倍

Regular mark (常规标记) : 8-SLR087/3E SLR-BATCH NUMBER (批号)

- ◆ Forged super alloy steel- Quenched and Tempered
- ◇ 高强度合金钢锻造并淬火回火处理
- ◆ Individually proof test at 2.5 times Working Load Limit
- ◇ 每件按工作压力的2.5倍进行验证测试
- ◆ Fatigue tested at 1.5 times Working Load Limit for 20000 cycles
- ◇ 材料进行20000次疲劳测试
- ◆ Breakage test
- ◇ 对每一件产品进行严格的破坏性测试
- ◆ 100% magnifical crack detection
- ◇ 100% 进行裂纹探伤



SLR216- FISHING AND OVERSEAS RIGGING
开口渔业钩

SLR216

ITEM NO.	WEIGHT (kg)	WLL (T)	BL (T)	Φ±1	B±1.5	E±1	H±1	L±2
8-SLR216-1.5T	0.4	1.5	6	16.3	51	4.5	34	81.5
8-SLR216-2.6T	0.5	2.6	10.4	21.3	75.5	4.3	42	110.5
8-SLR216-4T	1.25	4	18	25.1	94	4.5	50.6	144
8-SLR216-6T	2.113	6	24	26.3	111	5	54	164

Ultimate load is 4 times the Working Load Limit 破断力是工作压力的4倍

Regular mark (常规标记) : WLL1.5T/3E SLR-BATCH NUMBER (批号)



FISHING AND OVERSEAS RIGGING

渔业用具

- ◆ Forged super alloy steel- Quenched and Tempered
- ◆ 高强度合金钢经淬火及回火处理
- ◆ Individually proof test at 2.5 times Working Load Limit
- ◆ 每件经工作拉力达2.5倍进行验证测试
- ◆ Fatigue tested at 1.5 times Working Load Limit for 20000 cycles
- ◆ 疲劳进行20000次循环测试
- ◆ Breakage test
- ◆ 对每一批次产品进行严格的破坏性测试
- ◆ 100% magnetic crack detection
- ◆ 100% 进行磁粉探伤



SLR262- ALLOY FORGED G HOOK 合金锻造G型钩

SLR262

ITEM CODE 货号	WEIGHT (KG)重量	WLL(T)	B.L(T)	A±1	B±1.5	E±1	T±0.5	L±2
8-SLR262-3T	0.59	3	15	33.5	72.5	41.5	12	118
8-SLR262-5T	1.13	5	25	55	115.5	44	15	135.5
8-SLR262-8T	3.3	8	40	87	185.5	47	15	150
8-SLR262-10T	7.65	10	50	111	235	50	10.3	125
8-SLR262-15T	15.1	15	75	151	320	73	20	215
8-SLR262-20T	34	20	100	202	391	82	25	245

Ultimate load is 2 times the Working Load Limit 破断力是工作拉力的2倍

Inspection mark (检验标记): WLL & T CB

- ◆ Forged super alloy steel- Quenched and Tempered
- ◆ 高强度合金钢经淬火及回火处理
- ◆ Individually proof test at 2.5 times Working Load Limit
- ◆ 每件经工作拉力达2.5倍进行验证测试
- ◆ Fatigue tested at 1.5 times Working Load Limit for 20000 cycles
- ◆ 疲劳进行20000次循环测试
- ◆ Breakage test
- ◆ 对每一批次产品进行严格的破坏性测试
- ◆ 100% magnetic crack detection
- ◆ 100% 进行磁粉探伤



SLR119-FORGED "OFG" HOOK G型钩

SLR119

ITEM NO.	WEIGHT (KG)	WLL (T)	B.L (T)	A±0.5	Ø±1	D±1	H±1	R±1.5	E±0.5	L±2
8-SLR119-10	0.21	2.15	12.9	20	22	14	22	25.5	12	113
8-SLR119-13	1.5	5.3	21.2	33	40	18	32	65.5	15	140.5
8-SLR119-15	1.9	9	32	32	52	22	35.5	117	15.4	175
8-SLR119-19	2.7	12.5	35	35	63	25	43	141	22.5	210.5


Ultimate load is 4 times the Working Load Limit 破断力是工作拉力的4倍

- ◆ Inspection mark (检验标记): 10-T, WLL & T CB, SLR=PARTS NUMBER (数量)



WARNING 警告 This is a lifting device and can be dangerous if not used properly.

- ◆ Forged super alloy steel- Quenched and Tempered
- ◇ 高强度合金钢经合金钢热处理，经过热处理
- ◆ Individually proof test at 2.5 times Working Load Limit
- ◇ 每件按工作压力的2.5倍进行验证测试
- ◆ Fatigue tested at 1.5 times Working Load Limit for 20000 cycles
- ◇ 每件进行20000次疲劳测试
- ◆ Breakage test
- ◇ 对每一批产品进行严格的断裂破坏测试
- ◆ 100% magniflix crack detection
- ◇ 100% 进行磁粉探伤



SLR822-NOSE TYPE ANTI-SLIP HOOK

G80 鼻型防滑钩

SLR822

ITEM NO.	WEIGHT/kg	WLL/T	BL/T	A±1	B±1	C±1	D±1	Ø±1	E±1	L±2.5
SLR822	1.5	8.15	12.6	22	93	40.8	26	31	42	202

- ◆ Forged super alloy steel- Quenched and Tempered
- ◇ 高强度合金钢经合金钢热处理，经过热处理
- ◆ Individually proof test at 2.5 times Working Load Limit
- ◇ 每件按工作压力的2.5倍进行验证测试
- ◆ Fatigue tested at 1.5 times Working Load Limit for 20000 cycles
- ◇ 每件进行20000次疲劳测试
- ◆ Breakage test
- ◇ 对每一批产品进行严格的断裂破坏测试
- ◆ 100% magniflix crack detection
- ◇ 100% 进行磁粉探伤



SLR-831 G80 EYE SLING HOOK WITH LATCH

G80 眼型滑钩

SLR831

ITEM NO.	WEIGHT/kg	WLL/T	BL/T	A±1	Ø1±1	E±1	ØD±1	Ø±1	L1±2	L±2	H±1
SLR831-18	3	9	12	93	22	97	70.4	51	135.2	255	40.3



FORGED HOOK 锻造钩

- ◆ Forged alloy steel-Quenched and tempered
- ◇ 优质合金钢锻造，经过热处理
- ◆ Regular mark(常规标记) : WLL5.3T



SLR228-HEAVY WINCH HOOK

重型吊钩

SLR228

ITEM NO. (型号)	WEIGHT (kg) 重量	WLL (LBS)	B.L (LBS)	Φ±1	A±1	B±1	C±1	D±1	E±1
102-518	1.5t			26	21	17.5	32.5	107	154.4
214-718	5.15t	11574	54295	21	20	27	49	130	130
↑	4.2	91727.5	108140	30	45.0	35	46.0	129	204
1-1-118	4.05t	91500	751900	35.5	38	24	50.8	140	207

Ultimate load is 4 times the Working Load Limit. 极限拉力是工作拉力4倍。

- ◆ Forged super alloy steel-Quenched and Tempered
- ◇ 高级合金钢在特殊合金钢制造而成，经过热处理
- ◆ Individually proof test at 2.5 times Working Load Limit
- ◇ 零件按工作拉力的2.5倍进行验证测试
- ◆ Fatigue tested at 1.5 times Working Load Limit for 20000 cycles
- ◇ 钩体进行20000次疲劳测试
- ◆ Breakage test
- ◇ 对每一批产品进行严格的破坏性测试
- ◆ 100% magnetic crack detection
- ◇ 100% 磁粉探伤探伤



SLR103-ALLOY LASHING HOOK

合金钢捆绑钩

SLR103

ITEM NO.	WEIGHT (kg)	WLL (T)	B.L (T)	Φ±1	E±2	R±2.5	L±2.5
2-SLR103-1.0T	1.25	1	4	20	18	125.5	127.2

Ultimate load is 4 times the Working Load Limit. 极限拉力是工作拉力4倍。


- ◆ Regular mark (常规标记) : 10-3 WLL:1.0T CO. SLP. + BATCH NUMBER (批号)



WARNING 警告 This is a heavy lifting device and can be dangerous if not used properly.

G80 SWIVEL HOOKS 80级 旋转钩

- ◆ Forged super alloy steel- Quenched and Tempered
- ◇ 高强度合金钢锻造并经回火处理，经过热处理
- ◆ Individually proof test at 2.5 times Working Load Limit
- ◇ 每件经工作能力的2.5倍进行验证测试
- ◆ Fatigue tested at 1.5 times Working Load Limit for 20000 cycles
- ◇ 每件进行20000次疲劳测试
- ◆ Breakage test
- ◇ 对每一批产品进行严格的破坏性测试
- ◆ 100% magniflux crack detection
- ◇ 100% 进行磁粉探伤



SLR788-SWIVLE HOOK WITH LATCH 带轴承旋转钩

SLR788

ITEM NO.	WEIGHT (kg)	WLL (T)	B.L (T)	A	B	E	M	L1	L	N	C	H
SLR-788-8-8	0.66	1.13	4.48	85±1.5	325±1	24±1.5	49±2	138±2	168±2	14±1	11±1	16±2.5
SLR-788-7.5-8	0.56	2	5	45±2	36±1	25.5±1.5	45±2	70±2	58±2	28±1	15±1	27±3.5
SLR-788-10-8	1.21	3.15	12.5	55±1	42±1	21±1.5	50±2	80±2	54±2	22±1	16±1.5	26.5±1
SLR-788-13-8	3.12	5.5	21.2	75±2	62±1.8	40±2	70±2	210±2	109±2	32±1.5	17±1.2	32±1
SLR-788-15-8	5.44	8	32	48±1	61±1.5	47±2	50±2	80±1	100±2	27.5±1.5	21.5±1.5	45±1
SLR-788-18120-8	6.5	12.5	50	85±2	34±2	66±2	104±2	59±4	104±4	41±2	26±2	52±2
SLR-788-22-8	15	15	30	105±2	10±2	70±2.5	224±2	44±4	50±4	58±2	75±2	12±2

Lifts the load at 4 times the Working Load Limit 根据能力是工作能力的4倍

- ◆ Regular mark (规格标记): 10-8 WLL: 1.1T C/L SLR + BATCH NUMBER (批号)

- ◆ Forged super alloy steel- Quenched and Tempered
- ◇ 高强度合金钢锻造并经回火处理，经过热处理
- ◆ Individually proof test at 2.5 times Working Load Limit
- ◇ 每件经工作能力的2.5倍进行验证测试
- ◆ Fatigue tested at 1.5 times Working Load Limit for 20000 cycles
- ◇ 每件进行20000次疲劳测试
- ◆ Breakage test
- ◇ 对每一批产品进行严格的破坏性测试
- ◆ 100% magniflux crack detection
- ◇ 100% 进行磁粉探伤

- ◆ 全球数据表中可找到WLL值



SLR268-G80 SWIVEL HOOK WITH LATCH 80级合金旋转钩

SLR268

ITEM NO.	WEIGHT (kg)	WLL (T)	B.L (T)	A±2	B±2.5	E±1.5	H±1.5	C±2	L±4
8-SLR268-7.5	0.55	2	8	30.5	35.5	27	27.5	25	114
8-SLR268-10	1.54	3.15	12.8	42	104.8	32	29.3	24	203
8-SLR268-13	3.24	5.5	21.2	49	126	40	56	41	241.8
8-SLR268-16	6.25	8	32	61	151	45	65.4	53	312


Lifts the load at 4 times the Working Load Limit 根据能力是工作能力的4倍

- ◆ Regular mark (规格标记): 10-8 WLL: 1.1T C/L SLR + BATCH NUMBER (批号)



G80 SWIVEL HOOKS 80级 旋转钩

- ◆ Forged super alloy steel- Quenched and Tempered
○ 高强度合金钢锻造而成，经过热处理
- ◆ Individually proof test at 2.5 times Working Load Limit
○ 每件按工作能力的2.5倍进行验证测试
- ◆ Fatigue tested at 1.5 times Working Load Limit for 20000 cycles
○ 钩体进行20000次疲劳测试
- ◆ Breakage test ○ 对每一批次产品进行严格的破坏性测试
- ◆ 100% magnifying crack detection ○ 100% 进行磁粉探伤
- ◆ Can be Rotated under Non-load Conditions
○ 非满载条件下可旋转90度角



SLR040-G80 SWIVEL HOOK WITH LATCH 80级带舌旋转钩

SLR040

ITEM NO.	WEIGHT (kg)	WLL (T)	B.L (T)	A±1.2	E±1.5	B±2.5	H±1	K±2	L±2.5	M±1
B-SLR040-06	0.24	1.12	4.84	30	12	22.5	8	106	127	16
B-SLR040-08	1.00	2	3	42	21.5	35	15.8	160	192	21
B-SLR040-10	1.24	3.15	12.8	42.5	28	35	15.8	182.5	203.5	23
B-SLR040-13	3.5	5.3	21.2	45	30.8	35	15	151	240	31
B-SLR040-16	4.80	8	30	52	43	53	28	242.5	212	34
B-SLR040-20	7.4	12.5	60	55	49.0	61	23.0	270.0	243.0	41.5
B-SLR040-22	10.5	15	80	70	54.5	65	30	330	431	45.7
B-SLR040-25	21.4	21.5	54.5	105	61	114	40	421.5	545.5	70
B-SLR040-32	32	31.5	120	115	100	90	40	455.0	590	110.2

Lifts to load is 4 times the Working Load Limit 钩体能力为工作能力的4倍

- ◆ Popular mark (常用标识) : 10-R VLLS-127 GE SLR + BATCH NUMBER (批号)

- ◆ Forged super alloy steel- Quenched and Tempered
○ 高强度合金钢锻造而成，经过热处理
- ◆ Individually proof test at 2.5 times Working Load Limit
○ 每件按工作能力的2.5倍进行验证测试
- ◆ Fatigue tested at 1.5 times Working Load Limit for 20000 cycles
○ 钩体进行20000次疲劳测试
- ◆ Breakage test ○ 对每一批次产品进行严格的破坏性测试
- ◆ 100% magnifying crack detection ○ 100% 进行磁粉探伤
- ◆ Can be Rotated under Full-load Conditions
○ 非满载条件下可旋转90度角



SLR616-G80 CLEVIS SWIVEL HOOK 80级无羊角旋转钩

SLR616

Suitable for EN818-2 G80 chain 6mm 配合G80链条6mm

ITEM NO.	WEIGHT (kg)	WLL (T)	B.L (T)	A±1	B±1	C±1	M±1	E±1	L±2
B-SLR616-6	0.53	1.12	4.15	30	35	51.5	35	25	102

Lifts to load is 4 times the Working Load Limit 钩体能力为工作能力的4倍


- ◆ Popular mark (常用标识) : 6-R VLLS-127 GE SLR + BATCH NUMBER (批号)



WARNING 警告 This product is not to be used for lifting personnel.

G80 CLEVIS GRAB HOOK 80级 羊角翅钩

- ◆ Forged super alloy steel- Quenched and Tempered
- ◇ 高强度合金钢锻造- 淬火及回火处理
- ◆ Suitable for EN818-2 G80 chain
- ◇ 与EN818-2 80级40号钢索配合使用
- ◆ Individually proof test at 2.5 times Working Load Limit
- ◇ 每件在工作拉力2.5倍进行验证测试
- ◆ Fatigue tested at 1.5 times Working Load Limit for 20000 cycles
- ◇ 抽样进行20000次疲劳测试
- ◆ Breakage test 100% for all products in production
- ◇ 100% 破坏性测试
- ◆ 100% magnetic crack detection
- ◇ 100% 进行磁粉探伤



SLR086-G80 CLEVIS GRAB HOOK 80级羊角翅钩

SLR086


ITEM NO.	WEIGHT (kg)	WLL (T)	B.L (T)	E±1	A±0.5	H±1	W±1	L±2
SLR086-6	0.25	1.12	4.48	8	8	12.7	21.8	77.8
SLR086-7/8	0.42	2	8	10.5	9.5	19.6	33.5	99
SLR086-10	0.75	3.15	12.6	13	12.5	20	48	129
SLR086-13	1.5	6.3	25.2	15.5	16	42.7	67.8	165.6
SLR086-16	2.5	8	32	18	18.5	49.6	74	185.9
SLR086-20	5	12.5	50	24	22	50	93	210
SLR086-22	6.5	15	60	27	27	60.5	101	254
SLR086-26	14.5	31.5	126	30	30	77	152	384

Ultimate load is 4 times the Working Load Limit 破断力是工作拉力的4倍
Allow Working Load Limit is based on safe pull 查表所列工作拉力是在安全拉力下的工作拉力

- ◆ Rough scale (粗糙刻度): 10-2 WLL & 15T (G 1/2) + BATHY (BAUMER) (型号)

- ◆ All load pins are 100% individually inspected and tested
- ◇ 所有销轴进行100%测试, 确保相同的强度位置
- ◆ Surface finish (表面处理): Powder painted (粉末)
- ◆ Colour code (颜色): Red (红色) RAL 3005

Yellow (黄色) RAL 3005.



SLR313-G80 CLEVIS GRAB HOOK WITH SAFETY PIN 80级带防脱手型翅钩

SLR313

With safety pin 配安全销, 安全防脱

ITEM NO.	WEIGHT (kg)	WLL (T)	B.L (T)	A±0.5	B±1.2	E±0.5	M±2	L±2
SLR313-6	0.25	1.12	4.48	8	32	8	45.5	75
SLR313-7/8	0.42	2	8	10.5	35	11	53	89
SLR313-10	0.75	3.15	12.6	13.5	40.5	14	72	120.5
SLR313-13	1.55	6.3	25.2	16	53	14.5	90	163.5
SLR313-16	2.4	8	32	18.5	60.5	16	112.5	182.5

Ultimate load is 4 times the Working Load Limit 破断力是工作拉力的4倍
Allow Working Load Limit is based on safe pull 查表所列工作拉力是在安全拉力下的工作拉力

- ◆ Rough scale (粗糙刻度): 10-2 WLL & 15T (G 1/2) + BATHY (BAUMER) (型号)



CLEVIS SHORTENING HOOK 羊角短钩

- ◆ Forged super alloy steel- Quenched and Tempered
- ◆ 高强度合金钢材料经淬火及回火处理
- ◆ Suitable for E1619-2 (ISO chain) & E1619-2650 (EN13450 chain)
- ◆ Individually proof test of 2.5 times Working Load Limit
- ◆ 逐件按工作拉力进行验证测试
- ◆ Fatigue tested at 1.5 times Working Load Limit for 20000 cycles
- ◆ 疲劳进行20000次验证测试
- ◆ Breakage test 对每一批次产品进行严格的破坏性测试
- ◆ 100% magnetic crack detection 100% 进行磁粉探伤
- ◆ Surface finish (表面处理): Powder coated (粉漆)
- ◆ Colour code (色号): Red (红色) RAL3020, Yellow (黄色) RAL1025



SLR064-CLEVIS SHORTENING HOOK
羊角短钩

SLR064

ITEM NO.	WEIGHT (KG)	WLL (T)	B.L (T)	A±2	B±2	E±2	M±3	L±3	Ø±3	N±3
8-SLR-64-05	0.25	1.12	4.48	6	32	3	44	75	7.6	21.7
8-SLR-64-7	0.32	2	8	10	39	11	56	103	11.6	30
8-SLR-64-10	0.73	3.15	12.6	13	46	14	74	127	15	44.5
8-SLR-64-13	1.29	5.1	21.2	17	70	18	84	164	18.4	67.5
8-SLR-64-16	2.50	8	32	21.5	73.5	21	119	184	21.3	84
8-SLR-64-20	4.19	12.5	50	24	77	24	129.5	212	24.3	85
8-SLR-64-22	6.5	16	64	27	83	27	143	247	26.2	97.5

Ultimate load is 4 times the Working Load Limit 最终拉力是工作拉力的4倍
Allow Working Load Limit is based on safe pull 安全使用的工作拉力是在最终拉力下的工作拉力

- ◆ Page code (页码): 14 (30) SLR + BATCH NUMBER (批号)

- ◆ All test pins are 100% individually inspected and tested
- ◆ 所有销轴进行100%测试，确保相同的强度品质
- ◆ Surface finish (表面处理): Powder coated (粉漆)
- ◆ Colour code (色号): Red (红色) RAL3020, Yellow (黄色) RAL1025



SLR142-680 DEEP THROAT CLEVIS GRAB HOOK
80级深喉羊角抓钩

SLR142

ITEM NO.	WEIGHT (KG)	WLL (T)	B.L (T)	A±2	B±2	E±2	M±3	L±3
8-SLR-142-06	0.2	1.12	4.48	7.5	21.5	6	45	85
8-SLR-142-7/8	0.5	2	8	9.5	27.5	10.5	57	106
8-SLR-142-10	0.75	3.15	12.6	12.5	47.5	13	74	127
8-SLR-142-13	1.0	5.1	21.2	15	49.5	16.5	90	165.5

Ultimate load is 4 times the Working Load Limit 最终拉力是工作拉力的4倍
Allow Working Load Limit is based on safe pull 安全使用的工作拉力是在最终拉力下的工作拉力

- ◆ Page code (页码): 10 (3) WLL, 15 (2) CE, SLR + BATCH NUMBER (批号)




WARNING 警告 This is a lifting device and can be dangerous if not used correctly. 此设备为起重设备，如不正确使用可能会造成危险。

CLEVIS SHORTENING HOOK

羊角短钩

- Forged super alloy steel- Quenched and Tempered
- ◇ 高强度耐热合金钢锻造而成，经过热处理
- Individually proof test at 2.5 times Working Load Limit
- ◇ 零件按工作压力的2.5倍进行验证测试
- Fatigue tested at 1.5 times Working Load Limit for 20000 cycles
- ◇ 材料进行20000次疲劳测试
- Breakage test
- ◇ 对每一批产品进行严格的破坏性测试
- 100% magnaflex crack detection
- ◇ 100% 磁粉裂纹探伤



SLR871-CLEVIS ANGLE REGULATOR HOOK
羊角调节钩


SLR871

ITEM NO.	WEIGHTING	WLLT	BLT	A±1	B±1	C±1	D±1	E±1	F±1	M±2	L±3	K±2
8-8	0.35	1.12	4.43	8	25.5	17	25	8	10	33	115.5	53
8-8	0.67	3	9	9.5	37	22	29	10.5	11	33.5	112	55.5
10-8	1.34	6.15	12.8	12	46	26	36.5	12.4	15	51	125.5	90
13-8	2.5	9.3	21.2	15	61	35	49	15.5	21	62.5	136.5	105
16-8	4.20	9	32	15.5	74	44	64	18	27	100	200	133
20-8	8.25	12.5	60	19	102	58	85.3	24	37	110	243	155.7

SPECIAL TYPE CROOK HOOK WITH SAFETY PIN

带保险销异型羊角抓钩

- Forged super alloy steel- Quenched and Tempered
- ◇ 高强度耐热合金钢锻造而成，经过热处理
- Individually proof test at 2.5 times Working Load Limit
- ◇ 零件按工作压力的2.5倍进行验证测试
- Fatigue tested at 1.5 times Working Load Limit for 20000 cycles
- ◇ 材料进行20000次疲劳测试
- Breakage test
- ◇ 对每一批产品进行严格的破坏性测试
- 100% magnaflex crack detection
- ◇ 100% 磁粉裂纹探伤



SLR712-SPECIAL TYPE CROOK HOOK WITH SAFETY PIN
带保险销异型羊角抓钩

SLR712

ITEM NO.	WEIGHT (KG)	WLL (T)	BL (T)	A±2	B±2	E±2	M±3	N±3	L±3
8-SLR-712-8	7.3	3	8	8	43	5.5	61	32	107
8-SLR-712-10	8	3.15	12.8	12	49	12	75	40	121
8-SLR-712-13	2.7	5.3	21.12	14.5	65	15	90.3	52	180
8-SLR-712-16	3.7	8	32	17.3	76	18	121	61	194

Ultimate Load is 4 times the Working Load Limit 破断力为工作压力4倍

Above Working Load Limit is based on single point load 所有工作压力点都是在单点情况下工作压力

- Regular note (定期测试) : 100% WLLT TTT C/C SLR-8 BATCH NUMBER (批号)



SPECIAL TYPE CROOK HOOK WITH SAFETY PIN 带档销异型羊角抓钩

- ◆ Forged super alloy steel- Quenched and Tempered
◇ 高强度异型特种合金钢锻造而成，经过热处理
- ◆ Suitable for EN1678-2 G80 chain B 与E级10-12分米吨链配合使用
- ◇ Individually proof test at 2.5 times Working Load Limit
- ◇ 逐件按工作拉力2.5倍进行验证测试
- ◆ Fatigue tested at 1.5 times Working Load Limit for 20000 cycles
◇ 抽样进行20000次疲劳测试
- ◆ Breakage test 对每一件次产品进行严格的抽样破坏测试
- ◆ 100% magnetic crack detection 100% 进行探伤检查
- ◆ Surface finish (表面处理) : Powder coated (喷漆)
- ◆ Colour code (颜色) : Red (红色)RAL 3020 / black (黑色)RAL 9005



SLR549-SPECIAL TYPE CROOK HOOK WITH SAFETY PIN

带档销异型羊角抓钩

SLR549

ITEM NO.	WEIGHT (KG)	WLL (T)	B.L (T)	Ø±2	E±2	D±2	R±3	M±3	L±3
8-SLR-549-7/8	11.43	2	5	16	11.5	40	68	51	104
8-SLR-549-10	13	3.35	12.5	20	13	52	62	75.5	115.5
8-SLR-549-13	1.62	5.5	21.2	25	15	64	105.5	92.5	164.5

Ullrichs test is 4 times the Working Load Limit 静载拉力是工作拉力的4倍
Above Working Load Limit is tested on side pin 表侧销上工作拉力是额定位置以下的工作能力

★ Regular make (定期制造) : 10-16 VLL 5.157 CE SLR 4 BATCH NUMBER (批号)

G80 DEEP THROAT EYE GRAB HOOK 80级深喉眼型抓钩

- ◆ Forged super alloy steel- Quenched and Tempered
◇ 高强度异型特种合金钢锻造而成，经过热处理
- ◆ Individually proof test at 2.5 times Working Load Limit
- ◇ 逐件按工作拉力2.5倍进行验证测试
- ◆ Fatigue tested at 1.5 times Working Load Limit for 20000 cycles
◇ 抽样进行20000次疲劳测试
- ◆ Breakage test 对每一件次产品进行严格的抽样破坏测试
- ◆ 100% magnetic crack detection 100% 进行探伤检查



SLR141-G80 DEEP THROAT EYE GRAB HOOK

80级深喉眼型抓钩

SLR141

ITEM CODE	WEIGHT (Kg)	WLL (T)	BF (T)	D±1	E±0.3	B±1.2	R±1.5	L±1.5
8-SLR141-6	0.16	1.32	4.42	15	7	45	46	55
8-SLR141-7/8	0.35	2	6	18	5.5	62	74.9	104.5
8-SLR141-10	0.75	3.35	12.5	25	11	81	84.5	124.5
8-SLR141-13	1.5	5.5	21.2	35	13.5	95	134	170

Ullrichs test is 4 times the Working Load Limit 静载拉力是工作拉力的4倍
Above Working Load Limit is tested on side pin 表侧销上工作拉力是额定位置以下的工作能力

★ Regular make (定期制造) : 10-16 VLL 5.157 CE SLR 4 BATCH NUMBER (批号)



WARNING 警告 This is a lifting device and can be dangerous if not used properly.

G80 EYE GRAB HOOK 80级 眼型翅钩 (调节链条)

- ◆ Forged super alloy steel- Quenched and Tempered
- ◇ 高强度合金材料经合金钢热处理, 经过热处理
- ◆ Suitable for EN818-2 G80 chain & EN1219-2 G80 chain使用
- ◆ Individually proof test at 2.5 times Working Load Limit
- ◇ 每件按工作拉力2.5倍进行验证测试
- ◆ Fatigue tested at 1.5 times Working Load Limit for 20000 cycles
- ◇ 材料进行20000次疲劳测试
- ◆ Breakage test 对每一款产品进行严格的破坏性测试
- ◆ 100% magnaflex crack detection 100% 进行磁粉探伤
- ◆ Surface finish (表面处理): Powder painted (喷漆)
- ◆ Colour code (颜色): Red (红色)RAL2009 Yellow (黄色)RAL1020



SLR085-G80 EYE SHORTENING GRAB HOOK 80级眼型翅钩

SLR085

ITEM CODE	WEIGHT (kg)	WLL (T)	BF (T)	E±0.5	Φ±1	H±1	R±2	L±2	M±2
8-SLR085-0	0.14	1.02	4.45	3	13.5	17.0	51.4	75.3	45.5
8-SLR085-7B	0.240	2	8	10.8	18	20	61.5	91.2	53
8-SLR085-10	0.66	3.10	12.8	15	20	20	50	122	71
8-SLR085-13	1.60	5.5	21.2	18.5	20	42.8	90.7	166	90
8-SLR085-16	2.2	8	32	20	20.5	47.7	104	192	115
8-SLR085-20	4.0	12.9	50	25	37.5	55	140	210	143
8-SLR085-22	6.3	19	70	30	44	58	155	232	160
8-SLR085-26	9.4	24.2	84.5	30	44	77	181.5	254	171
8-SLR085-32	15.4	31.5	120	38	57	55	228	381	220

Ultimate test is 4 times the Working Load Limit 破断拉力是工作拉力的4倍

Above Working Load Limit is based on static pull 破断拉力是静态情况下工作拉力

- ◆ Regular mark (规格标记): 10-3 WLLS 15T 20T SLR 16T 20T 22T 26T 32T (规格)

- ◆ Forged super alloy steel- Quenched and Tempered
- ◇ 高强度合金材料经合金钢热处理, 经过热处理
- ◆ Individually proof test at 2.5 times Working Load Limit
- ◇ 零件按工作拉力2.5倍进行验证测试
- ◆ Fatigue tested at 1.5 times Working Load Limit for 20000 cycles
- ◇ 材料进行20000次疲劳测试
- ◆ Breakage test 对每一款产品进行严格的破坏性测试
- ◆ 100% magnaflex crack detection 100% 进行磁粉探伤



SLR317-G80 EYE SHORTENING GRAB HOOK WITH SAFETY PIN G80 安全销眼型翅钩带销翅钩

SLR317

With safety pin 配备安全销, 安全钩

ITEM NO.	WEIGHT (kg)	WLL (T)	B.L (T)	A	B	D	E	L	Φ
8-SLR317-7B	0.25	2	8	80±2	40±1	5.5±1	10±1	33.5±1.2	17±1
8-SLR317-10	0.75	3.10	12.8	90±2	45±1	6±1	11±1.5	42.8±2	20±1
8-SLR317-13	1.62	5.5	21.2	100±3	57.5±2	11.5±2	12.5±1.2	55±3	25±1.5
8-SLR317-16	3.2	10	40	110±4	70±3	16±2	15.5±1.2	63±4	36±2

Ultimate test is 4 times the Working Load Limit 破断拉力是工作拉力的4倍

Above Working Load Limit is based on static pull 破断拉力是静态情况下工作拉力

- ◆ Regular mark (规格标记): 10-3 WLLS 15T 20T SLR 16T 20T 22T 26T 32T (规格)

NOTICE: Please read the instruction carefully before use.

WARNING 警告



G80 EYE GRAB HOOK 80级 眼型钩

- ◆ Forged super alloy steel- Quenched and Tempered
- ◇ 高强度合金在特殊合金炉锻造而成，经过热处理
- ◆ Individually proof test at 2.5 times Working Load Limit
- ◇ 每件在工作压力的2.5倍进行验证测试
- ◆ Fatigue tested at 1.5 times Working Load Limit for 20000 cycles
- ◇ 每件进行20000次疲劳测试
- ◆ Breakage test 对每一件产品进行严格的破坏性测试
- ◆ 100% magnetic crack detection 100% 进行磁粉探伤
- ◆ Surface finish (表面处理): Powder coated (喷涂)
- ◆ Color code (色号): Red (红色) RAL3020
- Yellow (黄色) RAL1015



SLR065-G80 ITALIAN TYPE EYE SHORTENING GRAB HOOK G80 意式短型钩

SLR065

ITEM CODE	WEIGHT (kg)	WLL (T)	BF (T)	Φ±1	B±1.5	E±0.5	L±2
B-SLR065-06	0.18	1.12	4.45	12.5	44	2	75.5
B-SLR065-07	0.367	2	9	16	48.5	3	92
B-SLR065-10	0.55	3.15	12.5	20	72	13	125
B-SLR065-13	1.34	5.1	21.2	25	81	17	150
B-SLR065-16	2.00	8	32	30	110	21	180
B-SLR065-20	3.64	12.5	50	35	132.5	25	211

Life span is based on Working Load Limit 使用寿命基于工作压力为 4 倍

Above Working Load Limit is based on safe 8 times of the working load in the static condition 以上工作压力是基于静态条件下安全 8 倍的工作压力

- ◆ Regular mark (常规标记) 10-4 WLL% TEST OR BATCH NUMBER (批号)

- ◆ Forged super alloy steel- Quenched and Tempered
- ◇ 高强度合金在特殊合金炉锻造而成，经过热处理
- ◆ Individually proof test at 2.5 times Working Load Limit
- ◇ 每件在工作压力的2.5倍进行验证测试
- ◆ Fatigue tested at 1.5 times Working Load Limit for 20000 cycles
- ◇ 每件进行20000次疲劳测试
- ◆ Breakage test
- ◇ 对每一件产品进行严格的破坏性测试
- ◆ 100% magnetic crack detection
- ◇ 100% 进行磁粉探伤



SLR768-G80 EYE SHORTENING GRAB HOOK 80 级眼型短钩

SLR768

ITEM NO.	WEIGHT/kg	WLL/T	B/L/T	E±1	Φ±1	D±1.5	M±2	L±3
08-SLR768-06	0.16	1.12	4.45	9	12.5	30.5	43.5	75
08-SLR768-08	0.3	2	9	11	17.5	37	53	92.7
08-SLR768-10	0.71	3.15	12.5	13.5	22	48.5	73	120
08-SLR768-13	1.47	5.1	21.2	17	27	58	96	162
08-SLR768-16	2.74	8	32	19	35	75	115	180
08-SLR768-20	4.72	12.5	50	24	43.5	88.5	143	227
08-SLR768-22	5.2	15	60	27	48.5	102.5	161.5	250.5



WARNING 警告: This equipment is not to be used for lifting personnel.

G80 CLEVIS GRAB HOOK 80级 羊角抓钩

- ◆ Forged super alloy steel- Quenched and Tempered
- ◇ 高强度易拉钩钩体合金钢锻造而成，经过热处理
- ◆ Suitable for EN818-2 G80 chain
- ◇ 与EN818-2标准40级链条配合使用
- ◆ Individually proof test at 2.5 times Working Load Limit
- ◇ 每件抓钩工作拉力均经2.5倍进行验证测试
- ◆ Fatigue tested at 1.5 times Working Load Limit for 20000 cycles
- ◇ 抽样进行20000次疲劳测试
- ◆ Breakage test 对每一批次产品进行严格的破坏性测试
- ◆ 100% magnetic crack detection ◇ 100% 进行磁粉探伤



SLR028-CLEVIS GRAB HOOK 羊角抓钩

SLR028


ITEM NO.	WEIGHT (KG)	WLL (T)	B.L (T)	A±2	B±2	E±2	H±3	K±3	L±3
8-SLR-28-1/4	0.22	1.2	4.8	8	34	8	19.8	67	10.5
8-SLR-28-1/2	0.51	3	8	14.5	41	9.5	23	146.5	106.5
8-SLR-28-3/8	0.7	3.2	12.8	12.7	46	12.6	31	82	137
8-SLR-28-1/2	1.6	5.4	21.8	15	81	15.7	49	115	184.5
8-SLR-28-5/8	3.1	8.2	32.8	19.5	115.5	20	40	129.5	215
8-SLR-28-3/4	4.1	11.8	51.2	24	138	24	55	157	259
8-SLR-28-7/8	6.2	15.1	62	27	151	29	64.2	178	296

Ullimate load is 4 times the Working Load Limit 破断力是工作拉力的4倍

Above Working Load Limit is based on safety factor 表格所列工作拉力是在安全系数下测试的工作拉力

- ◆ Register name (请登记) : TIT-028 SLR-8 BATCH NUMBER (批号)

- ◆ Forged super alloy steel- Quenched and Tempered
- ◇ 高强度易拉钩钩体合金钢锻造而成，经过热处理
- ◆ Individually proof test at 2.5 times Working Load Limit
- ◇ 每件抓钩工作拉力均经2.5倍进行验证测试
- ◆ Fatigue tested at 1.5 times Working Load Limit for 20000 cycles
- ◇ 抽样进行20000次疲劳测试
- ◆ Breakage test ◇ 对每一批次产品进行严格的破坏性测试
- ◆ 100% magnetic crack detection ◇ 100% 进行磁粉探伤



SLR686-CLEVIS GRAB HOOK 羊角抓钩

SLR686

ITEM NO.	WEIGHT (KG)	WLL (T)	B.L (T)	A±2	B±2	C±2	D±2	E±3	F±3	H±3	L±3
8-SLR-686-3/8	0.6	3.15	12.0	44	12.8	27.0	71	12	20	24	164.0

Ullimate load is 4 times the Working Load Limit 破断力是工作拉力的4倍


Above Working Load Limit is based on safety factor 表格所列工作拉力是在安全系数下测试的工作拉力

- ◆ Register name (请登记) : TIT-028 SLR-686 BATCH NUMBER (批号)



G80 U.S TYPE EYE GRAB HOOK 80级 美标眼型抓钩

- ◆ Forged super alloy steel- Quenched and Tempered
○ 高强度合金特殊合金钢锻造而成，经过热处理
- ◆ Suitable for EN1218-2 G80 chain & with EN1218-2行事链配合使用
- ◆ Individually proof test at 2.5 times Working Load Limit
- ◆ 每件抓钩工作拉力为U.S标准行验证测试
- ◆ Fatigue tested at 1.5 times Working Load Limit for 20000 cycles
- ◆ 每件进行20000次疲劳测试
- ◆ Breakage test 对每一件次产品进行严格的破坏测试
- ◆ 100% magnetic crack detection 100% 进行探伤检测
- ◆ Surface finish (表面处理) : Powder coated (喷漆)
- ◆ Colour code (颜色) : Red (红色)RAL3020 (黄色)RAL1003



SLR027-G80 U.S TYPE EYE GRAB HOOK
80级美标眼型抓钩

SLR027

ITEM CODE	WEIGHT (kg)	WLL (T)	BF (T)	E±0.5	D±1	H±1	K±2	L±2
8-SLR027-1/4	0.13	1.0	4.8	2	13	19	54	81
8-SLR027-3/32	0.27	2	9	2.5	16	23	64	95
8-SLR027-3/8	0.65	5.0	19.3	12.5	30	38	82	120
8-SLR027-1/2	1.5	8.4	21.6	17	35	42	100	140
8-SLR027-5/8	2.45	8.7	32.0	30	40	49	127	180
8-SLR027-3/4	3.0	12.8	51.2	35	50.5	60	152	210
8-SLR027-7/8	5.8	15.8	62	32.0	40.5	65.5	175	250

U.S limit load is 4 times the Working Load Limit 美国标准工作拉力的4倍

Above Working Load Limit is based on single point load 上述工作拉力是在单点负载下工作拉力

- ◆ Regular mark (常规标记) : 1R (红色) SLR + BAYTIN (黄色)

- ◆ Forged super alloy steel- Quenched and Tempered
○ 高强度合金特殊合金钢锻造而成，经过热处理
- ◆ Individually proof test at 2.5 times Working Load Limit
- ◆ 每件抓钩工作拉力为U.S标准行验证测试
- ◆ Fatigue tested at 1.5 times Working Load Limit for 20000 cycles
- ◆ 每件进行20000次疲劳测试
- ◆ Breakage test 对每一件次产品进行严格的破坏测试
- ◆ 100% magnetic crack detection 100% 进行探伤检测
- ◆ Surface finish (表面处理) : Powder coated (喷漆)
- ◆ Colour code (颜色) : Red (红色)RAL3020
Yellow (黄色)RAL1003



SLR217-EYE TYPE BELT WING HOOK
眼型带翅抓钩

SLR217

ITEM NO.	WEIGHT (kg)	WLL (T)	BL (T)	Ø±2	E±2	M±2	H±3	R±3	L±3
8-SLR-217-7/8	11.29	2	8	17	51.5	60	21.5	64.5	98

U.S limit load is 4 times the Working Load Limit 美国标准工作拉力的4倍

Above Working Load Limit is based on single point load 上述工作拉力是在单点负载下工作拉力

- ◆ Regular mark (常规标记) : 1R (红色) SLR217 (黄色)



WARNING 警告 This product is not to be used for lifting personnel.

CLEVIS GRAB HOOK

羊角抓钩

- ◆ Forged alloy steel-Quenched and tempered
- ◆ 优质合金钢锻造，经过热处理。
- ◆ Only for lashing and pulling. Not for lifting.
- ◆ 仅用于捆绑和拖拉，不能用于起重。
- ◆ Regular mark(常规标记)：WLL2T



SLR063 - SPECIAL-SHAPED EYE TYPE HOOK


异型眼型抓钩

SLR063

ITEM NO.	WEIGHT (Kg)	WLL (T)	B.L (T)	B±1	D±1	E±0.5	H±1	L±2	Φ±0.5
SLR-063-1.88T	0.4	1.85	7.44	57	13	10	16.5	100	8
SLR-063-2T	0.5	2	8	52	12	10	20	105	9
SLR-063-5T	1.7	5	20	62	20	16	30	170	15

Ultimate load is 4 times the Working Load Limit. 极限拉力是工作拉力的4倍。
Regular mark：(常规标记)：5/7WLL2T

- ◆ Forged alloy steel-Quenched and tempered
- ◆ 优质合金钢锻造，经过热处理。
- ◆ Only for lashing and pulling. Not for lifting.
- ◆ 仅用于捆绑和拖拉，不能用于起重。
- ◆ Regular mark(常规标记)：WLL2T



SLR025 - SPECIAL-SHAPED EYE TYPE HOOK

异型眼型抓钩

SLR025


ITEM NO.	WEIGHT (kg)	WLL (T)	B.L (T)	B±2	Φ±2	K±2	L±3
S-SLR-25-2T	0.7	2	8	14.5	20	105	1440

Ultimate load is 4 times the Working Load Limit. 极限拉力是工作拉力的4倍。



CONTAINER LIFTING CLEVIS LINK 集装箱索具配件

- ◆ Forged super alloy steel- Quenched and Tempered
- ◇ 高强度合金钢经淬火和回火处理
- ◆ Individually proof test at 2.5 times Working Load Limit
- ◇ 每件独立工作力为2.5倍运行额定测试
- ◆ Fatigue tested at 1.5 times Working Load Limit for 20000 cycles
- ◇ 疲劳运行20000次疲劳测试
- ◆ Breakage test
- ◇ 对每一件次产品进行严格的破坏性测试
- ◆ 100% magnifier crack detection
- ◇ 100% 进行磁粉探伤
- ◆ All load pins are 100% individually inspected and tested
- ◇ 所有销轴进行100%测试，确保销轴无质量缺陷
- ◆ Surface finish (表面处理) : Powder painted (喷漆)



SLR645-G80 CONTAINER LIFTING CLEVIS LINK 80级集装箱索具配件

SLR645

Available in G100 此产品也可供应100级!

ITEM NO.	WEIGHT (kg)	WLL (T) G80	B.L (T) G80	WLL (T) G100	B.L (T) G100	A+0.5	B+1	C+0.3	D+0.3	E+1	F+0.5	M+0.3	N+1	Q+0.1	L+1.5
SLR-645-12	1.29	6.5	21.0	6.7	20.8	21	86	60	21.5	98	10	35	62	17.2	170

HOOK WITH HALF LINK 单环滑钩

- ◆ Forged super alloy steel- Quenched and Tempered
- ◇ 高强度合金钢经淬火和回火处理
- ◆ Individually proof test at 2.5 times Working Load Limit
- ◇ 每件独立工作力为2.5倍运行额定测试
- ◆ Fatigue tested at 1.5 times Working Load Limit for 20000 cycles
- ◇ 疲劳运行20000次疲劳测试
- ◆ Breakage test
- ◇ 对每一件次产品进行严格的破坏性测试
- ◆ 100% magnifier crack detection
- ◇ 100% 进行磁粉探伤



SLR006-HOOK WITH HALF LINK 单环滑钩

SLR006


ITEM NO.	WEIGHT (kg)	WLL (T)	B.L (T)	E+2	B+1	Q+1.5	K+3	L+3
8-SLR006-6	0.35	1.12	4.40	22	15	31	115	132
8-SLR006-7.5	0.47	2	8	28	18	37	120	140
8-SLR006-10	1.3	3.15	12.4	28.8	26	47	153	217
8-SLR006-13	2	4.3	21.2	40	39	60	206	257
8-SLR006-16	4.4	6	30	44	36	75	224	293.4
8-SLR006-20	7.3	10.5	50	54.5	41.5	88	264	357.5
8-SLR006-22	12	13	59	71	57	100	325.5	414.0

- ◆ Ultra safe in line 4 times the Working Load Limit 超安全4倍工作力工作
- ◆ Regular mark (铭牌) : 70% B.W. 22T (13.5 SLR)



FORGED GRAB HOOK 锻造抓钩

- ◆ Forged alloy steel
- ◇ 锻造合金钢
- ◆ Quenched and Tempered
- ◇ 经过淬硬和回火处理
- ◆ Not for lifting, only for lashing or pulling
- ◇ 不能用于起重，仅用于捆绑和拖拉
- ◆ Can be Rotated under Full-load Condition!
- ◇ 在满载条件下可旋转90度方向！



SLR728-ALLOY GRAB HOOK FOR WEBBING
合金钢系带抓钩

SLR728


ITEM NO.	WEIGHT (kg)	LC (T)	B.L (T)	A×1	E×1	G×1	H×1	M×1	N×1	L×3
886	0.55	3.6	7.0	90	12	30	34	14.5	18	177

Ultimate load is 2 times the Working Load Limit. 破断拉力为工作拉力的2倍

- ◆ Register mark (注册标记): www.will.com

G80 SWIVEL HOOKS 80级 旋转钩

- ◆ Forged superior alloy steel- Quenched and Tempered
- ◇ 高强度合金钢铸造成型经回火处理
- ◆ Individually proof test at 2.5 times Working Load Limit
- ◇ 每件在工作拉力的2.5倍进行验证测试
- ◆ Fatigue tested at 1.5 times Working Load Limit for 200,000 cycles
- ◇ 疲劳进行30000次疲劳测试
- ◆ Breakage test at 100% for each product to ensure the safety of the product
- ◇ 100% 破断测试，确保每件产品的安全
- ◆ Can be Rotated under Full-load Condition!
- ◇ 在满载条件下可旋转90度方向！



SLR787-SWIVEL BELT SLING HOOK
旋转吊带钩

SLR787


ITEM NO.	WEIGHT (kg)	A×1	B×1.5	E×1	N×1	H×1	L×2
117	0.15	20	60	30.5	17	13.2	135



WARNING 警告: This product is not to be used for lifting personnel.

G80 CLEVIS WEBBING SLING HOOK 80级 羊角拉索带钩

- ◆ Forged super alloy steel- Quenched and Tempered
- ◇ 高强度合金材料经合金钢热处理而成，经过热处理
- ◆ Individually proof test at 2.5 times Working Load Limit
- ◇ 每件按工作压力的2.5倍进行验证测试
- ◆ Fatigue tested at 1.5 times Working Load Limit for 20000 cycles
- ◇ 钩体进行20000次疲劳测试
- ◆ Breakage test
- ◇ 对每一批产品进行严格的破坏性测试
- ◆ 100% magnet flux crack detection
- ◇ 100% 进行磁粉探伤



SLR016-G80 CLEVIS WEBBING SLING HOOK
80级羊角拉索带钩

SLR016

ITEM NO.	WEIGHT (KG)	WLL (T)	B.L (T)	A±1	B±2	E±1	L±2
SLR16-2.2T	1.47	2.2	8.8	51	119	47	167

Ultimate load is 4 times the Working Load Limit 破断力是工作压力的4倍

G80 WEBBING SLING HOOK 80级 眼型吊带钩

- ◆ Forged super alloy steel- Quenched and Tempered
- ◇ 高强度合金材料经合金钢热处理而成，经过热处理
- ◆ Individually proof test at 2.5 times Working Load Limit
- ◇ 每件按工作压力的2.5倍进行验证测试
- ◆ Fatigue tested at 1.5 times Working Load Limit for 20000 cycles
- ◇ 钩体进行20000次疲劳测试
- ◆ Breakage test
- ◇ 对每一批产品进行严格的破坏性测试
- ◆ 100% magnet flux crack detection
- ◇ 100% 进行磁粉探伤



SLR017-G80 WEBBING SLING HOOK
80级眼型吊带钩

SLR017

ITEM NO.	WEIGHT (KG)	WLL (T)	B.L (T)	A±1	B±2	E±1	L±2
SLR017-1.6T	1.2	1.6	6.4	45	111	30	150


Ultimate load is 4 times the Working Load Limit 破断力是工作压力的4倍

- ◆ Regular code (常规型号): WLL(T) (破断力) B.L (破断力) A (钩体长度) B (钩体宽度) C (钩体高度) D (钩体厚度) E (钩体孔径) F (钩体孔距)



G80 FOR WEB SLING 80级 吊带索具配件

- ◆ Forged super alloy steel- Quenched and Tempered
- ◇ 高强度合金钢锻造而成, 经过热处理
- ◆ Industrially proof test at 2.5 times Working Load Limit
- ◇ 零件在工作压力的2.5倍进行验证测试
- ◆ Fatigue tested at 1.5 times Working Load Limit for 20000 cycles
- ◇ 在1.5倍工作压力下进行2万次疲劳验证测试
- ◆ Breakage test
- ◇ 对每一批次产品进行严格的破坏性测试
- ◆ 100% magnetic crack detection
- ◇ 100% 进行磁力探伤



SLR090-G80 EYE WEBBING SLING HOOK
80级眼型吊带钩

SLR090

ITEM NO.	WEIGHT (kg)	WLL (T)	B.L (T)	A±1	W±1.6	M±2	N±1	B±2	E±1	L±2	L±0.5	K±2
8-SLR090-75mm	2.1	2.75	11	20	91.5	30	40	541	45	104	54.5	144.5

Ultimate limit is 4 times the Working Load Limit 极限破断力是工作压力的4倍

◆ Regular mark (常规标识): WLL, T, P, CE, SLR - BATCH NUMBER (批号)

- ◆ Forged super alloy steel- Quenched and Tempered
- ◇ 高强度合金钢锻造而成, 经过热处理
- ◆ Industrially proof test at 2.5 times Working Load Limit
- ◇ 零件在工作压力的2.5倍进行验证测试
- ◆ Fatigue tested at 1.5 times Working Load Limit for 20000 cycles
- ◇ 在1.5倍工作压力下进行2万次疲劳验证测试
- ◆ Breakage test
- ◇ 对每一批次产品进行严格的破坏性测试
- ◆ 100% magnetic crack detection
- ◇ 100% 进行磁力探伤



SLR632-G80 HOOK FOR WEB SLING
80级吊钩

SLR632

ITEM NO.	WEIGHT (kg)	WLL (T)	B.L (T)	A±2	B±2	D±1	E±1.5	L±2
8-SLR-632-1T	11.51	1	4	70	45	30	31	135

Ultimate limit is 4 times the Working Load Limit 极限破断力是工作压力的4倍

◆ Regular mark (常规标识): WLL, T, CE, SLR - BATCH NUMBER (批号)



WARNING 警告

Do not use for lifting people or loads exceeding the rated capacity.

G80 CLEVIS LINK FOR WEB SLING 80级 异型吊带环

- ◆ Forged super alloy steel- Quenched and Tempered
- ◇ 高强度合金钢经热处理锻造而成，经应力处理
- ◆ Individually proof test at 2.5 times Working Load Limit
- ◇ 逐件按工作拉力的2.5倍进行验证测试
- ◆ Fatigue tested at 1.5 times Working Load Limit for 20000 cycles
- ◇ 抽样进行20000次疲劳测试
- ◆ Breakage test
- ◇ 对每一批产品进行严格的抽样破坏测试
- ◆ 100% magnetic crack detection
- ◇ 100% 进行磁粉探伤



SLR235-G80 CLEVIS LINK FOR WEB SLING
80级异型吊带环

SLR235


ITEM NO.	WEIGHT (kg)	WLL (T)	B.L (T)	A±1	B±1	W±1	L±1
SLR235-10MM	0.22	0.15	12.5	12	41	11	71

与G80吊钩配合使用 Working Load Limit 破断拉力 工作拉力 4吨

◆ Tagline work (黄线吊钩) 11-15WLL 15T-15E SLR + 15T 10000000 (套)

FN TYPE WEBBING HOOK FN型双面挂带钩

- ◆ Forged super alloy steel- Quenched and Tempered
- ◇ 高强度合金钢经热处理锻造而成，经应力处理
- ◆ Individually proof test at 2.5 times Working Load Limit
- ◇ 逐件按工作拉力的2.5倍进行验证测试
- ◆ Fatigue tested at 1.5 times Working Load Limit for 20000 cycles
- ◇ 抽样进行20000次疲劳测试
- ◆ Breakage test
- ◇ 对每一批产品进行严格的抽样破坏测试
- ◆ 100% magnetic crack detection
- ◇ 100% 进行磁粉探伤



SLR852-FN TYPE WEBBING HOOK
FN型双面挂带钩


SLR852

ITEM NO.	WEIGHT (kg)	WLL (T)	A±1	B±1.5	D±1	E±1	F±1	H±1	N±0.5	L±2
1T	0.705	1	44	21	22	26.5	29	28.4	32	133.5
2T	3.73	2	73	137	25	30	80	34.5	15	191
3T	8.40	3	109	167	26	32.5	105	38	13	173
4T	4.39	4	146	218	35	41	126	41	21	215
5T	7.74	5	172	299	41	44	154	51	23	251



G80 SLIDING EYE CHOKE HOOK 80级滑眼钩

- ◆ Forged super alloy steel- Quenched and Tempered
- ◆ 高强度合金材料经金相配合处理，经过热处理
- ◆ Intentionally proof load at 2.5 times Working Load Limit
- ◆ 意外在工作能力为2.5倍额定工作负荷时断裂
- ◆ Fatigue tested at 1.5 times Working Load Limit for 20000 cycles
- ◆ 疲劳进行20000次疲劳测试
- ◆ Breakage test - 1/4吋每一批次必须经过严格的破坏测试
- ◆ 100% magnifying crack detection - 100% 进行裂纹检测



G80 SLIDING EYE CHOKE HOOK
80级滑眼钩

SLR072


ITEM NO.	WEIGHT (kg)	WLL (T)	BL (T)	Øx1	A±1.5	B±1.5	C±3	D±3.5
8-SLR072-3/8-1/2	0.66	1.5	8	17	56	71	19	102
8-SLR072-5/8	1.21	2	10	21	69.5	79	20	107.5
8-SLR072-3/4	1.59	3	15	27	83	108	25	170
8-SLR072-1	4.10	5	20	32.5	101.7	175	30	210

Ullrich load & 5 times the Working Load Limit 每英寸的工作能力为5倍

- ◆ Regular hook (常规钩) : 3/8-1/2 WLL 1.5T CE SLR + GATCHIN MASER (吨重)

G80 EYE ELEPHANT FOOT 80级眼型象脚

- ◆ Forged alloy steel
- ◆ 优质合金钢锻造而成
- ◆ Suitable for G80 lashing chain
- ◆ 与80级索链相配合
- ◆ Regular mark: 19-k WLL 5.1T CE SLR



G80 EYE ELEPHANT FOOT
80级眼型象脚

SLR088

ITEM NO.	WEIGHT (KG)	WLL/T	BL/T	Øx1	B±1	C±1	D±0.5	G±1	L±2
8-SLR088-13	0.37	5	22	29	61	30	16	10.5	116

Ullrich load at 4 times the Working Load Limit 每英寸的工作能力为4倍



WARNING 警告 This is a lifting device and must be used in accordance with the instructions.

FORGED HOOKS 锻造钩系列

- Forged super alloy steel- Quenched and Tempered
- 高强度耐热性合金钢锻造而成，经过淬火处理
- Individually proof test at 2.5 times Working Load Limit
- 每件钩工作拉力为2.5倍进行验证测试
- Fatigue tested at 1.5 times Working Load Limit for 20000 cycles
- 钩件进行1.5倍的工作拉力疲劳测试
- Breakage test
- 对每一件产品进行严格的钩件断裂测试
- 100% magnifying crack detection
- 100% 进行磁粉探伤



SLR111- G80 SHACKLE HOOK 80级扣和吊钩

SLR111

ITEM NO.	WEIGHT (kg)	WLL (T)	B.L (T)	A+1	B+2	D+0.6	E+0.5	L+2
8-SLR111-8.5T	0.46	8.5	94	70	145	90	49	271

Ultimate load is 4 times the Working Load Limit 极限拉力是工作拉力的4倍

- Regular mark (常规标记): VAL-8.5T, CE, SLR+WATCHNUMBER (铭牌)

- Forged super alloy steel- Quenched and Tempered
- 高强度耐热性合金钢锻造而成，经过淬火处理
- Individually proof test at 2.5 times Working Load Limit
- 每件钩工作拉力为2.5倍进行验证测试
- Fatigue tested at 1.5 times Working Load Limit for 20000 cycles
- 钩件进行1.5倍的工作拉力疲劳测试
- Breakage test
- 对每一件产品进行严格的钩件断裂测试
- 100% magnifying crack detection
- 100% 进行磁粉探伤



SLR282-LONG HANDLE SLAPPING TONGUE HOOK 长柄背舌钩

SLR282

ITEM NO.	WEIGHT (kg)	A	B	Ø	G	E	L
SLR-282-282	0.07	6.6	30	5.7	4.5	20.7	70.5

Ultimate load is 4 times the Working Load Limit 极限拉力是工作拉力的4倍

- Regular mark (常规标记): VAL-2.5T, CE, SLR+WATCHNUMBER (铭牌)



WARNING 警告 Please read the instructions carefully before use.

FORGED HOOKS 锻造钩系列

- ◆ Forged alloy steel—Quenched and tempered
○ 优质合金钢锻造，经过热处理。
- ◆ Regular mark (常规标记) : WLL 3T



SLR232 – EYE TWIST HOOK


合金钢扭型本钩可吊钩

SLR232

Only for lashing and pulling. Not for lifting. 仅用于捆绑和拖拉 不能用于起重

ITEM NO.	WEIGHT (kg)	WLL (T)	B.L. (T)	A±1	B±2	C±1.5	D±2.5	E±0.5
8-SLR232-BT	6.12	8	32	36	170	70.4	303	44.5

- ◆ Forged carbon steel—Quenched and tempered
○ 优质碳钢锻造，经过热处理
- ◆ Not for lifting. 不能用于起重
- ◆ Regular mark (常规标记) : WLL 1.5T



SLR280 – ROUND REVERSE EYE HOOK

圆型转颈钩

SLR280


Not for lifting. 不能用于起重

ITEM NO.	WEIGHT (kg)	WLL (T)	B.L. (T)	A±1	B±2	C±1	D±2	E±1
8-SLR280-0#	0.2	1.5	6	34	66	321	180	24
8-SLR280-7#	1.64	2	8	35	110	60	142	25



G80 TWIST EYE CHOKE HOOK 80级 眼型转脖钩

- ◆ Forged super alloy steel- Quenched and Tempered
- ◇ 高强度合金特种合金钢锻造而成, 经过热处理
- ◆ Individually proof test at 2.5 times Working Load Limit
- ◇ 每种在工作拉力2.5倍进行验证测试
- ◆ Fatigue tested at 1.5 times Working Load Limit for 20000 cycles
- ◇ 抽样进行20000次疲劳测试
- ◆ Breakage test
- ◇ 对每一批次产品进行严重的破坏性测试
- ◆ 100% magnified crack detection
- ◇ 100% 进行缺陷检测



SLR026- G80 TWIST EYE CHOKE HOOK
80级眼型转脖钩


SLR026

ITEM NO.	WEIGHT (kg)	WLL (T)	BL (T)	A±2.5	B±2	C±1.5	D±1	Ø1±2.5	Ø2±2.5	Ø3	E±1	L±2.5
8-SLR026-7/8	0.93	5	5	10	28	16.5	17	52	34.8	5.5	10	123
8-SLR026-10	0.72	3.2	12.5	26	40	12.5	19	88	30	8	31	167
8-SLR026-13	1.4	5.4	21.5	34	45	21	24	87	50	10	27	180.5
8-SLR026-16	3.17	8.7	32.3	51	45.5	31	30	106	84	12.5	30	244
8-SLR026-18	3.8	10	36	64.6	55	43.0	33.0	121	75	12	36.6	278.5
8-SLR026-20/22	5.95	15.8	61.2	70	60	44	52	148	54	14	47	387
8-SLR026-24	11.95	21.2	84.8	80	60	44	60	150	100	24.0	44	417

(Weight limit is 4 times the Working Load Limit 极限承载力是工作拉力的4倍)

- ◆ Regular mark (常规标记) : 10-KW1 3-151 10-SLR + BATCH NUMBER (批号)

- ◆ Forged super alloy steel- Quenched and Tempered
- ◇ 高强度合金特种合金钢锻造而成, 经过热处理
- ◆ Individually proof test at 2.5 times Working Load Limit
- ◇ 每种在工作拉力2.5倍进行验证测试
- ◆ Fatigue tested at 1.5 times Working Load Limit for 20000 cycles
- ◇ 抽样进行20000次疲劳测试
- ◆ Breakage test
- ◇ 对每一批次产品进行严重的破坏性测试
- ◆ 100% magnified crack detection
- ◇ 100% 进行缺陷检测



SLR018-G80 TWIST HOOK FOR WEB SLING
80级眼单扭扭钩

SLR018

ITEM NO.	WEIGHT (KG)	WLL (T)	BL (T)	A±1	B±1	D±2	E±1	G±1	L±2
8-SLR018	1.05	5	12	57	15	100	39	15	350

(Weight limit is 4 times the Working Load Limit 极限承载力是工作拉力的4倍)

- ◆ Regular mark (常规标记) : WLLT GC SLR + BATCH NUMBER (批号)



WARNING 警告 This product is not to be used for lifting personnel.

G80 LASHING TYPE HOOK 80级 薄型高强度板钩

- ◆ Suitable for G80 lashing system
- ◇ 适用于捆绑系统
- ◆ Forged alloy steel
- ◇ 优质合金钢板制成
- ◆ Fast and easy assembly
- ◇ 快速方便地安装
- ◆ Surface finish (表面处理):
- ◇ Powder paint (粉末)
- ◆ Colour code (色号):
- ◇ Red (红色) RAL3020 ◇ Yellow (黄色) RAL1003



SLR071-LASHING TYPE HOOK

薄型高强度板钩

SLR071

ITEM No.	WEIGHT (kg)	WLL (T)	B.L (T)	A	B	E	M	L
B-SLR071-9	11.1	2.5	10	22.5 ± 1	12 ± 0.5	13.5 ± 0.5	34.5 ± 2	143 ± 2
B-SLR071-11	6.6	3.75	10	22.5 ± 1	14 ± 0.5	15.0 ± 0.5	109.5 ± 2	177 ± 2
B-SLR071-13	1.4	5.4	21.6	31 ± 1	10 ± 1	18 ± 1	129 ± 1	207 ± 1

Ultimate load is 4 times the Working Load Limit 破断力是工作能力的4倍。
Regular mark (常规标记): 10MM WLL 2 RT CE

G80 LASHING COMPONENTS 80级 捆绑配件

- ◆ Forged alloy steel - Ground and tempered.
- ◇ 优质合金钢板，经过热处理。
- ◆ Ultimate load is 4 times the Working Load Limit.
- ◇ 破断力为工作能力的4倍。
- ◆ Working Load Limit at tip of the hook is 2T
- ◇ 钩尖处工作拉力为2T。
- ◆ Working Load Limit at bottom of hook is 5.8T
- ◇ 钩子底部的工作拉力为5.8T



SLR108 - FORGED SORTING HOOK

锻造分货钩

SLR108

ITEM NO.	WEIGHT (kg)	WLL (T)	WLL (T)	D	B	C	L	H
B-SLR108-2T	3.08	2	6.8	35	1.01	53	25.1	81

Regular mark (常规标记): WLL 2T



BLOCK HOOK 锻造葫芦钩

- ◆ Forged super alloy steel- Quenched and Tempered
- ◇ 高强度耐热合金钢锻造而成，经过热处理
- ◆ Breakage test
- ◇ 对每一批产品进行严格的破坏性测试
- ◆ 100% magnific crack detection
- ◇ 100% 进行裂纹检测
- ◆ All load pins are 100% individually inspected and tested
- ◇ 所有销轴进行 100% 测试，确保每个销轴品质
- ◆ Surface finish (表面处理) : Powder painted (喷漆)



SLR041- BLOCK HOOK 葫芦钩

SLR041

ITEM NO.	WEIGHT (kg)	WLL (T)	B.L (T)	Φ	Φ1±1	D	E±0.5	L±1.2	M±1
SLR-41-0.8T	0.45	0.5	4	21	16.5	14.5	45	112.5	83.5
SLR-41-1.8T	0.92	1.8	8	24	42	37.5	50	128	101

- 1/3rated load is the Working Load Limit 额定拉力是工作拉力的1/3
- ◆ Rough scale (粗糙刻度) : WLL 0.5T

- ◆ Forged super alloy steel- Quenched and Tempered
- ◇ 高强度耐热合金钢锻造而成，经过热处理
- ◆ Breakage test
- ◇ 对每一批产品进行严格的破坏性测试
- ◆ 100% magnific crack detection
- ◇ 100% 进行裂纹检测
- ◆ All load pins are 100% individually inspected and tested
- ◇ 所有销轴进行 100% 测试，确保每个销轴品质
- ◆ Surface finish (表面处理) : Powder painted (喷漆)



SLR261- BLOCK HOOK 葫芦钩

SLR261

ITEM NO.	WEIGHT (kg)	WLL (T)	B.L (T)	Φ±0.1	B±0.5	D±0.3	E±0.1	H±1	L±1.2	M±1.2
SLR-261-1.5T	0.715	1.5	8	32	10.5	27	30.2	33	145.5	103

- 1/3rated load is the Working Load Limit 额定拉力是工作拉力的1/3
- ◆ Rough scale (粗糙刻度) : WLL 1.5T CE BATCH NUMBER (型号) : SLR

BLOCK HOOK
锻造葫芦钩

- ◆ Forget! Super alloy steel: Quenched and Tempered
- ◆ 高强度合金钢在热处理后必须回火处理，经过回火处理
- ◆ Breakage test
- ◆ 对轴一些关键点进行严格的破坏性测试
- ◆ 100% magnetic crack detection
- ◆ 100% 进行磁粉检测
- ◆ All load joints are 100% individually inspected and tested
- ◆ 所有载荷在100%测试，确保用好的质量品质
- ◆ Surface finish (表面处理) : Powder blasted (抛丸)
- ◆ Can be Rotated under Non-load Condition!
- ◆ 可在无载荷条件下进行转动!

SLR254- BLOCK HOOK
 钩形钩

SLR254

ITEM NO.	WEIGHT (kg)	WLL (T)	BL (T)	a ± 0.1	D ± 0.3	E ± 0.1	L ± 1.2	M ± 1.2
SLR-254-0.26T	0.27	0.35	0.5	15.6	16.5	23	37.6	71
SLR-254-0.75T	0.66	0.76	1.5	29.5	16	27	110.5	82
SLR-254-1.5T	1.1	1.6	3	34	16	32	104	104.5
SLR-254-3T	1.56	3	5	31	14	42	126	131

Downloaded from <http://ajphaphysiol.physiology.org/> by guest on September 11, 2012

● 研究報告 (編輯部註) | 2015年12月25日 第16卷第12期 | 151

SLIDING COUPLING TACKLE HOOK
滑车钩

- ◆ Forged super alloy steel - Quenched and Tempered
- ◆ 高强度合金钢经淬火及回火处理，提供最佳处理
- ◆ Individually proof tested at 2.5 times Working Load Limit
- ◆ 每件工作力均经 2.5 倍工作负载测试
- ◆ Fatigue tested at 1.5 times Working Load Limit for 20000 cycles
- ◆ 疲劳进行 20000 次疲劳测试
- ◆ Breakage test
- ◆ 对每一批产品进行严格的破坏性测试
- ◆ 100% magnetic particle detection
- ◆ 100% 磁粉探伤检测



SLR721-SLIDING COUPLING TACKLE HOOK

SLR721

ITEM NO.	WEIGHT (KG)	WLL (T)	R.L (T)	A±1	B±1	E±2	F±2	M±1	N±1	G±1	L±3
8-SLR-721-8	0.05	2	8	54	40	25	00	10.7	0.0	20	151
8-SLR-721-10	1.67	3.15	32.6	54	40	30	100	17	39	32	198
8-SLR-721-13	6.67	9.3	12.9	68.5	54	32	131	46	90	57	230



WARNING 警告: Do not use the power tool with a damaged power cord. A damaged power cord can cause electric shock or fire.

G80 CONTAINER LIFTING 80级 集装箱索具配件

- ★ Forged super alloy steel- Quenched and Tempered
- ◇ 高强度合金铸钢件合金钢锻造而成，经过热处理
- ★ Individually proof test at 2.5 times Working Load Limit
- ◇ 零件按工作拉力的2.5倍进行验证测试
- ★ Fatigue tested at 1.5 times Working Load Limit for 20000 cycles
- ◇ 材料进行20000次疲劳测试
- ★ Breakage test ◇ 对每一批次产品进行严格的破坏性测试
- ★ 100% magnetic crack detection ◇ 100% 进行磁粉探伤



SLR243-G80 CONTAINER LIFTING CLEVIS LINK
80级集装箱羊吊吊环

SLR243

ITEM NO.	WEIGHT (kg)	WLL (T)	B.L (T)	A	B±1	C±1	D±2	E±2
8-SLR-13mm	5.0	5.9	21.2	16	60	71.6	114	106

Ultimate tensile 4 times the Working Load Limit 破断力是工作拉力的4倍

- ★ Product code (产品编号): 13-SLR-5.9 21.2 16 60 71.6 114 106

KB TYPE CLEVIS CONTAINER HOOK KB型羊角集装箱钩

- ★ Forged super alloy steel- Quenched and Tempered
- ◇ 高强度合金铸钢件合金钢锻造而成，经过热处理
- ★ Individually proof test at 2.5 times Working Load Limit
- ◇ 零件按工作拉力的2.5倍进行验证测试
- ★ Fatigue tested at 1.5 times Working Load Limit for 20000 cycles
- ◇ 材料进行20000次疲劳测试
- ★ Breakage test
- ◇ 对每一批次产品进行严格的破坏性测试
- ★ 100% magnetic crack detection
- ◇ 100% 进行磁粉探伤



SLR851-KB TYPE CLEVIS CONTAINER HOOK
KB 型羊角集装箱钩


SLR851

ITEM NO.	WEIGHT/KG	WLL/T	B.L/T	A±1	B±1.5	C±1	E±1	M±2	N±0.5	H±1	L±2
13-B	8.5	11.2	21.2	15	57	24	35	347	38	44	357.5



SHANK HOOK WITH EYE SCREW 吊环ROV直杆钩

- ◆ Forged super alloy steel- Quenched and Tempered
- ◆ 高强度异形合金钢锻造而成，经过热处理
- ◆ Inductively proof test at 2.5 times Working Load Limit
- ◆ 零件在工作应力2.5倍范围内验证测试
- ◆ Fatigue tested at 1.5 times Working Load Limit for 20000 cycles
- ◆ 吊钩进行20000次疲劳测试
- ◆ Breakage test
- ◆ 对每一批次产品进行严格的破坏性测试
- ◆ 100% magnaflux crack detection
- ◆ 100% 进行磁粉探伤



SLR552-ALLOY SHANK HOOK WITH EYE SCREW
合金钢ROV吊环直杆钩

SLR552

ITEM CODE	WEIGHT (KG)	WLL (T)	BL (M)	A	B±3	E±1.5	F ⁺⁰ -0.5	H	M±3	K±0.5	P±1	T±1	M±0.5	D	R	N±2	L±5
SLR-552-5.4T	9.0	3.4	31.8	100	30	34.2	56	150	100	275.5	45	46	58	21	39	90	447
SLR-552-12T	17.3	12	50	150	60	54	56	46	152	275.5	65	70	72	30	51	110	771
SLR-552-22T	34.6	22	68	180	87	70	108	60	206	280	85	102	41	51	90	100	730
SLR-552-31.6T	44	31.6	100	181	83	78	100	70	250	280	115	115	45	130	110	128	820

(Regular code (常规型号)) : Alloy steel (合金钢) : ALLOY-552-5.4T CE-552

OPENING EYE HOOK 眼型大开口钩

- ◆ Forged super alloy steel- Quenched and Tempered
- ◆ 高强度异形合金钢锻造而成，经过热处理
- ◆ Inductively proof test at 2.5 times Working Load Limit
- ◆ 零件在工作应力2.5倍范围内验证测试
- ◆ Fatigue tested at 1.5 times Working Load Limit for 20000 cycles
- ◆ 吊钩进行20000次疲劳测试
- ◆ Breakage test
- ◆ 对每一批次产品进行严格的破坏性测试
- ◆ 100% magnaflux crack detection
- ◆ 100% 进行磁粉探伤



SLR625-OPENING EYE HOOK
眼型大开口钩

SLR625

ITEM NO.	WEIGHT (KG)	WLL (T)	BL (M)	A±2	R±2	M±2	U±3	L±3
SLR-625-2T	9	3	12	75	40.5	200	25	300.0

Ultimate limit is 4 times the Working Load Limit 极限应力为工作应力的4倍

★ Regular code (常规型号) : 10-3-552-12T CE-552 + PART NUMBER (型号)



WARNING 警告: This is a lifting equipment and must be used properly. (此设备为起重设备，必须正确使用。)

G80 EYE SHORTENING GRAB HOOK 80级 眼型翅钩

- ◆ Forged super alloy steel - Quenched and Tempered
- ◆ 锻造超高强度特种合金钢锻造而成，经过热处理
- ◆ Individually proof test at 2.5 times Working Load Limit
- ◆ 每件钩工作压力的2.5倍进行验证测试
- ◆ Fatigue tested at 1.5 times Working Load Limit for 20000 cycles
- ◆ 抽样进行20000次疲劳测试
- ◆ Breakage test
- ◆ 对每一批次产品进行严格的破坏性测试
- ◆ 100% magnaflix crack detection
- ◆ 100% 进行磁粉探伤



SLR926-G80 EYE SHORTENING GRAB HOOK

SLR926

眼型翅钩


ITEM NO. 货号	WEIGHT (kg)	WLL (T)	B.L (T)	A	B	C	E	M	D	L
6-B	0.23	1.12	4.43	8±1	5±0.5	25.0±1	8.5±1	50±3	15.5±1	56.5±2
7.8-B	0.5	2	7	9.5±1	11±0.5	34±1.5	10.5±1	62.5±2	17.5±1	104±2
12-B	2.15	8.3	27.2	16.5±2	17±1	58±2	16.0±2	101±3	20±2	171±3

Ultimate load is 4 times the Working Load Limit. 极限拉力是工作压力的4倍。
Above Working Load Limit is based on design 超载使用的工作压力是在设计条件下工作压力。

- ◆ Please mark: 请标注: 10-B WLL: 8.3 T (2) SLR + BATCH NUMBER (批号)

CLEVIS GRAB HOOK WITH CRADLE 羊角翅钩

- ◆ Forged super alloy steel - Quenched and Tempered
- ◆ 锻造超高强度特种合金钢锻造而成，经过热处理
- ◆ Individually proof test at 2.5 times Working Load Limit
- ◆ 每件钩工作压力的2.5倍进行验证测试
- ◆ Fatigue tested at 1.5 times Working Load Limit for 20000 cycles
- ◆ 抽样进行20000次疲劳测试
- ◆ Breakage test
- ◆ 对每一批次产品进行严格的破坏性测试
- ◆ 100% magnaflix crack detection
- ◆ 100% 进行磁粉探伤



SLR937-CLEVIS GRAB HOOK WITH CRADLE

SLR937

羊角翅钩

ITEM NO.	WEIGHT (kg)	WLL (T)	BF (T)	A	B	C	D	E	M	L
6-B	0.25	1.12	4.43	8±0.5	5±1	8±1	18±1	8.3±1	50±2	91±2
7.8-B	0.58	2	6	9.5±0.5	10±1	11±1	24±1	10.5±1	62.5±2	115±3
12-B	2.4	8.3	27.2	15±0.5	16±2	19±1	37±2	15.5±1.5	60±3	173±4

Ultimate load is 4 times the Working Load Limit. 极限拉力是工作压力的4倍。
Above Working Load Limit is based on design 超载使用的工作压力是在设计条件下工作压力。


- ◆ Please mark: 请标注: 10-B WLL: 8.3 T (2) SLR + BATCH NUMBER





EYE HOOK 锻造眼钩

- ◆ Available in carbon steel and alloy steel
- ◇ 可以锻造碳钢和合金钢两种材料
- ◆ Forged + Quenched and Tempered
- ◇ 锻造而成，经过热处理
- ◆ Bridge test
- ◇ 对每一批次产品进行严格的桥式破坏测试
- ◆ 100% magnetic particle detection
- ◇ 100% 进行磁粉探伤
- ◆ Surface finish (表面处理)
- ◇ Powder plastcoat (喷塑)
- ◆ Color code(色号)
- ◇ Red (红色) RAL3020/Yellow (黄色) RAL1003



SLR130-EYE HOOK

链条吊钩

SLR130

ITEM NO.	WEIGHT (kg)	ALLOY 合金钢		CARBON 碳钢		D×1	E×2	H×1.5	K×2.5	L×3	M×1.5
		WLL (T)	S.L (T)	WLL (T)	S.L (T)						
SLR-130-A0.75T/C0.5T	0.21	0.75	3.75	0.5	3.5	15.5	12	17	75	67	10
SLR-130-A1T/C0.75T	0.27	1	5	0.75	3.75	16	22	20.5	85	112	15
SLR-130-A1.5T/C1T	0.4	1.5	7.5	1	5	20	24.5	21.5	104	128	17.5
SLR-130-A2T/C1.5T	0.8	2	10	1.5	7.5	22	26	25	104.5	142	21
SLR-130-A3T/C2T	0.64	3	15	2	10	24	27	28	120	151	23
SLR-130-A5T/C3T	1.31	5	25	3	15	30	35.5	40	148	200	35
SLR-130-A7T/C5T	4.35	7	35	5	25	51	44	48	187.5	266	55
SLR-130-A11T/C7.5T	6.7	11	55	7.5	37.5	67	65	67	201.5	317	66
SLR-130-A15T/C10T	9.6	15	75	10	50	73	77	85	202	350	65
SLR-130-A22T/C15T	16	22	110	15	75	84	83	78.5	319	428	102.5
SLR-130-A36T/C20T	26.3	30	150	20	100	90	90	91	450	495.5	120

Ultimate load is 5 times the Working Load Limit. 终极拉力是工作拉力的5倍。

Request mark: (规格号) : 规格: SLR130-CZ SLR-40ATCHINUMBER (字母) ;
色套号: ALLOY WLL T/C SLR-40ATCHINUMBER (字母) .




WARNING 警告

SLR-130-EYE HOOK is a lifting device. It is not a toy. Please use it correctly.

NEW TYPE EYE HOOK 眼型货钩

- ◆ Forged - Quenched and Tempered
◇ 锻造而成, 经过热处理
- ◆ Brantidge test
◇ 对称一批次产品进行严格的拉伸屈服测试
- ◆ 100% magnanum crack detection
◇ 100% 进行磁粉探伤
- ◆ Surface finish (表面处理): Powder painted (喷漆)
- ◆ Colour code(色号): Red (红色) RAL 3020 / Yellow (黄色) RAL 1003



NEW! 改进型



SLR156 - NEW TYPE ALLOY STEEL EYE HOIST HOOK
新型合金钢眼型吊钩

SLR156

ITEM NO.	WEIGHT (kg)	WLL (T)	BL (T)	E	Ø	Ø1	Ø2	L	K	M
SLR-156-0.75T	0.21	0.75	8.75	16 ± 1	12 ± 1	16.6 ± 1	12.5 ± 1	97 ± 2	22 ± 2	16 ± 1
SLR-156-1T	0.30	1	9	22.5 ± 1	19 ± 1	19 ± 1	12.9 ± 1	112 ± 2	92 ± 2	16 ± 1
SLR-156-1.5T	0.4	1.5	9.5	24.5 ± 1	24 ± 1	20 ± 1.5	44 ± 2	120 ± 2	94 ± 2	17.5 ± 1
SLR-156-2T	0.60	2	10	25.5 ± 1	24 ± 1	26 ± 1.5	51 ± 2	142 ± 2	105 ± 2	21 ± 1
SLR-156-3T	0.84	3	10	27 ± 1.5	21 ± 1.5	31 ± 1.5	81 ± 2	150 ± 2	129 ± 2	22 ± 1
SLR-156-6T	1.75	6	25	35.5 ± 1.5	30 ± 1.5	30 ± 1.5	73 ± 2	203 ± 2	140 ± 2	34 ± 2
SLR-156-7T	9.77	7	36	43 ± 2	42 ± 2	51 ± 2	97 ± 2.5	206 ± 2	195 ± 2	58 ± 2
SLR-156-11T	6.1	11	55	58 ± 2	45 ± 2	57 ± 2	119 ± 2.5	317 ± 2	213 ± 2	40 ± 2
SLR-156-15T	11.8	15	75	69 ± 2	57 ± 2	73 ± 2	137 ± 2.5	390 ± 4	327 ± 4	55 ± 2
SLR-156-22T	15.24	22	110	75 ± 2	64 ± 2	80 ± 2.5	153 ± 3	454 ± 4	416 ± 4	68.5 ± 2.5
SLR-156-30T	25.4	30	150	105 ± 2	82 ± 2	104 ± 2.5	175 ± 3	494 ± 4	460 ± 4	75 ± 2.5

Ultimate Proof or Stress that Working Load Limit, 按断应力为工作能力的极限

Regulation(国家标准): ALLOY CAST IRON SLR-BATCH NUMBER (批号)



EYE HOOK

眼型货钩

- ◆ Large throat opening and small cross area
- ◇ 大开口, 小截面, 更便捷装卸和穿入。
- ◆ Forged alloy steel, High strength and good ductility
- ◇ 优质合金钢锻造而成, 强度高, 韧性好。
- ◆ Only for general hoist. Not for overhead lifting
- ◇ 仅用于一般起吊, 不得用于头上起吊作业。



SLR0113-EYE HOOK

眼型货钩


SLR113

ITEM NO.	WEIGHT (KG)	WLL (T)	B.L (T)	$\varnothing \pm 0.5$	B ± 1	L ± 3	R ± 2	E ± 1.5	H ± 1
SLR-113-2T	6.05	2	4	26	32.5	94.5	44	87	24
SLR-113-3T	1.28	3	6	40.0	48.0	179	69.0	80	31.0
SLR-113-5T	1.45	4	10	55.5	65.5	185	97	64	35.5
SLR-113-6T	2.75	6	12	67.5	78.5	234	116.5	81	41.5
SLR-113-8T	3.25	8	16	82	92	253	129.5	89.5	47

U-Shape Key & 2 times the Working Load Limit 钩型为吊工作能力的两倍

Regular mark (常规标记): WLL 2T CE SLR

- ◆ Large throat opening and small cross area
- ◇ 大开口, 小截面, 更便捷装卸和穿入。
- ◆ Forged alloy steel, High strength and good ductility
- ◇ 优质合金钢锻造而成, 强度高, 韧性好。
- ◆ Only for general hoist. Not for overhead lifting
- ◇ 仅用于一般起吊, 不得用于头上起吊作业。



SLR118-ALLOY EYE HOOK

合金钢无舌眼型大开口钩

SLR118

ITEM CODE 货号	WEIGHT (Kg)	WLL (T)	B.L (T)	D ± 1	L ± 3	B ± 2	R ± 2	E ± 2	H ± 2
SLR118-2T	0.31	2	4	20	136	62	66.5	44	20

U-Shape Key & 2 times the Working Load Limit 钩型为吊工作能力的两倍

Regular mark (常规标记): WLL 2T CE SLR 118 118-2T 118 118 2T 118 118 2T



WARNING 警告

Do not use for lifting people or other loads not intended for lifting.

FORGED EYE HOOK 锻造眼型钩

- ◆ Large throat opening and small end area
○ 大开口、小断面，更方便装卸和吸入
- ◆ Forged alloy steel/High strength and good ductility
○ 优质合金锻造而成，高强度、韧性好
- ◆ Only for general load and for overhead lifting
○ 仅用于一般起重，不能用于吊上起重停止。



SLR536-EYE SLING HOOK

眼型滑钩

SLR536

ITEM CODE 货号	WEIGHT (kg)	WLL (T)	B.L (T)	D±1	L±3	B±2	R±2	E±2	H±2
SLR536-5T	2.8	5	18	32	259	23	189	63	42

Regular mark (常规款式) (SLR536-5T为例) : 9324 151 127 CC SLR 536ATCH 18.55566 (型号)

- ◆ Forged alloy steel or carbon steel
○ 合金钢或碳钢锻造而成
- ◆ Forged + Quenched and Tempered
○ 锻造而成，经过热处理
- ◆ Breakage test
○ 对每一批次产品进行严格的破坏性试验
- ◆ 100% magniflux crack detection
○ 100% 进行磁粉探伤
- ◆ Surface finish (表面处理) : Powder painted (喷漆)
- ◆ Colour code (色号) : Red (红色)RAL 3020/Yellow (黄色)RAL 1003



SLR618-EYE HOOK

眼型滑钩

SLR618

ITEM NO.	WEIGHT (kg)	ALLOY		CARBON		D±1	E±2	H±1.5	K±2.5	L±3	M±1.5
		WLL (T)	B.L (T)	WLL (T)	B.L (T)						
SLR-618-A1TAC0.75T	0.71	1	5	0.75	3.75	10	2a	27	75.5	111	10
SLR-618-A1.5TAC1T	0.81	1.5	7.5	1	5	22	25	24	84	129	15
SLR-618-A2TAC1.5T	0.90	2	10	1.5	7.5	25	24.5	27	108.5	146	20
SLR-618-A3TAC2T	1.16	3	15	2	10	27	25.5	32	118.5	167	24
SLR-618-A5TAC3T	1.76	5	25	3	15	40	35	37	142	205	30.5
SLR-618-A7TAC5T	2.72	7	35	5	25	51	45	46	158.5	250.5	43
SLR-618-A11TAC7.5T	6.78	11	55	7.5	37.5	62	56	59	175	316	49
SLR-618-A15TAC10T	11.2	15	75	10	50	72	62	68	205	315	51

Working Load Limit is 5 times the Working Load Limit. 破断力是工作力5倍。

Regular mark (常规标记) : Alloy steel (合金钢) : 9324 151 127 CC SLR 618ATCH 18.55566 (型号)


合金钢, ALLOY STEEL CC SLR 618ATCH 18.55566 (型号)。



EYE SLING HOOK

单眼货钩

- ◆ Forged alloy steel or carbon steel-Quenched and Tempered
- ◇ 合金钢或碳素钢锻造，严格的淬火处理保证了强度和韧性
- ◆ 100% magnetic crack detection
- ◇ 100%进行磁粉探伤
- ◆ Surface finish (表面处理) :
- ◇ Powder (plastic) (粉塑)
- ◆ Color code (颜色) :
- ◇ Red (红色) RAL 3020 / Yellow (黄色) RAL 1003



SLR504-EYE SLING HOOK

单眼货钩


SLR504

ITEM NO.	WEIGHT (KG)	WLL (T)		M±2	d±2	E±2	D±3	L±3
		CARBN (S.T)	ALLOY (d.T)					
SLR-504	6.3	0.6	1.25	73.4	10	25	4.5	111.0
SLR-504	0.33	1	1.6	92	28	27	11.5	120
SLR-504	0.58	1.5	2.5	92	29	31	19	140
SLR-504	0.0	2	3.2	104	32	33	16	164
SLR-504	1.6	2.2	5.4	122	40	37	14	204
SLR-504	3.33	3	3	132	51	48.6	23.0	252.0

ITALIAN TYPE EYE SLING HOOK

意式单眼货钩

- ◆ Forged alloy steel or carbon steel-Quenched and Tempered
- ◇ 合金钢或碳素钢锻造，严格的淬火处理保证了强度和韧性
- ◆ 100% magnetic crack detection
- ◇ 100%进行磁粉探伤
- ◆ Surface finish (表面处理) :
- ◇ Powder (plastic) (粉塑)
- ◆ Color code (颜色) :
- ◇ Red (红色) RAL 3020 / Yellow (黄色) RAL 1003



SLR505-ITALIAN TYPE EYE SLING HOOK

意式单眼货钩

SLR505


ITEM NO.	WEIGHT (KG)	WLL (T)		M±2	d±2	E±2	D±3	H±3	L±3
		CARBN (S.T)	ALLOY (d.T)						
SLR-505	0.6	0	0.7	100	30	33	19	30	104



WARNING 警告 This is a safety-critical component. It must be used in accordance with the instructions.

SPECIAL EYE HOIST HOOK 异型眼型货钩

- ◆ Forged super alloy steel—Quenched and Tempered
- ◇ 高强度异型材料锻造并经热处理，经过热处理
- ◆ Brautridge test
- ◇ 对每一批产品进行严格的拉伸屈服测试
- ◆ 100% magniflor crack detection
- ◇ 100%进行磁粉探伤
- ◆ Surface finish (表面处理) :
- ◇ Powder (plastic) (涂层)
- ◆ Colour code (色号) :
- ◇ Red (红色) : RAL 3020 / Yellow (黄色) : RAL 1003




SLR291-SPECIAL EYE HOIST HOOK
异型眼型货钩

SLR291

ITEM NO.	WEIGHT (KG)	CARBON (B:1)	ALLOY (A:1)	W+2	B+2	E+2	D+3	L+3
SLR-291-0.8T	0.29	0.8	1.25	19	08	29	11.8	170
SLR-291-1.0T	0.39	1	1.2	22	81	28	11.6	120
SLR-291-1.4T	0.52	1.6	1.5	28	63	30	13	134
SLR-291-2.0T	0.61	2	2.2	30	106	38.2	16	163

ITALIAN TYPE EYE SLING HOOK WITH FLAT 意式带扁单眼货钩

- ◆ Forged super carbon steel—Quenched and Tempered
- ◇ 高强度扁钢材料锻造并经热处理，经过热处理
- ◆ 100% magniflor crack detection
- ◇ 100%进行磁粉探伤
- ◆ Surface finish (表面处理) :
- ◇ Powder (plastic) (涂层)
- ◆ Colour code (色号) :
- ◇ Red (红色) : RAL 3020 / Yellow (黄色) : RAL 1003



SLR366-ITALIAN TYPE EYE SLING HOOK WITH FLAT
意式带扁单眼货钩

SLR366

ITEM NO.	WEIGHT (KG)	WLL (T) (4:1)		D+2	W+2	H+2	E+3	L+3
		CARBON	ALLOY					
SLR-366-0.8T	0.22	0.8	1.25	9.5	19	23	15	111
SLR-366-1.0T	0.34	1	1.2	11	22	25	15.8	127
SLR-366-1.5T	0.51	1.6	2.2	11.75	25.5	25.5	18	144.5
SLR-366-2T	0.805	2	2.2	15	37	36	21	168
SLR-366-5T	0.84	5	5	25	61	60.3	45.4	285.5
SLR-366-7.5T	0.91	7.5	11	29	62	63	50	321



EYE HOIST HOOK

眼型货钩

- ◆ Forged alloy steel or carbon steel-Quenched and Tempered
- 合金钢锻造制造，严格的淬火处理保证了强度和韧性
- ◆ 100% magnetic crack detector
- 100%进行磁粉探伤
- ◆ Surface finish (表面处理) ;
- Powder plating(镀塑)
- ◆ Colour code(颜色) ;
- Red(红色) /RAL 3020 /Yellow(黄色) /RAL 1003



SLR629-EYE HOIST HOOK

SLR629


眼型货钩

ITEM NO.	WEIGHT (KG)	WLL (T)		D±2	E±2	H±3	M±3	L±3
		CARBON (B.1)	ALLOY (B.1)					
SLR-629	0.18	0.5	0.75	10.5	21	05	62	102
SLR-629	0.3	0.75	1	17	29	20.0	70	134
SLR-629	0.4	1	1.6	22	36	33.0	77.8	127
SLR-629	0.54	1.5	2	26.5	39	101.5	67	141
SLR-629	0.91	2	3.2	30	39	112.5	87	195
SLR-629	1.3	3	5	30	39	102.5	102	211
SLR-629	3.1	5	7.5	49	46.7	120	160	217
SLR-629	9.5	7.5	11	69	61.6	181	100	319

ITALIAN TYPE EYE SLING HOOK CARBON STEEL

意式碳钢单眼滑钩

- ◆ Forged carbon steel-Quenched and Tempered
- 合金钢锻造，严格的淬火处理保证了强度和韧性
- ◆ 100% magnetic crack detector
- 100%进行磁粉探伤
- ◆ Surface finish (表面处理) ;
- Powder plating(镀塑)
- ◆ Colour code(颜色) ;
- Red(红色) /RAL 3020 /Yellow(黄色) /RAL 1003



SLR097-ITALIAN TYPE EYE SLING HOOK CARBON STEEL

SLR097

意式碳钢单眼滑钩

ITEM NO.	WEIGHT (KG)	WLL (T)	B.L (T)	D±2	φ±2	E±2	H±3	L±3
SLR-97-3T	1.1	3	12	18	40	40	40	200
SLR-97-5T	3.0	5	20	21.5	51.5	50	45	200.5




WARNING 警告 This is a lifting equipment and can be dangerous, use with care.

LARGE OPENING HOOKS

高强度细筋大开口钩

- ◆ Large throat opening and small throat area
- ◆ 大开口，小颈部，更方便连接和吸入
- ◆ Forged alloy steel high strength and good ductility
- ◆ 优质合金钢锻造而成，高强度，韧性好
- ◆ Only for general hoist/lift for even and lifting
- ◆ 仅用于一般起重，不能用于头上起重作业



SLR114-ALLOY EYE HOOK WITH LATCH

合金钢合金钢型大开口钩

SLR114

ITEM CODE 货号	WEIGHT (Kg)	WLL (T)	BL (T)	D*1	L*3	B*2	R*2	E*2	H*2
SLR114-1.5T	0.22	1.5	4.5	17	58.5	71.5	75	20	75

1. For use load 3/4 of rated load (working load limit) 使用负荷为额定负荷的3/4

Regulation (Machinery Directive 114-1.5T hook): EN 1371 CE mark (CE mark is required)

EYE SLIP HOOK

眼型滑钩

- ◆ Forged super carbon/low alloy steel - Quenched and Tempered
- ◆ 高强度超低碳/低合金钢锻造而成，经过淬火处理
- ◆ Not for lifting, only for lashing or pulling
- ◆ 不能用于起重，仅用于捆绑和拉拽
- ◆ 100% magnetic particle detection / 100% 进行磁粉探伤
- ◆ Surface finish (表面处理): ○ Powder painted (喷塑)
- ◆ Color code (色号):
- Red (红色) RAL 3020 / Yellow (黄色) RAL 1003



SLR128-EYE SLIP HOOK

眼型滑钩

SLR128

ITEM NO.	WEIGHT (lbs)	WLL (lbs) (4:1)		A*2	D*2	R*2	E*2	L*3	M*3	N*3
		CARBON	ALLOY							
SLR-128-1/4	0.22	1050	2750	8.5	10	66.5	18.5	70	72	14.5
SLR-128-5/16	0.5	2875	4300	9	10	74	24.5	100	77	16
SLR-128-3/8	0.67	4000	5750	10.75	12	85.5	27	113.5	85	19
SLR-128-7/16	0.71	5200	7500	12.7	12.5	96.5	32	142.5	107	21
SLR-128-1/2	0.85	6500	9500	14.5	13	109.5	34	156	114	23
SLR-128-3/4	2.82	12000	18000	18.3	15.8	148	50.0	212	158	34

◆ Regulation (EN 1281): EN 1281-14 FORKED: 5/16 D-43 H/21 T/21 FORKED 1/4



COMMERCIAL HOOKS

普通拖钩和绑钩系列

◆ Forged super alloy steel - Quenched and Tempered.

◆ 合金钢锻造而成，经过热处理。

◆ Not for lifting only for hoisting or pulling.

◆ 不能用于起重，仅用于吊移或牵引。

◆ Breakage limit

◆ 对每一批次的产品进行严格的破坏性测试。

◆ 100% magnetic crack detection

◆ 100% 进行磁粉探伤



SLR062-ALLOY TRIANGLE RING HOOK

三角环吊钩

SLR062

ITEM NO.	WEIGHT (KG)	WLL (daN)	B.L (T)	A±4	D±1	H±2	K±2	L±3	N±1
SLR-062-5T	1.55	2500	5	65	12	28	110	173	20
SLR-062-10T	1.51	5000	10	78	16	32	137.5	216	40




WARNING 警告: Do not use for lifting or pulling. Do not use for lifting or pulling.

COMMERCIAL HOOKS

普通拖钩和绑钩系列

- ◆ Forged carbon steel-Quenched and tempered
- ◇ 优质碳钢锻造，经过热处理
- ◆ Surface finish: Galvanized
- ◇ 表面处理：镀锌白件
- ◆ Only for lashing or pulling. Never to be used for lifting
- ◇ 仅用于捆绑或拉拽，绝不要用于起重



SLR050-TOW HOOK


铝漆保钩

SLR050

ITEM CODE 型号	WEIGHT (KG)	B.L (T)	D±1	N±2	E±1	B±2	L1±3	L2±3
SLR050-6mm	0.15	2.3	7	13	17	53	80	56
SLR050-8mm	0.20	2.8	8	17	21	62	102	76
SLR050-9mm	0.25	3.3	9	19.4	22	71	109	79

Regular mark (常规标识) SLR050-6mm系列 (6mm VILLAGE OF SLR HATCH (常规标识))

- ◆ Forged carbon steel-Quenched and tempered
- ◇ 优质碳钢锻造，经过热处理
- ◆ Surface finish: Galvanized
- ◇ 表面处理：镀锌白件
- ◆ Only for lashing or pulling. Never to be used for lifting
- ◇ 仅用于捆绑或拉拽，绝不要用于起重



SLR233-TOW HOOK

铝漆保钩

SLR233

ITEM CODE 型号	WEIGHT (KG)	B.L (T)	D±1	N±2	E±2	B±2	L1±3	L2±3
SLR233-114	0.16	2.3	5.5	10	20	52.5	117.5	87
SLR233-516	0.20	3.3	6.0	10	23.5	70	112.5	80

Regular mark (常规标识) SLR233-010系列 (010 OF SLR HATCH (常规标识))



EYE SLING HOOK

单眼货钩

- ◆ Forged alloy steel or carbon steel-Quenched and Tempered
- ◇ 合金钢或碳素钢，严格的淬火处理保证了强度和韧性
- ◆ 100% magnetic crack detection
- ◇ 100%进行磁粉探伤
- ◆ Surface finish (表面处理): ◇ Powder-plated (镀锌)
- ◆ Colour code (色号):
- ◇ Red (红色) RAL3020 / Yellow (黄色) RAL1003



SLR223-EYE SLING HOOK

单眼货钩


SLR223

ITEM NO.	WEIGHT (KG)	WLL(T)		E±2	Ø±2	D±2	H±3	B±3	M±3	N±3	L±3
		CHAIN	ALLOY								
SLR-223-0.8T	0.25	0.8	1.25	25.4	19	9.5	21	40	15	13	111.5
SLR-223-1.0T	0.4	1	1.6	27	21	11.5	23	43	16	14	122
SLR-223-1.6T	0.5	1.6	2.5	29	23	12	24.5	47	21	14	145
SLR-223-2.0T	0.9	2	3.2	33	25	15	30	50	24	15	154
SLR-223-3.0T	1.6	3.2	5.4	41	30	15	40.7	62	30	30	201
SLR-223-5.0T	3.75	5	8	49.5	37	23.5	48	80	36	24	254.5

EYE HOOK WITH LAING

眼型钩

- ◆ Forged carbon steel-Quenched and Tempered
- ◇ 合金钢，严格的淬火处理保证了强度和韧性
- ◆ 100% magnetic crack detection
- ◇ 100%进行磁粉探伤
- ◆ Surface finish (表面处理):
- ◇ Powder-plated (镀锌)
- ◆ Colour code (色号):
- ◇ Red (红色) RAL3020 / Yellow (黄色) RAL1003



SLR225-EYE HOOK WITH LAING

眼型钩

SLR225

ITEM NO.	WEIGHT (KG)	WLL (T)	B.L	E±2	Ø±2	B±2	H±3	D±3	R±3	L±3
8-SLR-225-1.5T	0.55	1.5	8	26	27	13	26.5	13.5	10.5	142.4



WARNING 警告: This is a lifting device and must be used in accordance with the instructions.

LARGE OPENING HOOKS 高强度细筋大开口钩

- ◆ Large throat opening and small cross area
- ◇ 大开口，小截面积，更方便连接和拆卸。
- ◆ Forged alloy steel, High strength and good ductility
- ◇ 优质合金钢锻造而成，高强度，韧性好。
- ◆ Only for general hoist/lift for overhead lifting
- ◇ 仅用于一般起重，不得用于吊上拉紧作业。



SLR502-EYE HOOK


SLR502

眼型钩

ITEM CODE 货号	WEIGHT (Kg)	WLL (T)	BL (T)	D±1	L±3	B±2	R±2	E±2	H±2
SLR502-3.2T	0.22	3.2T	3.2T	21	104	103	530	67	74

LARGE OPENING HOOKS 高强度细筋大开口钩

- ◆ Large throat opening and small cross area
- ◇ 大开口，小截面积，更方便连接和拆卸。
- ◆ Forged alloy steel, High strength and good ductility
- ◇ 优质合金钢锻造而成，高强度，韧性好。
- ◆ Only for general hoist/lift for overhead lifting
- ◇ 仅用于一般起重，不得用于吊上拉紧作业。



SLR117-ALLOY EYE HOOK WITH LATCH

SLR117

合金钢带舌眼型大开口钩

ITEM CODE	WEIGHT (Kg)	WLL (T)	BL (T)	D±1	L±3	B±2	C±2	R±2	E±2	H±2
SLR117-6300LBS	0.49	3	3	21.5	127	67.9	21	16.7	27	38.3


Ultimate loads 2 times the Working Load Limit 极限拉力为工作拉力2倍

Regular check 1. 定期检查 SLR117-6300LBS (3T) : 5418300LBS (3T) SUBSTITUTION PROHIBITED (禁用)



MILD STEEL HOOKS 普通低碳钢货钩

- ◆ Forged mild steel
- ◇ 普通低碳钢锻造
- ◆ Surface finish: Galvanized
- ◇ 表面处理: 电镀锌
- ◆ Only for lashing or pulling. Never to be used for lifting
- ◇ 仅用于捆绑或拉紧, 绝不可用于起重



SLR020-DING689 HOOK WITH LTACH

型号DING689货钩

SLR020

ITEM NO.	WEIGHT (kg)	SWL (KG)	A±0.5	B±1	C±1.2	D±0.5	E±2
SLR-020-250KG	0.15	250	12	54	10	725	38.5
SLR-020-500KG	0.27	500	15	69	23	15	117
SLR-020-1000KG	0.34	1000	20	95	34	15	100
SLR-020-1600KG	1.3	1600	22	111	37	16	183
SLR-020-2500KG	2.95	2500	28	145	46	20	253

Regular mark (常规标记): SLR 250KG-CE

EYE SLIP HOOK 眼型滑钩

- ◆ Forged super corrosion-resistant Quenched and Tempered
- ◇ 高强度耐腐蚀性经淬火回火钢锻造而成, 经过热处理
- ◆ Not for lifting, only for lashing or pulling
- ◇ 不能用于起重, 仅用于捆绑和拉紧
- ◆ 100% magnetic crack detection
- ◇ 100%进行磁粉探伤
- ◆ Surface finish (表面处理): / ◇ Powder paint (粉末)
- ◆ Colour code (色号): / ◇ Red (红色) RAL 3020
- ◇ Yellow (黄色) RAL 1015



SLR126-EYE SLIP HOOK

眼型滑钩

SLR126

ITEM NO.	WEIGHT (LBS)	WLL (4:1)		Ø±2	R±2	L±3	M±3	E±2
		CARBON	ALLOY					
SLR-126-14	0.4	1065	2150	13.7	65	62	16.5	25
SLR-126-5/16	0.52	1275	4550	16	72.5	106	15	26
SLR-126-3/8	1	4650	8250	18	91.5	124	20.5	30
SLR-126-7/16	1.36	6050	10500	20.5	91.5	142	106	40
SLR-126-1/2	2.1	8950	16000	23	100.6	150	110.6	43
SLR-126-5/8	3.2	12550	19800	26.8	120.9	171.6	140	52
SLR-126-3/4	4.75	12500	19200	30	147.9	222	150	55

★ Regular mark (常规标记): 1275-1575 1/4 IN. 127500-1475 5/4 IN. 127500 TEST FOR 6800 LBS



WARNING 警告 This product is not to be used for lifting.

FORGED HOOK 锻打钩

- ◆ Large throat opening and small cross area
- ◇ 大开口、小截面，更方便连接和导入。
- ◆ Forged alloy steel, High strength and good ductility
- ◇ 优质合金钢锻造而成，高强度、韧性好。
- ◆ Only for general hoist, Not for overhead lifting
- ◇ 仅用于一般起吊，不能用于头上起重作业。



SLR257-FORGED HOOK
锻打钩

SLR257

ITEM CODE	WEIGHT (Kg)	WLL (LBS)	D ±1	L ±3	B ±2	R ±2	E ±2	H ±2
SLR257-3300LBS	0.22	3300	16.5	76	75	77	37	13.5

Please be mark (钢钩标注(SLR257-3300LBS钩)) : 3300LBS (CE CLIP/BATCH NUMBER钩)

EYE HOOK 眼型钩

- ◆ Large throat opening and small cross area
- ◇ 大开口、小截面，更方便连接和导入。
- ◆ Forged alloy steel, High strength and good ductility
- ◇ 优质合金钢锻造而成，高强度、韧性好。
- ◆ Only for general hoist, Not for overhead lifting
- ◇ 仅用于一般起吊，不能用于头上起重作业。



SLR206-EYE HOOK
眼型钩

SLR206


ITEM CODE	WEIGHT (Kg)	WLL (T)	BL (T)	D ±1	L ±3	B ±2	R ±2	E ±2	H ±2
SLR206-1.5T	0.20	1.5	4.5	7	69.6	71.5	76	39	13
SLR206-3T	0.36	3	9	16.5	125.3	127.5	131	52.5	21.2

Please be mark (钢钩标注(SLR206-1.5T钩)) : WLL 1.5T CE SLR+BA7 CHINAMAC (钩号)



ALLOY EYE HOOK WITH LATCH
合金钢含舌眼型大开口钩

- ◆ Large throat opening for small sized tools
- ◆ 大开口，小锯齿，更方便清理和穿入
- ◆ Forged alloy steel, high strength and good ductility
- ◆ 锻造合金钢制齿面，强度高，韧性好
- ◆ Only for general hole. Not for overhung drilling
- ◆ 仅用于一般钻孔，不适用于过肩钻孔



SLR115-3.1T



SLR115-2.2T

SLR115-ALLOY EYE HOOK WITH LATCH

SLR115

合金板壳筒型大开口圆


ITEM CODE	WEIGHT (Kg)	YLL (lbs)	B/L (lbs)	D+1	L+3	B+2	C+1	R+2	E+2	H+2
SLR115-5000LB	0.82	099	10000	18	162	97	16	131	37	209
SLR115-7000LB	1.41	0702	14000	22	108	118	26.5	138.5	40	24

1. 1875年2月，The Virginia Lumber Co. 成立，这是美国第一家专门从事木材贸易的公司。

Register now / 注册 [Get Data Now - Free!](#) **Now Get Your Free Trial!**

TOW HOOK
锻造保险钩

- ◆ Forged carbon steel-Quenched and tempered
- ◆ 优质碳素结构钢，调质处理
- ◆ Fatigue tested at 1.5 times Working Load Limit for 20000 cycles
- ◆ 抽样进行20000次疲劳强度测试
- ◆ Breakage test
- ◆ 对每一次产品进行产后的破坏性强度测试
- ◆ 100% magnetize for crack detection
- ◆ 100% 进行磁粉探伤



SLR379-TOW HOOK

聯華保險

SLR379

ITEM CODE	WEIGHT (kg)	B.L (T)	D±1	L±5	B±2	H±2	R±2	E±2
SLR379-3/16	0.14	1.5	12	154	164	12	65	41
SLR379-1M	0.2	2.4	17	170	175	18	72	34.0

【参考文献】 [1] 王德成, 王德成. 中国人口地理学[M]. 北京: 中国人口出版社, 2004.




WARNING 警告: Do not use this product if you are pregnant or breastfeeding. Do not use if you are allergic to any of the ingredients. Do not use if you are taking any other medication. Do not use if you are taking any other medication.

COMMERCIAL HOOKS

普通拖钩和绑钩系列

- ◆ Forged carbon steel-Quenched and tempered
- ◇ 优质碳素钢制造，经过热处理
- ◆ Surface finish: Galvanized
- ◇ 表面处理：电镀锌
- ◆ Only for lashing or pulling. Never to be used for lifting
- ◇ 仅用于捆绑或拖拉，绝不可用于起重



SLR455-TOW HOOK

普通拖钩


SLR455

ITEM NO.	WEIGHT (kg)	BF (KN)	A±1	B±1.2	D±0.8	H±0.8	E±1	L±2
SLR-455-LATCH	0.175	3.5	15	40	6.5	6	70	Ø1.5
SLR-455-WIRE	0.115	2.5	15	40	5.5	7	10	Ø1.5

COMMERCIAL HOOKS

普通拖钩和绑钩系列

- ◆ Forged carbon steel-Quenched and tempered
- ◇ 优质碳素钢制造，经过热处理
- ◆ Surface finish: Galvanized
- ◇ 表面处理：电镀锌
- ◆ Only for lashing or pulling. Never to be used for lifting
- ◇ 仅用于捆绑或拖拉，绝不可用于起重



SLR460-TOW HOOK

普通拖钩

SLR460

ITEM NO.	WEIGHT (kg)	BF (KN)	φ	B	E	L
SLR-460-LATCH	0.22	3.5	15	62	13	55
SLR-460-WIRE	0.21	2.5	15	62	13	55



COMMERCIAL HOOKS 普通拖钩和绑钩系列


- ◆ Forged carbon 6Nch-Quenched and tempered
- ◇ 优质碳素钢锻造，经过热处理
- ◆ Surface finish: Galvanized
- ◇ 表面处理：电镀锌
- ◆ Only for loading or pulling. Never to be used for lifting
- ◇ 仅用于装卸或牵引，绝不要用于起重

SLR462-TOW HOOK 起重拖钩

SLR462

ITEM CODE 型号	WEIGHT (Kg)	B.L (T)	$\Phi \pm 1$	B ± 2	E ± 2	L ± 3
SLR462-3.5T	0.21	3.5	10	50	17	110

Regular mark (常规标已以SLR462-3.5T为钩) : BL3.5T



SLR419-TOW HOOK 起重拖钩

SLR419

ITEM NO.	WEIGHT (kg)	BF (KN)	Φ	B	E	D	L
SLR-419-XBC65	0.15	2	13.3	50	17	10	100.5
SLR-419-XDL90	0.25	3	22	70	20.5	11	127



SLR420-TOW HOOK 起重拖钩

SLR420

ITEM NO.	WEIGHT (kg)	BF (KN)	Φ	B	E	L
SLR-420-LATCH	0.11	1.5	15	40	11	93
SLR-420-WIRE	0.145	1.5	16	40	15	93




WARNING 警告 This product is not to be used for lifting.

COMMERCIAL HOOKS

普通拖钩和绑钩系列

- ◆ Forged carbon steel-Quenched and tempered
- ◇ 优质碳钢锻造，经过热处理
- ◆ Surface finish: Galvanized
- ◇ 表面处理：电镀锌
- ◆ Only for lashing or pulling. Never to be used for lifting
- ◇ 仅用于捆绑或牵引，绝不能用于起重



SLR423-TOW HOOK

普通拖钩


SLR423

ITEM NO.	WEIGHT (kg)	BF (KN)	Φ	B	H	E	L
SLR-423-216	0.15	4.8	18	43.0	10	15	425.5

COMMERCIAL HOOKS

普通拖钩和绑钩系列

- ◆ Forged carbon steel-Quenched and tempered
- ◇ 优质碳钢锻造，经过热处理
- ◆ Surface finish: Galvanized
- ◇ 表面处理：电镀锌
- ◆ Only for lashing or pulling. Never to be used for lifting
- ◇ 仅用于捆绑或牵引，绝不能用于起重



SLR461-TOW HOOK

普通拖钩

SLR461

ITEM CODE 型号	WEIGHT (Kg)	B.L (T)	Φ ±1	B ±2	E ±2	L ±3
SLR461-LATCH	0.31	5	21	77	10	115
SLR461-WIRE	0.31	5	21	77	23	115


Regular mark (美国标准(SLR461-Latch和Wire)) : S7075 (R+LATCH) (R+Wire)



FORGED HOOKS

锻造钩系列

- ◆ Forged carbon steel—Quenched and tempered.
- ◆ 优质碳钢锻造，经过热处理。
- ◆ Stainless steel latch set is available.
- ◆ 可以提供不锈钢扣配件。
- ◆ Surface finish (表面处理): ○ Powder (last color) (涂层)
- ◆ 表面处理为工作拉力时所需。
- ◆ Color code (色号): ○ Red (红色) RAL 3020 ○ Yellow (黄色) RAL 1003



SLR352-FORGED SNAP HOOK

锻造简易保险钩

SLR352

ITEM NO.	WEIGHT (KG)	WLL (LBS)	D $\pm$ 2	E $\pm$ 2	F $\pm$ 2	G $\pm$ 2	H $\pm$ 3	L $\pm$ 3
SLR-352-916	0.24	1000	28	8	19.5	40	16	120

Regular hook (常规钩) SLR-352 V6 L14002.B5

DIN HOOK

德标货钩

- ◆ Forged carbon steel—Quenched and tempered.
- ◆ 优质碳钢锻造，经过热处理。
- ◆ Breakage test.
- ◆ 对每一批次产品进行严格的破坏性测试。
- ◆ 100% magnetic crack detection.
- ◆ 100% 进行磁粉探伤。



SLR357-DIN HOOK

德标货钩

SLR357


ITEM NO.	WEIGHT (Kg)	WLL (T)	SL (T)	D $\pm$ 1	E $\pm$ 2	H $\pm$ 1.5	K $\pm$ 1.5	L $\pm$ 2	M $\pm$ 1
SLR-357-250KG	0.10	0.25	0.5	15	50	18	20	26.0	13.5
SLR-357-500KG	0.27	0.6	1	10	30	21.0	20	110	14



WARNING 警告 See the instruction manual for safety instructions.

LIFTING TOOLS 锻打钢板钩

- ◆ Forged carbon steel
- ◆ 锻制碳素钢板
- ◆ Quenched and Tempered
- ◆ 经过热处理
- ◆ Breakage test
- ◆ 对每一批产品进行严格的破坏性测试



SLR624- LIFTING TOOLS

锻打钢板钩


SLR624

ITEM NO.	WEIGHT (kg)	WLL (T)	B.L (T)	A±1.5	B±3	C±1	H±3	L±3
SLR-624-ST	9.12	5	20	130	53	75	132.5	337.5
SLR-624-16T	21.8	10	40	205	135.5	115	140	435

Lifting tool is a kind of Working Load Limit (WLL) CE SLR.
吊钩钩体为一种工作负荷力限制 (WLL) CE SLR。

EYE HOIST HOOK 眼型钩

- ◆ Forged super alloy steel- Quenched and Tempered
- ◆ 高强度合金材料锻制产品完成，经过热处理
- ◆ Breakage test
- ◆ 对每一批产品进行严格的破坏性测试
- ◆ 100% mag. ultra crack detection
- ◆ 100% 进行磁粉探伤



SLR876- EYE HOIST HOOK

眼型钩

SLR876


ITEM NO.	WEIGHT (kg)	WLL (T)	B.L (T)	A±1.5	B±1.5	E±1	F±1	L±2	M±1.5	Ø±1	Ø±1
ST	1.40	5	20	10	25	27	21.5	137	75.5	10	65



WARNING 警告 This product is not to be used for lifting people or other loads.

LARGE OPENING HOOKS 高强度细筋大开口钩

- ◆ Forged superalloy steel - Quenched and Tempered
- ◇ 采用高强度材料经合金钢淬火处理，经回火处理
- ◆ Breakage free
- ◇ 对每一次使用进行严格的材料检测
- ◆ 100% magnetic crack detection
- ◇ 100% 进行磁粉探伤



SLR044-ALLOY EYE HOOK
合金钢无齿型大开口钩

SLR044

ITEM NO.	WEIGHT (kg)	WLL (T)	B.L (T)	D $\pm$ 1	E $\pm$ 2	M $\pm$ 1	H $\pm$ 1	R $\pm$ 1	L $\pm$ 2
SLR044-650SLBS	0.42	8	0	20.5	45	27	21.5	25	120

Ultimate load is 2 times the working load Limit 破断拉力是工作拉力的2倍

Regular mark 规格标记: (WLL) 0.07 (T)

MILD STEEL HOOKS 普通低碳钢货钩

- ◆ Forged mild steel
- ◇ 普通低碳钢锻造
- ◆ Only for lashing or pulling. Never to be used for lifting
- ◇ 仅用于捆绑或牵引，绝不准用于起重



SLR046-AGRICULTURAL HOOK
普通农钩

SLR046


ITEM NO.	WEIGHT (kg)	WLL (T)	$\Phi \pm 0.5$	$\Phi \pm 1$	E ± 0.5	L ± 1
SLR046-60	0.04	0.4	8.5	34	13	100
SLR046-60	0.04	0.9	9.5	41	16	70
SLR046-70	0.095	1	11	46.5	13	64
SLR046-80	0.13	1.3	11	54	17	60
SLR046-90	0.170	1.3	12.5	52	18	110
SLR046-100	0.2	2.4	12.5	92	19	114.5
SLR046-120	0.33	2.0	15.5	92	20	112

Regular mark 规格标记: (T) 100



TOW HOOK 拖钩系列

- ◆ Forged super alloy steel- Quenched and Tempered
- 高级合金材料经淬火及回火处理，强度高且稳定
- ◆ Resuable tool
- 对同一批次产品进行严格的材料检测测试
- ◆ 100% magnetic crack detection
- 100% 进行磁粉探伤



SLR444-FORGED TOW HOOK 普通拖钩

SLR444

ITEM NO.	WEIGHT (KG)	Ø1	Ø2	M±0.5	N	L ±1	L ±1
SLR-444	0.34	12	16	54.5	30	130	170



SLR311-FORGED TOW HOOK 合金钢普通汽车拖钩

SLR311

Forged alloy steel quenched and tempered.
合金钢锻造，进行热处理。
With safety latch. 带安全锁片。
Max load is 11000LBS 最大安全负重 11000LBS

ITEM NO.	WEIGHTkg	Maxload
SLR311-1A	0.72	11000LBS



SLR311-FORGED HEAVY TOW HOOK 重型钢普通汽车拖钩


Forged alloy steel quenched and tempered.
合金钢锻造，进行热处理。



WARNING 警告 Do not use this product if you find it damaged or defective.

TOW HOOK 拖钩系列

- ◆ Forged super alloy steel- Quenched and Tempered
- ◇ 高强度合金材料经合金钢锻造而成，经过热处理
- ◆ Breakage test
- ◇ 对称一批次产品进行严格的材料破坏测试
- ◆ 100% magnetic crack detection
- ◇ 100% 进行磁粉探伤




SLR051-FORGED U PART U型卡

SLR051

ITEM NO.	WEIGHT (KG)	A±1	B±0.5	C	D±1	ΦD±0.5	L±3
1#	0.11	32	35	5/8-13	23	12.6	63
2#	0.15	32	14	5/8-18	23	12.6	59.5

- ◆ Forged super alloy steel- Quenched and Tempered
- ◇ 高强度合金材料经合金钢锻造而成，经过热处理
- ◆ Breakage test
- ◇ 对称一批次产品进行严格的材料破坏测试
- ◆ 100% magnetic crack detection
- ◇ 100% 进行磁粉探伤



SLR681-FORGED TOW HOOK 牵引钩

SLR681

ITEM NO.	WEIGHT (KG)	WLL (T)	BL (T)	A±2	B±2	H±2	H±3	L±3	Φ±2
SLR-681	2.4			22	40	115	62	242	32



LIFTING TOOLS

起重吊具系列

- ◆ Large throat-opening and small cross-area
- ◆ 大开口、小截面、面积狭缝和吸入。
- ◆ Forged alloy steel/high strength and good ductility
- ◆ 优质合金钢锻造而成，强度高，延展性好。
- ◆ Only for general hoist. Not for overhead lifting.
- ◆ 仅用于一般起吊，不能用于头上起重作业。
- ◆ Surface finish (表面处理) :
- ◆ Powder paint (漆) (粉漆)
- ◆ Colour (颜色) :
- ◆ Red (红色) : RAL3009 / Yellow (黄色) : RAL1003



SLR713-FORGED LIFTING TOOL

水平吊吊具

SLR713

ITEM NO.	WEIGHT (KG)	WLL (T)	BL (T)	M±2	N±2	W±2	Y±3	K±3	L±3
SLR-713-3T	7.2	3	12	107	91	106	191	195	230
SLR-713-5T	11.42	5	20	110	94	111	240	246.5	281


Lifting force is 4 times the working load limit 起吊能力是工作能力的4倍

Regularly inspect 定期检查 - WLL 2T 以上

LIFTING TOOLS

起重吊具系列

- ◆ Forged carbon steel
- ◆ 锻钢锻造而成
- ◆ Quenched and Tempered
- ◆ 经过热处理
- ◆ Breakage test
- ◆ 对每一批次产品进行严格的破坏性测试



SLR646-LIFTING TOOLS

钳座吊钩

SLR646


ITEM NO.	WEIGHT (KG)	WLL (T)	A±1	B±1	C±1	D±0.5	E±0.5	H±1	Φ±0.5	L±2
SLR-646-3T	4.28	3	60	100	20	30	24	91	43.5	117



WARNING 警告: Do not use lifting tools with cracks or damage. Do not use lifting tools with cracks or damage.

LARGE OPENING HOOKS 高强度细筋大开口钩

- ◆ Large throat opening and small cross area
- ◇ 大开口，小截面，便于吊装和卸车
- ◆ Forged alloy steel, High strength and good ductility
- ◇ 铁合金锻造而成，高强度，韧性好
- ◆ Only for general hoisting for overhead lifting
- ◇ 仅用于一般起吊，不得用于点上起吊作业。



SLR207-ALLOY FORGED LARGE OPENING HOOK
合金钢锻造大开口钩

SLR207


ITEM CODE	WEIGHT (Kg)	WLL (T)	B.L (T)	D±1	N±2	E±2	B±2	L1±3	L2±3
SLR207-1T	0.44	1	4	11	24	52.5	107.2	181.5	152
SLR207-1.5T	1.27	1.5	3	26	40	59	117	272	230

Forging hook (参照图202SLR150~1.5T为制) : 5X005 WLL 1.5T Q235 SLR-BATCH FURNACE 制造



FORGED SWIVEL HOOK 旋转钩

- ◆ Forged alloy steel or carbon steel
- ◆ 合金钢或碳钢锻造而成
- ◆ Breakage test
- ◆ 对每一批产品进行严格的破坏性测试
- ◆ 100% magnetic crack detection
- ◆ 100% 进行磁粉探伤
- ◆ With safety latch
- ◆ 含保险舌扣
- ◆ Surface finish (表面处理) : Powder coated (喷漆)
- ◆ Colour code(颜色) : Red(红色)RAL3020
Yellow(黄色)RAL1000
- ◆ Alloy steel Ultimate load is 4.5 times the Working Load Limit
- ◆ 合金钢货钩: 破断拉力为工作拉力的4.5倍
- ◆ Carbon steel Ultimate load is 5 times the Working Load Limit
- ◆ 碳钢货钩: 破断拉力为工作拉力的5倍
- ◆ Can be Mounted under Non-load Conditions
- ◆ 安装时必须在无负载条件下进行(如有疑问)




SLR132-FORGED SWIVEL HOOK 旋转钩

SLR132

ITEM NO.	WEIGHT (kg)	ALLOY		CARBON		A±1	B±2	E±2	H±0.5	K±4	L±5	M±1
		WLL (T)	B.L (T)	WLL (T)	B.L (T)							
SLR-132-A0.75T/C0.6T	0.3	0.75	0.99	0.5	0.5	30	22.5	17	6	110	132	18
SLR-132-A1T/C0.75T	0.34	1	1.3	0.75	0.75	32	22.5	17	6	108	138	18
SLR-132-A1.5T/C1T	0.64	1.5	1.95	1	1	37.5	25.5	22.5	12	160	191.5	22.5
SLR-132-A2T/C1.5T	1.24	2	2.6	1.5	1.5	42.5	28	24.5	15.5	185	210	24
SLR-132-A2.5T/C2T	1.74	2.5	3.25	2	2	47.5	30	26	18.5	193	250	25
SLR-132-A3T/C2.5T	2.3	3	3.9	2.5	2.5	48	32	28.5	19	191	248	26
SLR-132-A3.5T/C3T	2.9	3.5	4.55	3	3	54	33	30	21.5	243.5	245	34
SLR-132-A4T/C3.5T	4	4	5.2	3.5	3.5	56	34	31	22	247	247	34
SLR-132-A4.5T/C4T	4.3	4.5	5.85	4	4	57	35	32	23	247	247	34
SLR-132-A5T/C4.5T	5.0	5	6.5	4.5	4.5	58	36	33	24	247	247	34
SLR-132-A5.5T/C5T	5.7	5.5	7.15	5	5	59	37	34	25	247	247	34
SLR-132-A6T/C5.5T	6.4	6	7.8	5.5	5.5	60	38	35	26	247	247	34
SLR-132-A6.5T/C6T	7.1	6.5	8.45	6	6	61	39	36	27	247	247	34
SLR-132-A7T/C6.5T	7.8	7	9.1	6.5	6.5	62	40	37	28	247	247	34
SLR-132-A7.5T/C7T	8.5	7.5	9.75	7	7	63	41	38	29	247	247	34
SLR-132-A8T/C7.5T	9.2	8	10.4	7.5	7.5	64	42	39	30	247	247	34
SLR-132-A8.5T/C8T	9.9	8.5	11.05	8	8	65	43	40	31	247	247	34
SLR-132-A9T/C8.5T	10.6	9	11.7	8.5	8.5	66	44	41	32	247	247	34
SLR-132-A9.5T/C9T	11.3	9.5	12.35	9	9	67	45	42	33	247	247	34
SLR-132-A10T/C9.5T	12.0	10	13.0	9.5	9.5	68	46	43	34	247	247	34
SLR-132-A10.5T/C10T	12.7	10.5	13.65	10	10	69	47	44	35	247	247	34
SLR-132-A11T/C10.5T	13.4	11	14.3	10.5	10.5	70	48	45	36	247	247	34
SLR-132-A11.5T/C11T	14.1	11.5	14.95	11	11	71	49	46	37	247	247	34
SLR-132-A12T/C11.5T	14.8	12	15.6	11.5	11.5	72	50	47	38	247	247	34
SLR-132-A12.5T/C12T	15.5	12.5	16.25	12	12	73	51	48	39	247	247	34
SLR-132-A13T/C12.5T	16.2	13	16.9	12.5	12.5	74	52	49	40	247	247	34
SLR-132-A13.5T/C13T	16.9	13.5	17.55	13	13	75	53	50	41	247	247	34
SLR-132-A14T/C13.5T	17.6	14	18.2	13.5	13.5	76	54	51	42	247	247	34
SLR-132-A14.5T/C14T	18.3	14.5	18.85	14	14	77	55	52	43	247	247	34
SLR-132-A15T/C14.5T	19.0	15	19.5	14.5	14.5	78	56	53	44	247	247	34
SLR-132-A15.5T/C15T	19.7	15.5	20.15	15	15	79	57	54	45	247	247	34
SLR-132-A16T/C15.5T	20.4	16	20.8	15.5	15.5	80	58	55	46	247	247	34
SLR-132-A16.5T/C16T	21.1	16.5	21.45	16	16	81	59	56	47	247	247	34
SLR-132-A17T/C16.5T	21.8	17	22.1	16.5	16.5	82	60	57	48	247	247	34
SLR-132-A17.5T/C17T	22.5	17.5	22.75	17	17	83	61	58	49	247	247	34
SLR-132-A18T/C17.5T	23.2	18	23.4	17.5	17.5	84	62	59	50	247	247	34
SLR-132-A18.5T/C18T	23.9	18.5	24.05	18	18	85	63	60	51	247	247	34
SLR-132-A19T/C18.5T	24.6	19	24.7	18.5	18.5	86	64	61	52	247	247	34
SLR-132-A19.5T/C19T	25.3	19.5	25.35	19	19	87	65	62	53	247	247	34
SLR-132-A20T/C19.5T	26.0	20	26.0	19.5	19.5	88	66	63	54	247	247	34
SLR-132-A20.5T/C20T	26.7	20.5	26.65	20	20	89	67	64	55	247	247	34
SLR-132-A21T/C20.5T	27.4	21	27.3	20.5	20.5	90	68	65	56	247	247	34
SLR-132-A21.5T/C21T	28.1	21.5	27.95	21	21	91	69	66	57	247	247	34
SLR-132-A22T/C21.5T	28.8	22	28.6	21.5	21.5	92	70	67	58	247	247	34
SLR-132-A22.5T/C22T	29.5	22.5	29.25	22	22	93	71	68	59	247	247	34
SLR-132-A23T/C22.5T	30.2	23	29.9	22.5	22.5	94	72	69	60	247	247	34
SLR-132-A23.5T/C23T	30.9	23.5	30.55	23	23	95	73	70	61	247	247	34
SLR-132-A24T/C23.5T	31.6	24	31.2	23.5	23.5	96	74	71	62	247	247	34
SLR-132-A24.5T/C24T	32.3	24.5	31.85	24	24	97	75	72	63	247	247	34
SLR-132-A25T/C24.5T	33.0	25	32.5	24.5	24.5	98	76	73	64	247	247	34
SLR-132-A25.5T/C25T	33.7	25.5	33.15	25	25	99	77	74	65	247	247	34
SLR-132-A26T/C25.5T	34.4	26	33.8	25.5	25.5	100	78	75	66	247	247	34
SLR-132-A26.5T/C26T	35.1	26.5	34.45	26	26	101	79	76	67	247	247	34
SLR-132-A27T/C26.5T	35.8	27	35.1	26.5	26.5	102	80	77	68	247	247	34
SLR-132-A27.5T/C27T	36.5	27.5	35.75	27	27	103	81	78	69	247	247	34
SLR-132-A28T/C27.5T	37.2	28	36.4	27.5	27.5	104	82	79	70	247	247	34
SLR-132-A28.5T/C28T	37.9	28.5	37.05	28	28	105	83	80	71	247	247	34
SLR-132-A29T/C28.5T	38.6	29	37.7	28.5	28.5	106	84	81	72	247	247	34
SLR-132-A29.5T/C29T	39.3	29.5	38.35	29	29	107	85	82	73	247	247	34
SLR-132-A30T/C29.5T	40.0	30	39.0	29.5	29.5	108	86	83	74	247	247	34
SLR-132-A30.5T/C30T	40.7	30.5	39.65	30	30	109	87	84	75	247	247	34
SLR-132-A31T/C30.5T	41.4	31	40.3	30.5	30.5	110	88	85	76	247	247	34
SLR-132-A31.5T/C31T	42.1	31.5	40.95	31	31	111	89	86	77	247	247	34
SLR-132-A32T/C31.5T	42.8	32	41.6	31.5	31.5	112	90	87	78	247	247	34
SLR-132-A32.5T/C32T	43.5	32.5	42.25	32	32	113	91	88	79	247	247	34
SLR-132-A33T/C32.5T	44.2	33	42.9	32.5	32.5	114	92	89	80	247	247	34
SLR-132-A33.5T/C33T	44.9	33.5	43.55	33	33	115	93	90	81	247	247	34
SLR-132-A34T/C33.5T	45.6	34	44.2	33.5	33.5	116	94	91	82	247	247	34
SLR-132-A34.5T/C34T	46.3	34.5	44.85	34	34	117	95	92	83	247	247	34
SLR-132-A35T/C34.5T	47.0	35	45.5	34.5	34.5	118	96	93	84	247	247	34
SLR-132-A35.5T/C35T	47.7	35.5	46.15	35	35	119	97	94	85	247	247	34
SLR-132-A36T/C35.5T	48.4	36	46.8	35.5	35.5	120	98	95	86	247	247	34
SLR-132-A36.5T/C36T	49.1	36.5	47.45	36	36	121	99	96	87	247	247	34
SLR-132-A37T/C36.5T	49.8	37	48.1	36.5	36.5	122	100	97	88	247	247	34
SLR-132-A37.5T/C37T	50.5	37.5	48.75	37	37	123	101	98	89	247	247	34
SLR-132-A38T/C37.5T	51.2	38	49.4	37.5	37.5	124	102	99	90	247	247	34
SLR-132-A38.5T/C38T	51.9	38.5	50.05	38	38	125	103	100	91	247	247	34
SLR-132-A39T/C38.5T	52.6	39	50.7	38.5	38.5	126	104	101	92	247	247	34
SLR-132-A39.5T/C39T	53.3	39.5	51.35	39	39	127	105	102	93	247	247	34
SLR-132-A40T/C39.5T	54.0	40	52.0	39.5	39.5	128	106	103	94	247	247	34
SLR-132-A40.5T/C40T	54.7	40.5	52.65	40	40	129	107	104	95	247	247	34
SLR-132-A41T/C40.5T	55.4	41	53.3	40.5	40.5	130	108	105	96	247	247	34
SLR-132-A41.5T/C41T	56.1	41.5	53.95	41	41	131	109	106	97	247	247	34
SLR-132-A42T/C41.5T	56.8	42	54.6	41.5	41.5	132	110	107	98	247	247	34
SLR-132-A42.5T/C42T	57.5	42.5	55.25	42	42	133	111	108	99	247	247	34
SLR-132-A43T/C42.5T	58.2	43	55.9	42.5	42.5	134	112	109	100	247	247	34
SLR-132-A43.5T/C43T	58.9	43.5	56.55	43	43	135	113	110	101	247	247	34
SLR-132-A44T/C43.5T	59.6	44	57.2	43.5	43.5	136	114	111	102	247	247	34
SLR-132-A44.5T/C44T	60.3	44.5	57.85	44	44	137	115	112	103	247	247	34
SLR-132-A45T/C44.5T	61.0	45	58.5	44.5	44.5	138	116	113	104	247	247	34
SLR-132-A45.5T/C45T	61.7	45.5	59.15	45	45	139	117	114	105	247	247	34
SLR-132-A46T/C45.5T	62.4	46	59.8	45.5	45.5	140	118	115	106	247	247	34
SLR-132-A46.5T/C46T	63.1	46.5	60.45	46	46	141	119	116	107	247	247	34
SLR-132-A47T/C46.5T	63.8	47	61.1	46.5	46.5	142	120	117	108	247	247	34
SLR-132-A47.5T/C47T	64.5	47.5	61.75	47	47	143	121	118	109	247	247	34
SLR-132-A48T/C47.5T	65.2	48	62.4	47.5	47.5	144	122	119	110	247	247	34
SLR-132-A48.5T/C48T	65.9	48.5	63.05	48	48	145	123	120	111	247	247	34
SLR-132-A49T/C48.5T	66.6	49	63.7	48.5	48.5	146	124	121	112	247	247	34
SLR-132-A49.5T/C49T	67.3	49.5	64.35	49	49	147	125	122	113	247	247	34
SLR-132-A50T/C49.5T	68.0	50	65.0	49.5	49.5	148	126	123	114	247	247	34
SLR-132-A50.5T/C50T	68.7	50.5	65.65	50	50	149	127	124	115	247	247	34
SLR-132-A51T/C50.5T	69.4	51	66.3	50.5	50.5	150	128	125	116	247	247	34
SLR-132-A51.5T/C51T	70.1	51.5	66.95	51	51	151	129	126</				

FORGED SWIVEL HOOK 锻造旋转钩

- ◆ Forged super alloy steel- Quenched and Tempered
 - 锻造高强度合金钢经淬火及回火处理
 - ◆ Breakage test
 - 对每一批次产品进行严格的破坏性测试
 - ◆ 100% magniflux crack detection
 - 100% 进行磁粉探伤
 - ◆ With safety load
 - 含保险负荷
 - ◆ Surface finish: (表面处理): Powder painted (喷漆)
 - ◆ Colour code (颜色): Red (红色)RAL3020
- ◆ Alloy steel Ultimate load is 4.5 times the Working Load Limit
 ○ 合金钢负荷: 破断力为工作拉力的4.5倍。
- ◆ Carbon steel Ultimate load is 5 times the Working Load Limit
 ○ 碳钢负荷: 破断力为工作拉力的5倍。
- ◆ Can be Rotated under Non-load Condition
 ○ 在未受负载下可旋转(非受方向)



NEW! 改进型



SLR554-FORGED SWIVEL HOOK

旋转钩

SLR554


ITEM NO.	WEIGHT (kg)	ALLOY		CARBON		A*1	B*2	E*2	H*0.6	K*4	L*5	M*1
		WLL (T)	B.L (T)	WLL (T)	B.L (T)							
SLR-554-A1TC0.75T	6.34	1	4.5	0.75	3.75	32	26.5	32	9	110	104	30
SLR-554-A1.5TC1T	6.94	1.5	6.75	1	5	32.5	29.5	32.5	12	130	133.5	37.5
SLR-554-A2.7TC1.5T	7.62	2	9	1.5	7.5	44.4	35	34	15.3	155	153	37
SLR-554-A3.7TC2T	1.24	3	13.5	2	10	42.5	33	26	15.8	150	200	33
SLR-554-A5.7TC3T	2.25	5	22.5	3	15	50	39	34	16	161	261	33
SLR-554-A7.7TC5T	4	7	31.5	5	25	64	53	43	21.5	243.5	313	34
SLR-554-A11TC7.5T	7.02	11	49.5	7.5	37.5	70	61	50	26	275	364	41.5

Tagging mark 吊钩标记: 规格: SW-1T-TC-0.75-BATCH#1680001 (批号);
 合金钢: ALLOY-AL-1T-TC-SLR-BATCH#1680001 (批号);



SWIVEL HOOK 旋转钩

- ◆ Forged super carbon steel - Quenched and Tempered
- ◇ 高强度高韧性特殊碳钢锻造而成，经过热处理
- ◆ 100% magnetic crack detection
- ◇ 100%进行磁粉探伤
- ◆ Surface finish (表面处理) :
- ◇ Powder plating (粉塑)
- ◆ Colour code (色号) :
- ◇ Red (红色) RAL 3020 / Yellow (黄色) RAL 1003
- ◆ Can be Rotated under Non-load Conditions
- ◇ 非满载条件下可旋转钩的方向



SLR067-
LD7785/吊钩旋转钩

SLR067

ITEM NO.	WEIGHT (KG)	WLL (T)	BL (T)	A±1.5	B±1	M±2	E±1	R±1	L±2.5
SLR-067-1.6T	1.7	1.5	9	45	85	95	24.5	17	211
SLR-067-2T		2	10	45	45	100	30	17	225

- ◆ Forged super carbon steel - Quenched and Tempered
- ◇ 高强度高韧性特殊碳钢锻造而成，经过热处理
- ◆ 100% magnetic crack detection
- ◇ 100%进行磁粉探伤
- ◆ Surface finish (表面处理) :
- ◇ Powder plating (粉塑)
- ◆ Colour code (色号) :
- ◇ Red (红色) RAL 3020 / Yellow (黄色) RAL 1003
- ◆ Can be Rotated under Non-load Conditions
- ◇ 非满载条件下可旋转钩的方向



SLR508-LD2805吊钩旋转钩

SLR508

ITEM NO.	WEIGHT (KG)	WLL (T)	BL (T)	A±2	B±2.5	E±1.5	G±2	L±4
1.6T	1.47	1.6	5	45	22	35	48	214.5




WARNING 警告: This is a lifting device and can be dangerous if not used.

SWIVEL HOOK

旋转货钩

- ◆ Forged alloy steel or carbon steel-Quenched and Tempered
- ◇ 合金钢或碳钢锻造，严格的淬火和回火保证了强度和韧性
- ◆ 100% magnifying crack detection
- ◇ 100%进行裂纹探伤
- ◆ Surface finish (表面处理):
- ◇ Powder painted(涂层)
- ◆ Colour code(颜色):
- ◇ Red(红色) RAL3020 / Yellow(黄色) RAL1015



SLR372-SWIVEL HOOK

旋转货钩

SLR372

ITEM NO.	WEIGHT (KG)	WLL (T)	BL (T)	A	B	E	H	K	L
SLR-372-0.8T	0.48	0.8	4	30±1	28±2	36±1±2	10±1	123±2	191±3
SLR-372-1T	0.52	1	5	30±1.0	28±2	37±1±2	10±1	117±2.5	192±3
SLR-372-2T	1.02	2	10	40±2	40±1	32±2±3	17±1.5	174±4	220±5

SPECIAL 322C SWIVEL HOOK

异型 322C 旋转钩

- ◆ Forged alloy steel or carbon steel-Quenched and Tempered
- ◇ 合金钢或碳钢锻造，严格的淬火和回火保证了强度和韧性
- ◆ 100% magnifying crack detection
- ◇ 100%进行裂纹探伤
- ◆ Surface finish (表面处理):
- ◇ Powder painted(涂层)
- ◆ Colour code(颜色):
- ◇ Red(红色) RAL3020 / Yellow(黄色) RAL1015



SLR383-SPECIAL 322C SWIVEL HOOK


异型 322C 旋转钩

SLR383

ITEM NO.	WEIGHT (KG)	WLL (T)		A±1	B	C	E	L	K
		STEEL	ALLOY						
SLR-383-0.8T	0.57	0.8	1.25	32±1.5	27.5±2	50±2	23±1±2	148±3	118±3
SLR-383-1T	0.52	1	1.6	32±1.0	23±3	67±3	21±1±2	162±3	123±3
SLR-383-1.6T	1.24	1.6	2.5	44±2	36±5	71±3	28±2±3	185±4	153±4
SLR-383-2T	1.35	2	3.2	44±2	39±5	71±3	31±2±3	210±5	165±5

SWIVEL HOOK 旋转钩

- ◆ Forged super alloy steel- Quenched and Tempered
- ◇ 高强度合金材料经淬火和回火处理
- ◆ Individually proof test at 2.5 times Working Load Limit
- ◇ 每件钩工作力为2.5倍额定载荷进行测试
- ◆ Fatigue tested at 1.5 times Working Load Limit for 20000 cycles
- ◇ 钩体进行20000次疲劳测试
- ◆ Breakage test ◇ 对每一批次产品进行严格的材料破坏测试
- ◆ 100% magnetic crack detection ◇ 100% 进行磁粉探伤
- ◆ Can be Rotated under Non-load Conditions
- ◇ 非满载条件下可旋转钩体方向



SLR795-SWIVEL HOIST HOOK 旋转钩

SLR795

ITEM NO.	WEIGHT (kg)	WLL (T)	B.L (T)	A±1	B±1	C±2.5	M±1	N±1	E±1.5	H±0.5	L±3	L1±2.5
8-SLR795-6	0.44	1.21	5	34	32	32	78	16.5	24.8	22	102	116.5
8-SLR795-7	0.6	1.5	6	35	34	32	84	19	25.3	23	132	146
8-SLR795-8	0.9	2	8	36	34	32	84	19	25.3	23	131	146
8-SLR795-9	1.26	2.5	10	47	39	42	95	23	29	27	211	175
8-SLR795-10	1.52	3.2	12.5	47	39	42	110	24	27	21	210.5	171

SHANK HOOK & BLOCK HOOK 直杆钩

- ◆ Forged carbon steel-Quenched and tempered
- ◇ 优质碳钢锻造，经过热处理
- ◆ Breakage test
- ◇ 对每一批次产品进行严格的材料破坏测试
- ◆ 100% magnetic crack detection
- ◇ 100% 进行磁粉探伤



SLR047-SHANK HOOK 杆式钩

SLR047

ITEM CODE	WEIGHT (kg)	WLL (T)	M±1	B±2	C±2	E±2	L±3
SLR047-250	0.21	0.25	12	63	21	16	126
SLR047-500	0.59	0.5	14	69	30	19	134
SLR047-1000	1.57	1	16	81	39	29	153
SLR047-2500	3.14	2	20	114	42	34	156


Remarks: 1. 重量规格SLR047-2500kg为例外，WLL为2.5T



WARNING 警告 This is a lifting equipment and can be dangerous, use with care.

FORGED GRAB HOOK 羊角抓钩

- ◆ Forged alloy steel or carbon steel. ◇ 合金钢或碳钢锻造而成
- ◆ Quenched and Tempered ◇ 经过热处理
- ◆ Not for lifting only for loading and unloading
- ◇ 不能用于起重，仅用于装卸和卸载
- ◆ Breakage load ◇ 对每一件次产品进行严格的抽样破坏测试
- ◆ 100% magnetic crack detection ◇ 100% 进行磁粉探伤
- ◆ G43 Ultimate load is 3 times the Working Load Limit
- ◇ 43级：极限负荷是工作负荷的3倍
- ◆ G70 Ultimate load is 4 times the Working Load Limit
- ◇ 70级：极限负荷是工作负荷的4倍



SLR123-G70 AND G43 CLEVIS GRAB HOOK
70级和43级羊角抓钩


SLR123

ITEM NO.	WEIGHT (lbs)	WLL (lbs)		A ±1	B ±1.5	E ±0.5	H ±1	K ±1	L ±2	M ±2	N ±1
		CARBON ALLOY									
SLR-123-114	0.38	2090	3150	5.5	26	9.5	12	45	75.5	47.6	12.5
SLR-123-916	0.42	2650	4700	11.5	29	11.5	25	54	95.5	54.7	13
SLR-123-218	1	5430	9500	12.5	35	12.2	31	64.5	113.5	67.6	13
SLR-123-716	1.5	7250	12700	17	42	14.5	33.5	70	124	76.9	13
SLR-123-112	2.25	9350	15300	19.5	47	17	36.5	85	148.5	91	20.5
SLR-123-516	4.41	18100	25000	25	56	20	49	102.5	177	104.5	22
SLR-123-314	0.5	30200	34250	24	53.5	24	54	118	207.5	150.5	23.3

- ◆ Please note: (请留意) : (lbs) : Lbs Weight for the Heat Treat Batch Number (批号) , (kg) : G70 FORGED 14 SLR-BATCH NUMBER (批号)

ALLOY CLEVIS GRAB HOOK 澳式70级合金钢羊角抓钩

- ◆ Grade 70, only for loading and unloading, hook to be used for lifting
- ◇ 70级产品，仅用于装卸和卸载，钩不能用于起重
- ◆ Forged alloy steel - Q, quenched and Tempered
- ◇ 合金钢锻造，严格热处理保证了强度和韧性
- ◆ Suitable for G70 transport chain
- ◇ 配合70级链条使用



SLR099-G70 ALLOY CLEVIS GRAB HOOK
澳式70级合金钢羊角抓钩

SLR099

ITEM CODE	WEIGHT (KG)	LC (KG)	BL (KG)	A ±0.5	B ±1	E ±0.5	L ±1.2
SLR-099-6mm	0.23	2300	4000	5.5	26	9.5	93
SLR-099-8mm	0.38	2616	4600	12	28	13	91
SLR-099-10mm	0.42	2520	4200	15.5	35	13.5	115
SLR-099-13mm	1.24	5500	15000	15	45.5	13	152

LC=LOAD CAPACITY BL=BREAKAGE LOAD BL=LC X 2 TIMES 破断是工作负荷的2倍



FORGED GRAB HOOK 眼型抓钩

- ◆ Forged alloy steel or carbon steel ◯ 合金钢或碳素钢锻造
- ◆ Quenched and Tempered ◯ 经过热处理
- ◆ Part for lifting only for loading and unloading ◯ 不能用于起重，仅用于装卸和搬运
- ◆ Breakage test ◯ 对每一批次产品进行严格的抽样破坏测试
- ◆ 100% magnetic crack detection ◯ 100% 进行磁粉探伤
- ◆ Q435, Ultimate load is 3 times the Working Load Limit ◯ 4.3级：极限负荷是工作拉力的3倍
- ◆ Q705, Ultimate load is 4 times the Working Load Limit ◯ 7.0级：极限负荷是工作拉力的4倍



SLR125—FORGED GRAB HOOK
眼型抓钩

SLR125

ITEM NO.	WEIGHT (LBS)	WLL (lbs)		K±1	H±1	Ø±0.5	E±0.5	L±2	M±2	N±1
		CARBON	ALLOY							
SLR-125-1/4	0.31	2400	3150	11.5	10.5	11	5	27	48	11.5
SLR-125-5/16	0.57	4900	4700	57.5	23.8	14	11.5	90	57.5	14.5
SLR-125-3/8	0.85	6400	6800	68	25.3	17	13	104	65	17.5
SLR-125-7/16	1.22	7200	8200	77	32.5	19.5	15	122	81	19
SLR-125-1/2	1.72	9200	11500	85.5	37.4	22	17	145	90	21
SLR-125-5/8	2.2	13000	15500	116	44.5	30	21	180	110.5	24
SLR-125-3/4	3.11	20200	24700	143.5	54.5	35	25	211	153.5	34

- ◆ Forging mark (锻造标识) : Q435-Q455/FORGED 1/4 SLR HOOK TEST-BATCH NUMBER (批号)
Q705-Q715/FORGED 5/4 SLR HOOK TEST-BATCH NUMBER (批号)



WARNING 警告: This is a lifting tool. It is not to be used for any other purpose.

CLEVIS SLIP HOOK 羊角滑钩

- ◆ Forged super carbon alloy steel- Quenched and Tempered
- ◇ 高强度易锻性材料-合金钢锻造而成，经过热处理
- ◆ Not for lifting, only for lashing or pulling
- ◇ 不能用于起重，仅用于捆绑和牵引
- ◆ 100% magnaflex crack detection
- ◇ 100%进行磁粉探伤
- ◆ Surface finish (表面处理) : ◊ Powder blasted (抛丸)
- ◆ Colour code (色号) : ◊ Red (红色) RAL 3000
- ◇ Yellow (黄色) RAL 1003



SLR124-CLEVIS SLIP HOOK

羊角滑钩

SLR124

ITEM NO.	WEIGHT (LBS)	WLL (LBS) (4:1)		A ±2	B ±2	E ±2	L ±3	M ±3
		CARBON	ALLOY					
SLR-124-1/4	0.55	1050	2750	10.9	7.7	29.5	109	12.3
SLR-124-3/16	0.52	2875	4300	12	35	25	114	14.5
SLR-124-3/8	1.1	4000	6150	14.5	32	32	137.5	17.5
SLR-124-7/16	3.08	6000	7000	15.5	44	30	147	21
SLR-124-1/2	2.60	6500	9000	19	48	40.5	156	23
SLR-124-5/8	4.85	6500	15500	15.5	58.7	51	200.5	29
SLR-124-3/4	11.35	12100	15500	20	71	64.5	257	38.5

◆ Magnaflex (MAGNETIC) : ITEM 50114 FORGED 15451410501 TEST FORGED 114

- ◆ Forged super carbon alloy steel- Quenched and Tempered
- ◇ 高强度易锻性材料-合金钢锻造而成，经过热处理
- ◆ Not for lifting, only for lashing or pulling
- ◇ 不能用于起重，仅用于捆绑和牵引
- ◆ 100% magnaflex crack detection
- ◇ 100%进行磁粉探伤
- ◆ Surface finish (表面处理) : ◊ Powder blasted (抛丸)
- ◆ Colour code (色号) : ◊ Red (红色) RAL 3000
- ◇ Yellow (黄色) RAL 1003



SLR127-CLEVIS SLIP HOOK

羊角滑钩

SLR127


ITEM NO.	WEIGHT (LBS)	WLL (LBS) (4:1)		A ±2	B ±2	E ±2	L ±3	M ±3
		CARBON	ALLOY					
SLR-127-1/4	0.55	1050	2750	11	27	21.5	102	10.5
SLR-127-5/16	0.77	2675	4300	12.5	33	26	117	7.9
SLR-127-3/8	1.28	4000	6200	15	38	42	134	10.5
SLR-127-7/16	3.35	5000	7000	14.5	44	39	151.5	11.1
SLR-127-1/2	3.05	6500	10900	19	48	37.5	168	124.5
SLR-127-5/8	8.15	10500	15500	18.5	58.3	45.5	214.5	143
SLR-127-3/4	12.4	12500	19250	20	71	61	230	159

◆ Magnaflex (MAGNETIC) : ITEM 50114 FORGED 15451410501 TEST FORGED 114



ALLOY CLEVIS SLIP HOOK 澳式70级合金钢羊角滑钩

- ◆ Grade 70, only for lashing and pulling. Never to be used for lifting.
- ◆ 70级产品, 仅用于捆绑和拉紧, 绝不可用于起重!
- ◆ Forged alloy steel - Quenched and Tempered
- ◆ 合金钢锻造, 严格的热处理保证了强度和韧性
- ◆ Suitable for ISO transport chain
- ◆ 配合70级链条使用
- ◆ Regular mark (常规标记): - 6MM L03900K03 - 670



SLR100-G70 ALLOY CLEVIS SLIP HOOK

澳式70级合金钢羊角滑钩


SLR100

ITEM NO.	WEIGHT (KG)	WLL (T)	B.L (T)	A±0.5	B±1	E±1	M±0.5	L±1.2
SLR-100-6MM	0.27	2.8	4.6	9	69	10	17.5	90.5
SLR-100-8MM	0.34	3.8	7.8	11	70	20	14.5	191
SLR-100-10MM	0.4	5	12	12	85	30	10	120.5
SLR-100-12MM	1.135	5	12	18	121.5	42.5	25	107.5

(L)=LOAD CAPACITY B.=BREAKAGE LOAD B.L.=LIFTING TIMES 吨级指工作负荷吨数

CHAIN HANDLE 链子拉手

- ◆ Forged super alloy steel - Quenched and Tempered
- ◆ 高强度合金钢锻造并热处理而成, 强度高且耐用



SLR426-CHAIN HANDLE

链子拉手

SLR426

ITEM NO.	WEIGHT (Kg)	A	Ø	L
SLR-426-4mm	0.040	6	6.5	26
SLR-426-5mm	0.05	10	7	50.8
SLR-426-6mm	0.11	11	7.5	57.5
SLR-426-7mm	0.115	12.5	8	142
SLR-426-8mm	0.145	13.5	10	154



WARNING 警告 This is a lifting equipment and can be dangerous if not used properly.